

|   |         |  |         |
|---|---------|--|---------|
| Anti-Seize Compounds .....                | 99,100  | Layout Fluids .....                                      | 142     |
| Belt Dressings .....                      | 109,110 | Leak Detectors.....                                      | 80      |
| Car Waxes, Polishes & Protectants .....   | 142     | Lubricating Product Accessories .....                    | 132     |
| Chain & Cable Lubricants.....             | 113,114 | Magnetic Particles .....                                 | 80,81   |
| Cleaners & Degreasers .....               | 85,86   | Multi-Purpose Lubricants .....                           | 110,111 |
| Cleaning Products Accessories.....        | 98      | Oilers & Sprayers .....                                  | 131,132 |
| Coatings .....                            | 138,139 | Oils.....  | 128,129 |
| Corrosion Inhibitors .....                | 104,105 | Paint Brushes .....                                      | 140     |
| Cutting & Tapping Fluids.....             | 116,117 | Paint Rollers & Covers.....                              | 140,141 |
| De-Icers .....                            | 142     | Paint Stripers .....                                     | 141     |
| Drill Collar & Tool Joint Compounds.....  | 113     | Paint Trays & Liners.....                                | 141     |
| Drop Cloths .....                         | 139     | Paints.....  | 132,133 |
| Dry Lubes .....                           | 107,108 | Penetrant Kits .....                                     | 83,84   |
| Finding Paste.....                        | 142     | Penetrants .....   | 81,82   |
| Grease .....                              | 118,119 | Silicone Lubricants .....                                | 114,115 |
| Grease Fittings .....                     | 124     | Spray Gun Parts & Accessories.....                       | 141     |
| Grease Gun Accessories .....              | 128     | Spray Guns .....   | 141     |
| Grease Gun Hoses, Extensions & Adapters . | 127,128 | Starting Fluids .....                                    | 118     |
| Grease Guns .....                         | 124,125 | Surface Irregularity Testing<br>Product Accessories..... | 84,85   |
| Inks .....                                | 139     |  |         |
| Insect Killers .....                      | 98,99   |  |         |



**INDUSTRIAL**



## SNOOP

### Leak Detectors

**Features:**

- Non-Toxic, non-flammable
- Does not collect dust
- Does not contain chlorine, aliphatic amines, or ammonium compounds

**Physical Form:** Liquid



| SKU            | Capacity Vol. |
|----------------|---------------|
| 747-8OZ-SNOOP  | 8 oz          |
| 747-1GAL-SNOOP | 1 gal         |
| 747-1GAL-SNOOP | 1 gal         |



### Leak Test Solution

**Features:**

- Pinpoints leaks with visible bubbles
- Oxygen safe – dries clean
- For use with manifold equipment



| SKU        | Capacity Vol. |
|------------|---------------|
| 312-LT-200 | 1 gal         |

## MAGNAFLUX®

### Magnaflux® Dry Method Magnetic Particles

**Features:**

- General purpose dry method particles
- Used on dark surfaces for optimum contrast




| SKU            | Capacity Wt. | Color  |
|----------------|--------------|--------|
| 387-01-1780-69 | 10 lb        | Red    |
| 387-01-1716-87 | 45 lb        | Gray   |
| 387-01-1732-87 | 45 lb        | Yellow |
| 387-01-1780-87 | 45 lb        | Red    |

### Magnaglo® 14A Wet Method Fluorescent Magnetic Particles

**Features:**

- Fluorescent wet method particles
- Most widely used, general purpose
- Highly sensitive and meets all wet method specifications
- Suspension medium: water or oil

**Color:** Brown



| SKU            | Capacity Wt. | Quantity   |
|----------------|--------------|------------|
| 387-01-0130-71 | 1 lb         | 6 per pack |
| 387-01-0130-57 | 1 lb         |            |

### Magnaglo® 14A Wet Method Redi-Bath™ Fluorescent Premix Concentrates

**Features:**

- Fluorescent wet method solution
- Concentrated mix of 14A particles, water, wetting agent, and corrosion inhibitor
- Easy to use, just add concentrate to water

**Color:** Brown



| SKU            | Capacity Wt. | Quantity   |
|----------------|--------------|------------|
| 387-01-9130-41 | 27 oz        | 6 per pack |

### Magnaglo® 14AM Fluorescent Premixed Prepared Bath w/Carrier II

**Features:**

- Ready to use fluorescent wet method bath
- Prepared bath of 14A particles and Carrier II oil vehicle
- Assures proper concentration
- No mixing or measuring
- Suspension medium: oil

**Color:** Brown




| SKU            | Capacity Vol. | Packing Type |
|----------------|---------------|--------------|
| 387-01-0145-40 | 5 gal         | Pail         |
| 387-01-0145-79 | 16 oz         | Aerosol Can  |

### Magnaglo® 20B Wet Method Preblended Dry Mixes

**Features:**

- Easy to use fluorescent wet method mix
- Pre-blended mix of 14A particles and WA-2B conditioner
- Suspension medium: water

**Color:** Brown



| SKU            | Capacity Wt. | Quantity   |
|----------------|--------------|------------|
| 387-01-0179-71 | 1 lb         | 6 per pack |

### Magnaglo® 7HF Wet Method Black Visible Premix w/Carrier II

**Features:**

- Non-fluorescent wet method particles
- 9C pre-blended with high flash point Carrier II
- Suspension medium: water or oil

**Color:** Black



| SKU            | Capacity Vol. | Quantity    |
|----------------|---------------|-------------|
| 387-01-1580-79 | 16 oz         | 12 per case |

Industrial Safety Welding Oilfield Construction

## MAGNAFLUX®

### Magnaglo® Aqua-Glo™ 14A Wet Method Fluorescent Premix/Waters

**Features:**

- Fluorescent wet method solution
- Prepared solution of 14A particles in a water based medium

**Packing Type:** Aerosol Can

**Color:** Brown

| SKU            | Quantity    |
|----------------|-------------|
| 387-01-1725-38 | 12 per case |

### Magnaglo® MG-410 Wet Method Fluorescent Magnetic Powder

**Features:**

- Dry, free-flowing magnetic powder
- Yellow-green color fluoresces under black light
- Bright color provides a vivid contrast against metal parts
- Does not require total darkness for viewing
- Closely controlled to assure optimum consistency and reliability
- Can be used with either water or oil vehicles
- Excellent for general purpose wet method magnetic particle inspection

**Color:** Yellow-Green



| SKU            | Capacity Wt. | Height | Width |
|----------------|--------------|--------|-------|
| 387-01-0191-59 | 2 lb         | 10 in  | 3 in  |

### Magnetic Particles

**Features:**

- Easy to use fluorescent wet method mix
- Pre-blended mix of 14A particles and WA-2B conditioner
- Suspension medium: water
- Articulated-leg yoke provides a portable method to magnetically inspect parts up to 11"

**Color:** Brown

**Used With:** Yoke Inspection Kit



| SKU            | Capacity Wt. |
|----------------|--------------|
| 387-01-0179-84 | 30 lb        |

### Oil Petroleum Vehicle Particles

**Features:**

- Suspension vehicle formulated for magnetic particle testing: odor-free, low-viscosity, high flash point

| SKU            | Capacity Vol. |
|----------------|---------------|
| 387-01-2122-40 |               |
| 387-01-2122-45 | 55 gal        |



### ZB 150 FSB Magnetic-Particle Inspection Blacklights

**Features:**

- Wetting agent additive for magnetic particle bath for bench inspection units
- Color:** Green



| SKU       | Voltage |
|-----------|---------|
| 387-43550 | 115 V   |



### N-D-T Cleaners

**Features:**

- Standard grade and nuclear grade
- Nuclear grade is halogen and sulfur free
- Standard grade uses non-flammable solvents with low sulfur and low halogens contents
- All products are available with certifications

**Grade:** Standard

**Physical Form:** Liquid



| SKU                 | Capacity Vol. |
|---------------------|---------------|
| 100-NDT-CLN-STD-AER | 15.2 oz       |

### N-D-T Developers

**Features:**

- Standard grade and nuclear grade
- Nuclear grade is halogen and sulfur free
- Standard grade uses non-flammable solvents with low sulfur and low halogens contents
- All products are available with certifications

**Grade:** Standard

**Physical Form:** Liquid



| SKU                 | Capacity Vol. |
|---------------------|---------------|
| 100-NDT-DEV-STD-AER | 14 1/4 oz     |

### N-D-T Penetrants

**Features:**

- Standard grade and nuclear grade
- Nuclear grade is halogen and sulfur free
- Standard grade uses non-flammable solvents with low sulfur and low halogens contents
- All products are available with certifications

**Physical Form:** Liquid



| SKU             | Capacity Vol. |
|-----------------|---------------|
| 100-NDT-PEN-AER | 9 1/2 oz      |

CANTESCO CORPORATION

## Cleaner Dye Penetrants

### Features:

- Blend of petroleum hydrocarbon solvents
- Cleaner

| SKU        | Quantity  |
|------------|-----------|
| 437-C101-A | 1 per box |



## Developer Dye Penetrants

### Features:

- A non-aqueous standard wet developer that sprays out white for red dye indications

| SKU        | Quantity  |
|------------|-----------|
| 437-D101-A | 1 per box |



## Dye Penetrants

### Features:

- Red-dye solvent
- Removable penetrant that indicates surface flaws

| SKU         | Quantity  |
|-------------|-----------|
| 437-P101S-A | 1 per box |



DYNAFLUX, INC.

## Visible Dye Penetrant Systems

### Features:

- The visible liquid dye penetrant testing is a three-step process of detecting faults in welds, castings, exotic alloys and standard materials
- Faults could be cracks, pin holes or welding laps on the metal surface

Capacity Vol.: 16 oz

| SKU           | Grade            |
|---------------|------------------|
| 368-CNF315-16 | Standard         |
| 368-DF315-16  | Nuclear          |
| 368-DNF315-16 | Nuclear          |
| 368-PHF315-16 | Standard/Nuclear |



MAGNAFLUX®

## Spotcheck® Penetrants, Developers & Cleaners

| SKU            | Capacity Vol. | Packing Type | Color     |
|----------------|---------------|--------------|-----------|
| 387-01-5155-79 | 16 oz         | Aerosol Can  | Red       |
| 387-01-5352-79 | 16 oz         | Aerosol Can  | White     |
| 387-01-5750-79 | 16 oz         | Aerosol Can  | Colorless |
| 387-01-5352-35 | 1 gal         | Can          | White     |
| 387-01-5750-35 | 1 gal         | Can          | Colorless |
| 387-01-5352-40 | 5 gal         | Pail         | White     |
| 387-01-5750-45 | 55 gal        | Drum         | Colorless |



## Spotcheck® SKL-SP2 Solvent Removable Penetrant

### Features:

- Non-chlorinated solvent developer
- Meets major requirements for special alloy and nuclear applications
- SKL-SP2 exhibits outstanding penetrating characteristics which provide for maximum reliability in locating surface-open flaws detection solvent removable (or post emulsifiable) red color contrast penetrant
- Red in daylight, fluorescent orange in UV light, LOX compatible
- Used as a leak detector and for inspection of plastics
- Approved Developer: SKD-S2
- Choose easy visibility with a bold red-colored contrast penetrant
- Excellent for use on all non-porous surfaces, including non-porous ceramics

Color: Red; Deep Red

| SKU            | Capacity Vol. | Quantity   |
|----------------|---------------|------------|
| 387-01-5155-35 | 1 gal         | 4 per case |



## Spotcheck® SKI-WP2 Water Washable Penetrants

### Features:

- Low odor, water washable penetrant that exhibits outstanding penetrating characteristics and discontinuity identification
- Water wash removable
- Eliminates the need for solvent removers or emulsifiers in the elimination of excess surface penetrant

Viscosity @ Temp.: 7.2 cSt @ 38 °C

Physical Form: Liquid

| SKU            | Capacity Vol. | Packing Type |
|----------------|---------------|--------------|
| 387-01-5190-79 | 16 oz         | Aerosol Can  |
| 387-01-5190-35 | 1 gal         | Bottle       |
| 387-01-5190-40 | 5 gal         | Pail         |



## MAGNAFLUX®

### Ultragel II® Ultrasonic NDT Couplants

**Features:**

- Possesses outstanding acoustic performance, chemical characteristics and corrosion inhibition
- Ideal for flaw detection, thickness gauging, flow metering and acoustic emission testing across a broad temperature boundary
- Ferrous corrosion inhibition rating of 90
- Broad temperature boundaries - from -10° to 210° F
- Reliable, industry standard couplant possesses outstanding acoustic performance, chemical characteristics and corrosion inhibition

**Physical Form:** Liquid



| SKU        | Capacity Vol. | Quantity   |
|------------|---------------|------------|
| 387-25-901 | 1 gal         | 4 per case |

### Zyglo® ZL-15B Water Washable Fluorescent Penetrants

**Features:**

- Convenient water washable penetrant fluoresces a bright greenish-yellow under ultraviolet radiation
- High flash point
- Recommended for use with an ultraviolet light source with a peak wavelength of 265 nanometers
- Safe for use on most engineering and aerospace alloys, including aluminum, steel, nickel and titanium

**Color:** Green-Yellow

**Applicable Materials:** Aluminum; Nickel; Steel; Titanium



| SKU            | Capacity Vol. |
|----------------|---------------|
| 387-01-3159-30 | 20 gal        |

### Zyglo® ZL-60D Water Washable Fluorescent Penetrants

**Features:**

- Water washable penetrant
- Normal sensitivity (level 2)
- Can be used in open dip tanks
- Fluoresces bright greenish-yellow under ultraviolet radiation
- High flash point
- Medium sensitivity (level 2)
- Safe for use on most engineering and aerospace alloys, including aluminum, steel, nickel and titanium

**Color:** Green-Yellow

**Applicable Materials:** Aluminum; Nickel; Steel; Titanium



| SKU            | Capacity Vol. | Packing Type |
|----------------|---------------|--------------|
| 387-01-3272-79 | 16 oz         | Aerosol Can  |
| 387-01-3272-40 | 5 gal         | Pail         |

### Zyglo® ZL-67 Water Washable Fluorescent Penetrants

**Features:**

- ZL-67 fluoresces a bright greenish-yellow under ultraviolet radiation and is safe for use on most engineering and aerospace alloys including aluminum, steel, nickel and titanium
- Safe for use on most engineering and aerospace alloys, including aluminum, steel, nickel and titanium
- ZL-67 fluoresces a bright greenish-yellow under ultraviolet radiation

**Packing Type:** Pail

**Viscosity @ Temp.:** 23.5 cSt @ 100 °F

**Color:** Green-Yellow



| SKU            | Capacity Vol. |
|----------------|---------------|
| 387-01-3274-40 | 5 gal         |

### Zyglo® ZP-48 Dry Powder Developer

**Features:**

- Free flowing, white fluffy powder used as a high sensitivity dry powder developer for Zyglo Penetrants
- Forms thin coating on parts to enhance the indications of defects
- High purity composition allows it to be used in applications where high purity is essential to the testing process
- Forms a thin film, enhancing indications of defects

**Viscosity @ Temp.:** 25 cSt @ 100 °F

**Color:** Off-White

**Physical Form:** Powder



| SKU            | Height | Wt.   | Width |
|----------------|--------|-------|-------|
| 387-01-3328-75 | 11 in  | 20 lb | 11 in |

### Fluorescent Penetrant Inspection Kits

**Features:**

- Used for portable inspection application requiring fluorescent penetrant inspection
- Includes the ZB-100F fan cooled backlight which stays cool to the touch for improved safety and operator comfort

**Includes:** (1) Can of ZL-27A Fluorescent Penetrant; (1) Can of ZP-9F Developer; (2) Cans of SKC-S Cleaner; Black Light; Hand Towels; Paint Marker; Plastic Case; Scrubs; Wiping Cloth



| SKU        | Capacity Vol. | Voltage |
|------------|---------------|---------|
| 387-600047 | 16 oz         | 115 V   |

## MAGNAFLUX®

### Spotcheck® Kits



**Features:**

- SPOTCHECK visible penetrant kits quickly locate surface cracks
- Easy to transport for field inspections
- No UV light required because of vivid red indications

**Includes:** Instructions; Paint Marker; Portable Plastic Case; Scrub Hand Towels; Wiping Cloth

**Includes:** (1) Cans of SKD-S2 Developer; (1) Cans of SKL-SP1 Penetrant; (2) Cans of SKC-S Cleaner/Remover

| SKU            | # |
|----------------|---|
| 387-01-5970-48 | 1 |

**Includes:** (2) Cans of SKD-S2 Developer; (2) Cans of SKL-SP1 Penetrant; (4) Cans of SKC-S Cleaner/Remover

| SKU            | # |
|----------------|---|
| 387-01-5920-48 | 2 |

### Battery-Powered Yoke Kits



**Features:**

- Battery powered, good for remote inspections
- Can find surface and sub-surface indications
- Kit contains all accessories to make an inspection

**Includes:** Yoke, battery, charger, gray powder

| SKU        | Depth | Height | Width |
|------------|-------|--------|-------|
| 387-611710 | 20 in | 5 in   | 24 in |

### Black Light Bulbs

**Features:**

- Replacement for ZB-100 and ZB-100F models, and all other Magnaflux 100 watt lamps made after May 1982

**Mounting:** Medium Base



| SKU        | Power Consumption |
|------------|-------------------|
| 387-507320 | 100 W             |

### Centrifuge Tubes

**Features:**

- With Magnaflux centrifuge tubes, you can monitor the concentration levels of contamination of magnetic particles in Magnaglo baths

**Used With:** 14A, 14AM, 20B Magnaglo Materials

**Increments:** 0 - 1.0 ml in .05

| SKU      | Capacity Vol. |
|----------|---------------|
| 387-8493 | 100 mL        |

### Fan Cooled Black Lights



**Features:**

- Cool running for increased safety and comfort
- Extended bulb life for greater operating efficiency
- Polycarbonate bezel shields operator's hands from lens
- Cord-through-handle design reduces operator fatigue
- Rugged aluminum housing and reinforced fiberglass handle
- Recessed lens for bulb protection

| SKU        |
|------------|
| 387-600005 |

### Hand Held, Fan-Cooled Black Lights



**Features:**

- Cool running for increased safety and comfort
- Cord-through-handle design reduces operator fatigue
- Extended bulb life for greater operating efficiency
- Recessed lens for bulb protection
- Rugged aluminum housing and reinforced fiberglass handle

**Bulb Type:** Black Light

**Phase:** Single

**Includes:** Carrier; Stand

| SKU        | Bulb Capacity | Voltage | Frequency |
|------------|---------------|---------|-----------|
| 387-600004 | 100 W         | 115 V   | 60 Hz     |

**MAGNAFLUX®**

**Hand-Held, LED Black Light**

**Features:**

- Up to 50,000 hour LED life
- Only weighs 2 lb
- Delivers 90% savings in power consumption vs. traditional black lights

**Bulb Type:** LED

**Phase:** Single

**Includes:** Cords, transformer

**Used With:** Fluorescent penetrants and magnetic particles



| SKU        | Voltage | Length   | Width |
|------------|---------|----------|-------|
| 387-624673 | 115 V   | 9 1/2 in | 4 in  |

**Magnvis® Y-7 AC/DC Magnetic Particle Inspection Yoke**

**Features:**

- Designed for one-person portable magnetic particle inspections of ferrous parts
- Ideal for inspection of welds and other remote testing
- Articulating, double-jointed legs of yokes contour to any part shape to assure good contact
- Designed for one-person portable magnetic particle inspections of ferrous parts
- Ideal for inspection of welds and other remote testing

**Includes:** 1 lb. of #1 Gray; 1 lb. of #8A Red Powder; Instructional Manual; Paint Marker; Portable Carrying Case; Powder Spray Bulb; SCRUBS™ Hand Cleaner; Y-7 AC/DC Yoke



| SKU       | Voltage |
|-----------|---------|
| 387-43509 | 115 V   |

**Y-1 AC Magnetic Yokes**

**Features:**

- Angled body and soft handgrip improve arm and wrist positioning
- Lightweight ergonomic design reduces muscle fatigue and stress
- Stainless steel protective foot guards prevent repeated contact damage
- Trigger style on/off switch

**Includes:** 1 lb #1 gray magnetic powder; 1 lb #8A red magnetic powder; Paint Marker; Portable carrying case and instructions; Powder Spray Bulb; SCRUBBS hand cleaner



| SKU        | Voltage |
|------------|---------|
| 387-623529 | 115 V   |

**Zyglo® ZP-9F Non-Aqueous Developers**

**Features:**

- Non-Aqueous developer
- Non-Chlorinated
- Recommended for titanium, nickel and alloys
- Flammable

| SKU            | Capacity Vol. | Quantity    |
|----------------|---------------|-------------|
| 387-01-3354-79 | 16 oz         | 12 per case |



**Stainless Steel Cleaner and Polish**

**Features:**

- Ideal for stainless steel, chrome, laminated plastics and aluminum surfaces
- High-gloss formula wipes clean with no streaks or buildup, resists fingerprints and masks surface blemishes
- Pleasant lime fragrance

**Odor/Scint:** Lime

**Physical Form:** Aerosol

**Removes:** Fingerprints; Grime

| SKU              | Capacity Vol. |
|------------------|---------------|
| 405-048011-14002 | 21 oz         |



**Citrus Base Cleaner**

**Features:**

- A multi-purpose cleaner which will dissolve and flush away dirt, grease, tar, most non-curing type adhesive films, and similar substances
- Citrus oil based cleaner that emulsifies when flushed with water
- It contains no petroleum distillates
- Contains no methylene chloride, 1, 1, 1-trichloroethane or chlorofluorocarbons

**Applicable Materials:** Concrete; Metal Parts; Motors; Tools

| SKU              | Capacity Vol. | Quantity    |
|------------------|---------------|-------------|
| 405-021200-76394 | 24 oz         | 12 per case |



**AerVOE Contact Cleaners**

**Features:**

- Fast evaporating, deep penetrator, no residue formula, high-deliver trigger spray, unique highly-refined wetting agent, cleaner/degreaser

| SKU     | Container Size | Quantity    |
|---------|----------------|-------------|
| 205-415 | 20 oz          | 12 per case |





## Misty® Contact & Circuit Board Cleaner III

**Features:**

- Leaves no residue
- Nonconductive to 25,000 volts

**Color:** Clear

**Removes:** Dirt; Flux; Oil; Other Contaminants



| SKU         | Container Size | Quantity    |
|-------------|----------------|-------------|
| 019-A368-16 | 16 oz          | 13 per case |



## Purge Papers

**Features:**

- Made of sodium carboxyl methyl, can be used to dam argon or helium gases during tungsten inert gas (Tig) welding of steel or aluminum pipes
- After welding is complete, flush out of system with water leaving no residue in the pipeline
- Environmentally friendly and nontoxic
- Can be formed into any size purge dam
- Position minimum of 6-8 inches from root gap
- Use heavy weight paper (Asw60) for pipes with an inside diameter of 4 in or more

**Quantity:** 4 per case

| SKU        | Size           | Length | Width     |
|------------|----------------|--------|-----------|
| 047-35R-15 | .0035 in thick | 165 ft | 15 1/2 in |
| 047-60R-15 | .0080 in thick | 165 ft | 15 1/2 in |



## Arcair® Protex® Alclean Aluminum Cleaners

**Features:**

- Works in minutes

**Color:** Blue

**Odor/Scent:** Solvent

**Applicable Materials:** Aluminum

**Removes:** Dirt; Oxidation



| SKU           | Capacity Vol. | Acidity | Quantity    |
|---------------|---------------|---------|-------------|
| 358-5702-1200 | 1 qt          | 2.5 pH  | 12 per case |



## B-12 CHEMTOOL® Carburetor/Choke Cleaners

**Features:**

- Cleans petroleum residue and disperses moisture from fuel system, fuel injector, valves, rings, pistons, oil returns, lifters, PCV valve, and oil pump screen with High Energy Solvent Technology
- Regular use ensures higher compression, fewer repairs, lower operation costs and increased spark plug and injector life



| SKU      | Capacity Wt. |
|----------|--------------|
| 084-0117 | 16 1/4 oz    |

## Berryman® Brake Cleaners

**Features:**

- Effectively removes brake fluid, grease, oil and other contaminants from all brake parts including brake linings, disc brake pads, drums, cylinders, springs, and other related brake parts
- Non-flammable, quick drying formula leaves no residue



| SKU      | Capacity Wt. |
|----------|--------------|
| 084-1420 | 20 oz        |

## Non-Chlorinated Brake Cleaners

**Features:**

- Specially formulated to clean as well as chlorinated brake cleaners without chlorinated solvents
- Tackles toughest oil, brake fluid, grease and grime deposits
- Dries quickly leaving no residue



| SKU      | Capacity Wt. |
|----------|--------------|
| 084-2421 | 19 oz        |



## Air Tool Conditioner

**Features:**

- Restores and prolongs air tool life by cleaning, coating and lubricating while tools are in use
- Removes built-up calcium, varnish, sludge and water
- Inhibits rust and increases RPMs



| SKU        | Container Size |
|------------|----------------|
| 108-16-ATC | 16 oz          |





## Citrus Based Degreasers

### Features:

- Fast acting
  - Spray on and wipe off tough grease
  - Dries residue free
- Removes:** Grease; Oil; Tar; Resin & Ink



| SKU        | Capacity Vol. |
|------------|---------------|
| 108-16-CBD | 11 oz         |

## Penetrating Catalyst

### Features:

- Loosens rusted, warped and frozen parts
- Breaks loose surface tension of rust and corrosion
- Lubricates and prevents rust



| SKU       | Container Size |
|-----------|----------------|
| 108-16-PB | 16 oz          |



## Freez-It® Sprays

### Features:

- High-performance pinpoint-accurate freeze spray for isolating components on PC boards
- Ozone Safe
- Safe on plastics
- Pinpoint accuracy isolates individual components without freezing surrounding areas
- Nonflammable

**Applicable Materials:** Plastics



| SKU        | Capacity Wt. |
|------------|--------------|
| 471-ES1050 | 10 oz        |



## 50 State Formula Brakleen® Brake Parts Cleaners

### Features:

- Degreases instantly
- Leaves no residue
- Non-chlorinated formula meets VOC regulations in all 50 states
- Non-flammable

**Fill Amount:** 14 oz

**Removes:** Brake Fluid; Grease; Oil



| SKU       | Container Size | Quantity    |
|-----------|----------------|-------------|
| 125-05050 | 20 oz          | 12 per case |

## Brakleen® Brake Parts Cleaners

### Features:

- Cleans fast/dries fast/no residue
- Degreases instantly
- Non-flammable
- Works without disassembly

**Color:** Clear

**Odor/Scent:** Solvent

**Chemical Compound:** Tetrachloroethylene

**Removes:** Brake Fluid; Grease; Oil



| SKU       | Container Size | Quantity    |
|-----------|----------------|-------------|
| 125-05089 | 20 oz          | 12 per case |

## Brakleen® Non-Chlorinated Brake Parts Cleaners

### Features:

- Cleans fast/dries fast/no residue
- Degreases instantly
- Works without disassembly
- Contains no chlorinated solvents
- Use where compliance calls for a chlorine free product
- Contains no chlorinated solvents

**Container Size:** 20 oz

**Removes:** Brake Fluid; Grease; Oil



| SKU       | Quantity    |
|-----------|-------------|
| 125-05084 | 12 per case |
| 125-05088 | 12 per case |
| 125-05151 | 12 per case |

## Chlor-Free™ Non-Chlorinated Degreasers

### Features:

- Fast drying to help minimize downtime
- Leaves no residue
- Non-conductive and non-corrosive
- Penetrates quickly to remove oil, grease and other contaminants

**Color:** White

**Odor/Scent:** Mild



| SKU       | Container Size | Dielectric Strength |
|-----------|----------------|---------------------|
| 125-03185 | 20 oz          | 20,800 V/mil        |



## CO® Contact Cleaners

### Features:

- Evaporates quickly and leaves no residue
- Non-flammable, non-chlorinated, non-staining and non-corrosive
- High dielectric strength of 27,600 volts
- Contains no VOCs
- Contains no Class I or Class II Ozone Depleting Chemicals
- NSF Registered (K2) for use in meat and poultry plants

**Color:** Clear

**Removes:** Dirt; Dust; Fingerprints; Oil

**Resistance:** Corrosive Process



| SKU       | Container Size | Dielectric Strength |
|-----------|----------------|---------------------|
| 125-02016 | 16 oz          | 27,600 V/mil        |

## Contact Cleaner 2000® Precision Cleaners



### Features:

- Removes dirt, light oils & other contaminants
- Evaporates quickly, leaves no residue, has no flash or fire point
- Use caution on sensitive plastics
- Non-conductive & non-corrosive
- Contains HCFC (141b) which has use restrictions and may only be sold to professional users for applications consistent with the regulations

**Color:** Clear

**Odor/Scent:** Faint Ether

**Chemical Compound:** HCFC

**Removes:** Dust; Fingerprints; Flux; Oil; Soil

| SKU       | # | Container Size | Dielectric Strength |
|-----------|---|----------------|---------------------|
| 125-02140 | 1 | 16 oz          | 21,000 V/mil        |
| 125-03150 | 2 | 16 oz          | 21,000 V/mil        |

## CRC Carb & Choke Cleaners

### Features:

- Will not harm oxygen sensors or catalytic converters
- Effectively dissolves deposits such as gum, sludge and varnish
- Fast acting cleaning action

**Color:** Clear

**Odor/Scent:** Aromatic

**Chemical Compound:** Acetone; Methanol; Toluene

**Removes:** Gum; Sludge; Varnish



| SKU       | Container Size |
|-----------|----------------|
| 125-03077 | 16 oz          |

## CRC Citrus Degreaser

### Features:

- Biodegradable
- Dries fast
- No Class I or Class II Ozone Depleting Chemicals
- 360° valve allows spraying in any position
- Non-corrosive, non-abrasive, and non-staining

**Color:** Clear

**Odor/Scent:** Citrus

**Chemical Compound:** Petroleum; d-Limonene

**Removes:** Adhesive; Grease; Oil; Rust; Sludge; Tar



| SKU       | Container Size | Quantity    |
|-----------|----------------|-------------|
| 125-14170 | 20 oz          | 12 per case |

## Duster™ Aerosol Dust Removal Systems

### Features:

- Removes dirt and dust from any surface without damaging sensitive components or surface finish
- Non-flammable, no residue and non-abrasive
- Safe on all plastics

**Color:** Clear

**Odor/Scent:** Faint Ether

**Chemical Compound:** HFC

**Applicable Materials:** Plastic

**Removes:** Dust; Flux



| SKU       | Container Size |
|-----------|----------------|
| 125-14085 | 12 oz          |

## Duster™ Moisture-Free Dust & Lint Remover

### Features:

- Safely eliminates debris from sensitive electronics, appliances and equipment
- No wetting or clumping
- Plastic safe
- Non-abrasive, non-corrosive
- Non-ozone depleting

**Packing Type:** Aerosol Can w/Trigger

**Removes:** Dirt; Dust; Lint



| SKU       | Container Size |
|-----------|----------------|
| 125-05185 | 16 oz          |



## Electrical Parts Cleaners

**Features:**

- Non-flammable
- Fast evaporation, leaves no residue
- Non-staining, non-corrosive and non-conductive
- High Dielectric Strength of 37,500 Volts
- Contains no 1,1,1-Trichloroethane

**Color:** Clear

**Odor/Scent:** Strong

**Chemical Compound:** Tetrachloroethylene

**Removes:** Corrosion; Grease; Oil; Sludge



| SKU       | Container Size | Dielectric Strength |
|-----------|----------------|---------------------|
| 125-02180 | 20 oz          | 37,500 V/mil        |

## Gasket Removers

**Features:**

- Contains no methylene chloride
- Loosens carbon deposits
- Protects equipment surfaces by reducing the need for excessive scraping
- Excellent paint, varnish, and graffiti remover

**Color:** Opaque

**Odor/Scent:** Solvent

**Applicable Materials:** Metals; Stone

**Removes:** Adhesive; Paint; Sealant; Varnish



| SKU       | Container Size |
|-----------|----------------|
| 125-03017 | 16 oz          |

## Heavy Duty Degreaser II

**Features:**

- High flash point
- Leaves no residue
- Non-conductive and non-corrosive
- High dielectric strength
- Low odor compound, unlike citrus-based products
- Contains no Class I or Class II Ozone Depleting Chemicals

**Color:** Clear

**Odor/Scent:** Mild

**Chemical Compound:** Petroleum

**Applicable Materials:** Metals; Nylon; Plastic

**Removes:** Dust; Grease; Ink; Oil; Tar; Wax

**Resistance:** Corrosive Process



| SKU       | Container Size | Dielectric Strength |
|-----------|----------------|---------------------|
| 125-03120 | 20 oz          | 29,000 V/mil        |

## Heavy Duty Degreasers

**Features:**

- No flash or fire Point
- Non-corrosive and non-staining
- High dielectric strength of 36,700 volts
- High cleaning strength of 129 KB
- Contains no Class I or Class II Ozone Depleting Chemicals

**Color:** Clear

**Odor/Scent:** Moderate

**Chemical Compound:** Chlorinated Solvent

**Removes:** Corrosion; Grease; Oil; Sludge

**Resistance:** Corrosive Process



| SKU       | Container Size | Dielectric Strength |
|-----------|----------------|---------------------|
| 125-03095 | 20 oz          | 36,700 V/mil        |

## HydroForce® Foaming Citrus All Purpose Cleaners

**Features:**

- Biodegradable
- Butyl free
- No Class I or Class II Ozone Depleting Chemicals
- No running or dripping
- Silicone Free

**Color:** White

**Odor/Scent:** Citrus

**Chemical Compound:** Water-Base

**Applicable Materials:** Fabric; Fiberglass; Metals; Plastics; Rubber; Stainless Steel; Vinyl

**Removes:** Dust; Grease; Ink



| SKU       | Container Size | Acidity | Quantity    |
|-----------|----------------|---------|-------------|
| 125-14400 | 20 oz          | 11 pH   | 12 per case |

## Industrial Contact Cleaners

**Features:**

- Evaporates quickly and leaves no residue
- Non-flammable, non-chlorinated, non-staining and non-corrosive
- High dielectric strength
- Contains no VOCs
- Contains no Class I or Class II Ozone Depleting Chemicals

**Color:** Clear

**Odor/Scent:** Odorless

**Chemical Compound:** HFE Blend

**Applicable Materials:** Plastic

**Removes:** Fingerprints; Oil



| SKU       | Container Size | Dielectric Strength |
|-----------|----------------|---------------------|
| 125-03070 | 16 oz          | 27,600 V/mil        |



## Knock'er Loose® Penetrating Solvents

### Features:

- Designed to quickly loosen and free seized, bound or frozen fasteners
- Quickly permeates rust, scale, gum, grease and corrosion
- Lubricating residue prevents corrosion



| SKU       | Container Size |
|-----------|----------------|
| 125-03020 | 16 oz          |

## Lectra Clean® Heavy Duty Degreasers

Dielectric Strength: 36,700 V/mil

Color: Clear

Odor/Scent: Mild

Chemical Compound: Chlorinated Solvent

Applicable Materials: Plastic

Removes: Grease; Oil; Sludge



| SKU       | Container Size | Packing Type |
|-----------|----------------|--------------|
| 125-02018 | 20 oz          | Aerosol Can  |
| 125-02021 | 5 gal          | Pail         |

## Lectra Clean® II Non-Chlorinated Heavy Duty Degreasers

### Features:

- High flash point
- Leaves no residue
- Non-conductive and non-corrosive
- High dielectric strength
- Low odor compound, unlike citrus-based products
- Contains no 1,1,1-Trichloroethane or any other chlorinated solvents
- Contains no Class I or Class II Ozone Depleting Chemicals

Color: Clear

Odor/Scent: Mild

Removes: Carbon; Dust; Grease; Ink; Oil; Sludge; Tar; Wax

Resistance: Corrosive Process



| SKU       | Container Size | Dielectric Strength |
|-----------|----------------|---------------------|
| 125-02120 | 20 oz          | 29,000 V/mil        |

## Lectra Motive® Electric Parts Cleaners

### Features:

- Non-flammable
- Leaves no residue
- Dissolves grease, oil, dirt and wax
- Provides fast thorough cleaning for non-sensitive electrical equipment

Color: Clear

Odor/Scent: Acrid

Removes: Grease; Oil; Wax



| SKU       | Container Size |
|-----------|----------------|
| 125-05018 | 20 oz          |

## Natural Degreaser™ Cleaners/Degreasers

### Features:

- Unique advanced technology blend of natural citrus and organic solvents
- Non-corrosive and effective for use on all metals
- High dielectric strength
- Suitable for use on some plastics

Odor/Scent: Citrus

Removes: Adhesive; Corrosion; Grease; Oil; Sludge

Resistance: Corrosive Process



| SKU       | Container Size | Dielectric Strength |
|-----------|----------------|---------------------|
| 125-14005 | 20 oz          | 36,500 V/mil        |

## PF™ Precision Cleaners

### Features:

- No flash or fire point
- Fast evaporation
- Plastic safe
- Contains no Class I Ozone Depleting Chemicals
- VOC exempt

Color: Clear

Odor/Scent: Faint Ether

Chemical Compound: HCFC; HFE



| SKU       | Container Size | Dielectric Strength |
|-----------|----------------|---------------------|
| 125-02190 | 16 oz          | 29,000 V/mil        |



## QD™ Contact Cleaners

**Features:**

- Quick drying, leaves no residue, safe on all plastics
- Effectively removes soil and other contaminants from electrical and electronic components
- Ideal for applications where lower flashpoint solvents can be used

**Container Size:** 16 oz

**Dielectric Strength:** 22,600 V/mil

**Color:** Clear

**Odor/Scent:** Petroleum

**Chemical Compound:** Alcohol; Petroleum Disrillate

**Applicable Materials:** Plastic

**Removes:** Dust; Fingerprints; Oil



| SKU       | Features           |
|-----------|--------------------|
| 125-02130 | • Electrical grade |
| 125-03130 | • Industrial grade |

## Quick Clean™ Safety Solvents and Degreasers

**Features:**

- Non-flammable
- Fast evaporation, leaves no residue
- Non-staining, non-corrosive and non-conductive
- High dielectric strength

**Color:** Clear

**Odor/Scent:** Strong

**Chemical Compound:** Chlorinated Solvent

**Resistance:** Corrosive Process



| SKU       | Container Size | Dielectric Strength |
|-----------|----------------|---------------------|
| 125-03180 | 20 oz          | 37,500 V/mil        |

## Super Degreaser™ Industrial Cleaners

**Features:**

- No flash or fire point
- Not labeled for use in California
- High dielectric strength of 26,800 volts
- No Class I or Class II Ozone Depleting Chemicals
- Non-conductive, non-corrosive, and non-chlorinated
- No flash or fire Point

**Color:** Clear

**Odor/Scent:** Strong

**Chemical Compound:** Halogenated

**Removes:** Grease; Oil; Rust; Sludge



| SKU       | Container Size | Quantity    |
|-----------|----------------|-------------|
| 125-03110 | 20 oz          | 12 per case |



## Crown Safety Solvent (NF)

**Features:**

- Fast-drying, no flashpoint
- Removes grease/oils, metallic particles
- High Delivery rate flushing action
- Demoisturizer penetrant

| SKU      | Capacity Wt. | Dielectric Strength | Quantity    |
|----------|--------------|---------------------|-------------|
| 205-8060 | 20 oz        | 36 kV/mm            | 12 per case |



## Off-Line Contact Cleaners

**Features:**

- Fast-evaporating, low-odor cleaner for off-line equipment maintenance
- Does not leave a film or residue
- Safe on most plastics and metals
- Does not contain CFCs, HCFCs, or chlorinated solvents

| SKU      | Container Size | Quantity    |
|----------|----------------|-------------|
| 205-8276 | 16 oz          | 12 per case |



## Toolmaker's Ink Remover

**Features:**

- Use to remove #6001 Toolmaker's Ink Blue

| SKU      | Capacity Wt. |
|----------|--------------|
| 205-6095 | 16 oz        |



**ITW Professional Brands**

## DYKEM® Remover & Cleaners

**Features:**

- No hazardous chemicals such as 1,1,1-trichloroethane, chlorofluorocarbons, or chlorinated solvents
- Applicable for plastic
- metals and glass
- Removes grease, ink, oil and paint

**Odor/Scent:** Sweet Solvent

**Applicable Materials:** Glass; Metals; Plastic



| SKU       | Capacity Vol. | Packing Type |
|-----------|---------------|--------------|
| 253-82038 | 16 oz         | Aerosol Can  |
| 253-82638 | 1 qt          | Bottle       |
| 253-82738 | 1 gal         | Bottle       |



## Clean-Up™ Industrial Safety Solvent/Cleaners

**Features:**

- Residue-free that and meets the requirements for a high rating of 29,000KV for electrical and energized equipment
- Degreaser that penetrates heavy oil and grease products to breakdown and dissolve the petroleum base ingredients to clean the surface prior to painting or preparing for assembly

**Color:** Clear

**Odor/Scent:** Ether

**Applicable Materials:** Metals; Plastic

**Removes:** Dust; Grease; Oil; Paint



| SKU       | Capacity Wt. | Dielectric Strength |
|-----------|--------------|---------------------|
| 399-61542 | 18 oz        | 29 kV/mm            |



## INDUSTRIAL

### Acetone Thinners and Reducers

**Features:**

- Fast evaporating for spray application
- Quick drying

**Color:** Clear

**Odor/Scent:** Solvent

**Chemical Compound:** Acetone



| SKU              | Capacity Vol. | Container Size |
|------------------|---------------|----------------|
| 425-K01663000-16 | 128 oz        | 1 gal          |



### Chisel® Gasket Remover

**Features:**

- Removes gaskets from any type of assembly in 10 to 15 minutes
- Prepares metal parts for new gaskets, eliminating scraping and sanding
- Not for use on plastics, linoleum, or synthetic fibers

**Color:** White

**Odor/Scent:** Mild Solvent

**Chemical Compound:** Methylene Chloride

**Applicable Materials:** Metals; Wood

**Removes:** Carbon; Grease; Oil; Paint



| SKU       | Capacity Wt. |
|-----------|--------------|
| 442-79040 | 18 oz        |

## Natural Blue® Biodegradable Cleaner & Degreaser

**Features:**

- All purpose, industrial strength, concentrated cleaner and degreaser
- Can be economically diluted with water
- Natural Blue® is formulated for wipe down, pressure spraying, and immersion cleaning processes - at room temperature or heated
- Non-flammable and non-toxic
- Contains no ODCs

**Color:** Blue

**Odor/Scent:** Pine Scent

**Removes:** Carbon; Grease; Ink; Mildew; Oil; Soot; Tar; Wax



| SKU       | Capacity Vol. | Packing Type |
|-----------|---------------|--------------|
| 442-82255 | 55 gal        | Drum         |
| 442-82251 | 1 gal         | Bottle       |



### A-151 Solvent/Degreaser

**Features:**

- Low odor
- Does not contain chlorinated solvents
- Replaces ozone depleting solvents and hazardous air pollutants such as MEK
- No rinsing and no residue
- Nonconductive
- Safe to use on most surfaces
- Inverted spray valve
- For cleaning equipment and parts



| SKU       | Capacity Vol. | Flash Point |
|-----------|---------------|-------------|
| 428-04320 | 15 oz         | 175 °F      |

### BFX All-Purpose Cleaners

**Features:**

- Biodegradable
- Industrial strength for hard to remove grease and oil
- PH 11.0 - 11.5
- Nonflammable
- Noncorrosive
- Ideal for parts washers and pressure washers
- Safe on most surfaces except magnesium



| SKU       | Capacity Vol. |
|-----------|---------------|
| 428-05528 | 28 oz         |



## CFC Free Electro Contact Cleaners

**Features:**

- Fast evaporation
  - No rinsing and no residue
  - Low odor
  - Inverted spray valve
  - Uses include delicate electrical and electronic parts, and painted surfaces
- Applicable Materials:** Fabric; Glass; Metals; Paint; Plastic; Rubber
- Removes:** Dirt; Flux; Grease; Oil



| SKU       | Capacity Vol. |
|-----------|---------------|
| 428-03116 | 11 oz         |

## CFC Free NU LVC Contact Cleaners

**Features:**

- Fast evaporating
- Safe on plastics
- Ideal for electrical/electronic and fine parts
- Cleans and degreases delicate precision mechanisms
- Penetrating action removes oil, grease, dirt, flux and other contaminants
- Does not contain chlorinated solvents



| SKU       | Capacity Vol. |
|-----------|---------------|
| 428-05416 | 11 oz         |

## Electra-X Contact Cleaner

**Features:**

- Removes oil, grease, dirt and other foreign materials from precision mechanical and delicate electrical/electronic parts
  - Nonflammable
  - Inverted spray valve
  - For use on precision mechanical and delicate electrical/electronic parts
- Removes:** Dirt; Grease; Oil



| SKU       | Capacity Vol. |
|-----------|---------------|
| 428-00816 | 12 oz         |

## Electro Contact Cleaners

**Features:**

- Nonflammable
- Fast penetration
- Quick evaporation
- Nonconductive
- Safe to use on most surfaces
- No rinsing and no residue
- Cleans/degreases delicate mechanisms
- Ideal for electrical/electronic fine parts
- Removes light greases, oils, dirt and organic soils
- No ozone depletion potential
- Penetrates into minute spaces
- Superior wetting action

**Removes:** Dirt; Grease; Oil; Soil

| SKU       | Container Size | Fill Amount |
|-----------|----------------|-------------|
| 428-00416 | 16 oz          | 14 oz       |



## F-104° Fast Dry Solvent/Degreaser

**Features:**

- For universal heavy-duty cleaning of most surfaces
  - Does not contain chlorinated solvents
  - No rinsing and no residue
  - Low odor
  - Complies with the Aerospace NESHAP for wipe solvents
- Odor/Scent:** Mild Citrus

| SKU       | Capacity Vol. |
|-----------|---------------|
| 428-04920 | 15 oz         |



## HDX Heavy-Duty Degreaser

**Features:**

- Nonflammable
- Nonconductive
- Quick penetration
- No residue
- Low odor
- No rinsing
- Heavy-duty action removes oil, grease, wax, dirt, moisture, tar, brake fluid and other contaminants

| SKU       | Capacity Vol. |
|-----------|---------------|
| 428-01020 | 19 oz         |



## Instant Super Degreaser

**Features:**

- Heavy-duty performance
  - Nonflammable
  - Fast evaporating
  - Nonconductive
  - No rinsing and no residue
  - Safe on metals
  - Inverted spray valve
- Removes:** Dirt; Grease; Oil; Other Contaminants; Tar; Wax

| SKU       | Capacity Vol. |
|-----------|---------------|
| 428-00720 | 20 oz         |



## Micro-X Fast Evaporating Contact Cleaners

**Features:**

- Quick penetration
- No residue
- Low odor
- Does not contain CFCs, HCFCs or 1,1,1 trichloroethane
- Safe on metal and most plastics
- No rinsing
- Inverted spray valve



| SKU       | Capacity Vol. | Packing Type |
|-----------|---------------|--------------|
| 428-04516 | 11 oz         | Aerosol Can  |
| 428-04555 | 55 gal        | Drum         |

## NoFlash® Electro Contact Cleaners

**Features:**

- Nonflammable
- Nonconductive
- Fast evaporating
- No rinsing and no residue
- Quick penetration
- Superior wetting action



| SKU       | Capacity Vol. |
|-----------|---------------|
| 428-04016 | 15 oz         |

## Precision Clean Multi-Purpose Cleaner/Degreaser

**Features:**

- Water-based biodegradable formula
- PH 12.5 - 13.0
- Removes tough, stubborn stains & soils such as grease, oil, sludge, soot, ink, coffee, and more
- Does not contain chlorinated or petroleum solvents, bleach, ammonia, abrasives or butyl
- Contains rust and corrosive inhibitor to prevent flash rusting of metal surfaces
- Safe on all surfaces except magnesium
- Nonflammable

**Color:** Turquoise

**Odor/Scent:** Citrus



| SKU       | Capacity Vol. | Packing Type         |
|-----------|---------------|----------------------|
| 428-02701 | 1 gal         | Jug                  |
| 428-02705 | 5 gal         | Pail                 |
| 428-02728 | 28 oz         | Trigger Spray Bottle |
| 428-02755 | 55 gal        | Drum                 |

## PreSolve® Orange Degreaser

**Odor/Scent:** Mild Citrus

**Removes:** Grease; Oil; Tar; Wax

| SKU       | Capacity Vol. | Packing Type |
|-----------|---------------|--------------|
| 428-01420 | 15 oz         | Aerosol Can  |
| 428-01428 | 1 gal         | Container    |



## PSC Plastic Safe Cleaners

**Features:**

- Formulated for contact cleaning
- Nonflammable
- Nonconductive
- Fast evaporation
- No rinsing and no residue
- Displaces moisture
- For contact cleaning of oxides and other contaminant build-ups on fine parts, electrical contacts, and electrical assemblies

**Applicable Materials:** Metals; Plastic



| SKU       | Capacity Vol. |
|-----------|---------------|
| 428-04620 | 18 oz         |

## TriFree Brake Cleaners

**Features:**

- Heavy-duty performance
- Instant degreasing action
- Improves brake performance
- Does not contain chlorinated solvents
- Helps stop disc brake squeal
- Fast evaporation
- High solvency
- No rinsing and no residue

**Removes:** Brake Fluid; Grease; Oil

| SKU       | Capacity Vol. |
|-----------|---------------|
| 428-03620 | 15 oz         |







## ZeroTri® Heavy-Duty Degreasers

### Features:

- Fast evaporating
- Instant degreasing action
- Ideal for cleaning metals
- Heavy-duty solvent
- Does not contain chlorinated solvents
- No rinsing and no residue
- Instant penetrating action
- Safe to use on most surfaces
- Inverted spray valve



| SKU       | Capacity Vol. | Packing Type |
|-----------|---------------|--------------|
| 428-03505 | 5 gal         | Pail         |
| 428-03520 | 15 oz         | Aerosol Can  |
| 428-03528 | 1 gal         | Jug          |
| 428-03555 | 55 gal        | Drum         |



## Industrial Strength Cleaners & Degreasers

### Features:

- Mean Green is a unique blend of non-toxic, biodegradable detergents that form a powerful, non-flammable, extra heavy-duty cleaner and degreaser
- Is gentle enough for cleaning clothes, upholstery, and carpet, but strong enough for heavy duty projects like cleaning engines and construction equipment



| SKU     | Capacity Vol. | Packing Type         |
|---------|---------------|----------------------|
| 483-102 | 1 gal         | Bottle               |
| 483-104 | 55 gal        | Drum                 |
| 483-106 | 5 gal         | Pail                 |
| 483-132 | 32 oz         | Trigger Spray Bottle |

## MICRO-MIST

### Safety Solvents

### Features:

- Fast drying
- Non-flammable and non-conductive formula can be used on motors while running
- Dielectric
- Leaves no residue

**Color:** Colorless

**Odor/Scent:** Chlorinated Solvent

**Chemical Compound:** Chlorinated Solvent

**Removes:** Dirt; Grease; Grime



| SKU      | Container Size | Dielectric Strength |
|----------|----------------|---------------------|
| 480-S101 | 20 oz          | 32,000 V/mil        |



## Tide® Floor and All-Purpose Cleaners

### Features:

- High levels of surfactant and builders combined to cut through tough grease
- UL Classified for slip resistance
- Easy-rinse powder formula is ideal for quarry tile



| SKU       | Capacity Wt. |
|-----------|--------------|
| 608-02364 | 36 lb        |



## PF® Solvents

### Features:

- Replaces chlorinated solvents and Methyl Ethyl Ketone (MEK)
- Excellent solvent for power cable preparation and termination
- Dissolves grease, oil, tar, resin and wax
- Nonconductive to 39 kV
- Compatibility tested and found completely acceptable for power cables, electric motors and other power utility components
- Evaporates and leaves no residue
- Safe to use on most metals and plastics



| SKU       | Size             |
|-----------|------------------|
| 429-61432 | 32 fl.oz. bottle |



## Brake Cleaners

### Features:

- Quickly dissolves and flushes away brake dust, brake fluid, grease, oil and other contaminants
- Not for sale in California
- Not for sale in California or New Jersey.

**Applicable Materials:** All Metals

**Removes:** grease, oil, brake dust, dirt, grime



| SKU       | Capacity Vol. |
|-----------|---------------|
| 615-M7-20 | 19 oz         |



## Engine Brite®

### Features:

- Heavy duty cleaning formula is packed with powerful degreasing solvents that quickly and easily remove the toughest grease, dirt, and grime



| SKU      | Capacity Vol. |
|----------|---------------|
| 615-EB-1 | 16 oz         |

## Super Concentrate Degreasers

### Features:

- Dilutes with kerosene and other similar petroleum solvents
- An economical concentrated cleaner helps dissolve grease

**Applicable Materials:** All Metals

**Removes:** Heavy-duty baked on grease, oil, dust and dirt



| SKU      | Capacity Vol. |
|----------|---------------|
| 615-SC-5 | 5 gal         |



## Simple Green® Concentrated Cleaner/Degreaser

**Color:** Clear

**Odor/Scent:** Sassafras scent

**Physical Form:** Liquid

**Chemical Compound:** aqueous based mixture



| SKU               | Container Size | Acidity         |
|-------------------|----------------|-----------------|
| 676-2710001213012 | 24 oz          | 8.5 pH - 9.5 pH |
| 676-2710200613005 | 1 gal          | 8.5 pH - 9.5 pH |

## Simple Green® Crystal Simple Green



### Features:

- For critical cleaning applications that demand a fragrance free solution

**Color:** Clear

| SKU               | # | Capacity Vol. | Packing Type | Acidity |
|-------------------|---|---------------|--------------|---------|
| 676-0600000119005 | 1 | 5 gal         | Pail         | 9.35 pH |
| 676-0600000119055 | 1 | 55 gal        | Drum         | 9.35 pH |
| 676-0610000619128 | 2 | 1 gal         | Bottle       | 9.35 pH |
| 676-0610001219024 | 2 | 24 oz         | Spray Bottle | 9.35 pH |

## Simple Green® Original Formula Cleaners

| SKU               | Capacity Vol. | Packing Type |
|-------------------|---------------|--------------|
| 676-2700000113006 | 5 gal         | Pail         |
| 676-2700000113008 | 55 gal        | Drum         |
| 676-2710001213033 | 32 oz         | Bottle       |



## 3-2-1 Contact Cleaners

### Features:

- Electronic cleaner
  - Alternative to TF113
  - Safe on metal and many plastics
  - Non-Flammable
- Dielectric Strength 1:** 12,500 V



| SKU           | Capacity Vol. |
|---------------|---------------|
| 425-S02204000 | 10 oz         |



## Brake & Parts Cleaners

### Features:

- Instantly flushes away brake fluids, grease and dirt to ensure accurate adjustments and smooth brake operations
- Non-chlorinated formula

**Applicable Materials:** Drums

**Series:** SP™ 705

**Removes:** Dirt; Grease



| SKU        | Capacity Vol. | Quantity    |
|------------|---------------|-------------|
| 425-S00705 | 20 oz         | 12 per case |

## Electrical Spray Lubricant & Cleaners

### Features:

- New non-ozone-depleting formula
- Leaves a fine microscopic corrosion-proof film
- Eliminates related humming noise
- Evaporates fast

**Removes:** Dirt; Dust; Grease; Oxidation



| SKU        | Capacity Wt. | Dielectric Strength |
|------------|--------------|---------------------|
| 425-S02001 | 16 oz        | 36,700 V/mil        |

## Environmental Cleaner & Degreasers

### Features:

- Designed for fast, effective removal of dirt, oil, grease, wax and tar on electrical equipment
- No CFCs or HCFCs
- For use on non-energized equipment
- Leaves no residue
- Fast-evaporating

**Color:** Clear

**Removes:** Grease; Oil; Tar; Wax



| SKU        | Capacity Wt. | Dielectric Strength |
|------------|--------------|---------------------|
| 425-S00749 | 15 oz        | 16,800 V/mil        |

## Flash Free Safety Solvent & Degreasers

### Features:

- Evaporates quickly, leaves no residue
- Non-conductive, non-flammable
- High-delivery valve

**Color:** Clear

**Removes:** Dirt; Grease; Wax; Metallic Particles



| SKU        | Capacity Wt. | Dielectric Strength |
|------------|--------------|---------------------|
| 425-S00848 | 13 oz        | 37,000 V/mil        |

## FLASH FREE® Electrical Degreaser

### Features:

- Non-flammable
- Non-Flammable
- Increases the life of electrical components by removing foreign materials that can cause costly downtime
- Excellent for degreasing aluminum and cleaning sheet and strip steel prior to galvanizing

**Applicable Materials:** Wire Rope

**Removes:** Dirt; Grease; Oil; Wax



| SKU        | Capacity Vol. | Quantity    |
|------------|---------------|-------------|
| 425-S20848 | 17 oz         | 12 per case |

## Sprayon® Citrus Cleaner Degreasers

### Features:

- Biodegradable, heavy-duty, multi-purpose cleaner and graffiti remover
- No CFCs or HCFCs

**Odor/Scent:** Citrus

**Applicable Materials:** Ceramic; Fiberglass; Formica™; Some Plastics; Wood

**Removes:** Grease; Oil



| SKU        | Capacity Wt. | Dielectric Strength |
|------------|--------------|---------------------|
| 425-S00757 | 16 oz        | 40,400 V/mil        |



## Sprayon® Heavy Duty Paint Removers

### Features:

- Effective on metal, wood, glass, concrete, stone, brick, ceramic tile and other hard surfaces
- Leaves surface clean and ready for repainting or installation of new gasket
- Fast acting

**Applicable Materials:** Concrete; Glass; Metals

**Removes:** Varnish; Hi-Bake & Air-Dry Paints; Urethane Finishes; Shellac; Decals



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S00615 | 15 oz        |



## Sprayon® Layout Fluid Removers

**Features:**

- Specially formulated to remove layout fluids quickly and efficiently
- Leaves no residue
- Does not contain chlorinated solvents
- Uses include by tool and die makers, maintenance mechanics, pattern makers, machinists, inspection and production departments, and sheet and metal workers.

**Color:** Clear

**Applicable Materials:** Glass; Metals

**Removes:** Light Soils; Greases; Lacquer Materials; Other Markings



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S00606 | 12.8 oz      |

## Sprayon® Stainless Steel Cleaners

**Features:**

- Water-based emulsion
- Effectively cleans most water and oil-based stains on stainless steel and other metal surfaces
- Invisible coating resists finger-prints, water marks and rusting

**Chemical Compound:** Water

**Applicable Materials:** Metals; Stainless Steel

**Removes:** Fingerprints; Oil



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S00885 | 17 oz        |



## Empty Trigger Bottles

**Features:**

- Bottle features blank lines and charts for product and safety information
- For use with bulk cleaners



| SKU       | Capacity Vol. |
|-----------|---------------|
| 125-14021 | 24 oz         |

## Bee Blast™ Wasp & Hornet Killer

**Features:**

- Fast acting
- No chlorinated solvents
- 22' jet blast

**Insect Type:** Ants; Scorpions; Spiders; Wasp & Hornets

| SKU       | Container Size |
|-----------|----------------|
| 125-14009 | 20 oz          |



## Wasp & Hornet Killer Plus™ Insecticides

**Features:**

- Will not damage plastic connectors and other insulating materials
- CRC trigger provides a dense, accurate spray that will reach over 20 feet to drench harmful insects and their nests
- The only wasp and hornet killer in the industry with CRC's patented M.S.D.[L.] , a current MSDS printed on the reverse side of the product label
- Will not damage plastic connectors and other insulating materials

**VOC:** 0.1 lb/gal; 15.9 g/L; 2.0 %

**Insect Type:** Ants; Bee; Scorpions; Spiders; Wasp & Hornets; Yellow Jacket

| SKU       | Container Size |
|-----------|----------------|
| 125-14010 | 20 oz          |



**ITW Professional Brands**

## The End.™ Insecticides

**Features:**

- Instant knockdown
  - Sprays up to 20 ft
  - Dielectric breakdown voltage of 40,700
  - Kills nest and insects with residual action
- Insect Type:** Bee; Wasp & Hornets; Yellow Jacket

| SKU       | Capacity Wt. |
|-----------|--------------|
| 253-18320 | 20 oz        |





## Blast'EM™ Wasp & Hornet Killer

### Features:

- Will not harm most plastics, including Noryl, ABS and Lexan
- 98% knockdown, 100% kill within 24 hours
- Sprays up to 20 feet with flood-type valve
- Residual deposit will kill returning wasps and hornets
- Contains a high amount of petroleum distillates
- For outside use only

**Insect Type:** Flies; Mosquitos; Moths; Wasp & Hornets; Yellow Jacket

**Dielectric Strength 1:** 33,000 V



| SKU           | Container Size | Fill Amount |
|---------------|----------------|-------------|
| 425-S00857    | 16 oz          | 12 oz       |
| 425-S02085700 | 20 oz          | 14 oz       |

## DYNAFLUX, INC.

## Defense Concentrates

### Features:

- Provides year-round pump protection for water recirculators and closed loop cooling systems
- Reduces the need for water fill maintenance by reducing water evaporation

**Color:** Blue

**Chemical Compound:** Ethylene Glycol



| SKU         | Capacity Vol. |
|-------------|---------------|
| 368-DF929-1 | 1 gal         |



## 550® Nonmetallic Anti-Seize Compounds

### Features:

- Assures protection against rust, oxidation, and corrosion

**Color:** Steel Blue

**NLGI Grade:** 1 - 1-1/2

**Thickener:** Aluminum Complex

**Applicable Materials:** Iron; Steel

**Resistance:** Corrosive Process; Wear

| SKU       | Capacity Wt. |
|-----------|--------------|
| 399-15502 | 1/2 lb       |
| 399-15504 | 1 lb         |

## Kopr-Kote® High Temperature Anti-Seize & Gasket Compounds

### Features:

- Provides a shield against metal-to-metal contact, preventing seizure and corrosion
- Assures protection against rust, oxidation, and corrosion
- Specially formulated to prevent excessive over torque issues and has a very high static friction factor of 0.17
- Unique blend of complex thickeners to help evenly distribute the copper flake onto the metal surfaces to eliminate metal to threaded metal contact

**Color:** Copper

**Thickener:** Aluminum Complex

**Chemical Compound:** Petroleum Based

**Physical Form:** Paste or Gel

**Applicable Materials:** Most Metals

**Resistance:** Corrosive Process; Water



| SKU       | Capacity  | Packing Type  |
|-----------|-----------|---------------|
| 399-10002 | 1/2 lb    | Can           |
| 399-10041 | 12 oz     | Aerosol Can   |
| 399-10004 | 1 lb      | Can           |
| 399-10007 | 2 lb      | Brush Top Can |
| 399-10091 | 1 gal     | Pail          |
| 399-10092 | 2 1/2 gal | Pail          |
| 399-10093 | 5 gal     | Pail          |

## Nikal® High Temperature Anti-Seize & Gasket Compounds

### Features:

- Retains the equipment in serviceable condition
- This blend enhances anti-seize performance, containing flake particles of pure Nickel and other additives blended in a high temperature complex grease carrier
- Can be used when copper products are prohibited
- Has controlled frictional characteristics so that the surfaces of the Nut & Bolt are torque to the designed K-Factor
- Assures full hydraulic efficiency by allowing the metal surfaces to slide over each other without metal-to-metal contact

**Color:** Silver

**NLGI Grade:** 1.5

**Thickener:** Aluminum Complex

**Chemical Compound:** Petroleum Based with Nickel

**Physical Form:** Paste or Gel

**Applicable Materials:** Most Metals; Stainless Steel

**Resistance:** Acid; Corrosive Process; Water; Wear



| SKU       | Capacity Wt. |
|-----------|--------------|
| 399-13604 | 1 lb         |



## SS-30™ High Temperature Anti-Seize & Gasket Compounds

### Features:

- Assures full hydraulic efficiency by allowing the metal surfaces to slide over each other without metal-to-metal contact
- Contains high concentration of copper flakes which is required for heavy loads or compression
- Environmentally preferred anti-seize thread lubricant and conductive termination compound
- Has controlled frictional characteristics so that the surfaces of the Nut & Bolt are torque to the designed K-Factor
- Retains the equipment in serviceable condition
- This compound formula will not melt in high temperatures and improves conductivity and ground continuity
- Works as a similar and dissimilar metal between two metal surfaces to prevent seizing

**Color:** Copper


**NLGI Grade:** 1.5

**Thickener:** Organo Clay

**Chemical Compound:** Petroleum Based

**Applicable Materials:** Brass; Cast Iron; Copper; Most Metals; Plastic; Stainless Steel

**Resistance:** Corrosive Process; Wear



| SKU       | Capacity Wt. |
|-----------|--------------|
| 399-12504 | 1 lb         |

## White Knight™ Food Grade Anti-Seize Compounds

### Features:

- Retains the equipment in serviceable condition
- Environmentally preferred food grade anti-seize thread lubricant
- Ideal for incident food contact applications
- Has controlled frictional characteristics so that the surfaces of the Nut & Bolt are torque to the designed K-Factor
- Assures full hydraulic efficiency by allowing the metal surfaces to slide over each other without metal-to-metal contact
- Contains Propylparaben - a bacterial fungi static agent

**Color:** White

**NLGI Grade:** 1.5

**Thickener:** Aluminum Complex

**Chemical Compound:** Mineral Oil; Synthetic Based

**Physical Form:** Paste or Gel

**Applicable Materials:** Most Metals; Stainless Steel

**Resistance:** Corrosive Process; Water; Wear



| SKU       | Capacity Wt. |
|-----------|--------------|
| 399-16404 | 1 lb         |



## C5-A® Copper Based Anti-Seize Lubricant

### Features:

- Exclusive formula suspends copper and graphite in a high quality grease
- Protects metal parts from rust, corrosion, galling, and seizing

**Applicable Materials:** Brass; Cast Iron; Copper; Most Metals; Plastic; Stainless Steel; Steel

**Resistance:** Corrosive Process



| SKU       | Capacity Wt. | Color  |
|-----------|--------------|--------|
| 442-51003 | 12 oz        | Grey   |
| 442-51005 | 10 oz        | Copper |
| 442-51006 | 1 lb         | Copper |
| 442-51007 | 1 lb         | Copper |
| 442-51008 | 2 1/2 lb     | Copper |
| 442-51009 | 8 lb         | Copper |
| 442-51011 | 42 lb        | Copper |
| 442-51147 | 8 oz         | Copper |

## Heavy Duty Anti-Seize

### Features:

- Metal-free
- Excellent lubricity
- Provides outstanding lubrication to all metals including stainless steel, aluminum, and soft metals

**Color:** Black

**Chemical Compound:** Graphite

**Odor/Scent:** Odorless

**Physical Form:** Paste or Gel

**Applicable Materials:** Aluminum; Most Metals; Stainless Steel

**Resistance:** Chemical



| SKU       | Capacity Wt. |
|-----------|--------------|
| 442-51605 | 9 oz         |
| 442-51606 | 1.2 lb       |

## Loctite Food Grade Anti-Seize

### Features:

- Prevents seizure, galling, and friction in stainless steel and other metal parts

**Color:** White

**Odor/Scent:** Mild Oil

**Physical Form:** Paste or Gel

**Applicable Materials:** Aluminum; Most Metals; Steel



| SKU         | Capacity Wt. |
|-------------|--------------|
| 442-1167237 | 8 oz         |



## Marine Grade Anti-Seize

### Features:

- Formulated to protect assemblies exposed directly or indirectly to fresh and salt water
- Works especially well in high humidity conditions
- It has excellent lubricity, superior water wash-out and water spray resistance, and prevents galvanic corrosion

**Color:** Black

**Thickener:** Complex Calcium Sulphonate

**Odor/Scent:** Mild

**Physical Form:** Paste or Gel

**Resistance:** Corrosive Process; Saltwater; Water



| SKU       | Capacity Wt. |
|-----------|--------------|
| 442-34026 | 16 oz        |
| 442-34395 | 8 oz         |

## N-5000™ High Purity Anti-Seize

### Features:

- Lubricates and protects Class 1, 2, and 3 power plant hardware
- Recommended for highly corrosive environments

**Color:** Silver

**Chemical Compound:** Graphite; Nickel

**Odor/Scent:** Grease

**Physical Form:** Paste or Gel

**Resistance:** Chemical; Corrosive Process



| SKU       | Capacity Wt. |
|-----------|--------------|
| 442-51243 | 8 oz         |
| 442-51269 | 1 lb         |

## N-7000™ High Purity Anti-Seize, Metal Free

### Features:

- Metal-free formulation provides high levels of purity and excellent lubricating properties
- For Class 1, 2, and 3 power plant hardware

**Color:** Silver

**Chemical Compound:** Graphite

**Odor/Scent:** Grease

**Physical Form:** Paste or Gel

**Resistance:** Chemical



| SKU       | Capacity Wt. |
|-----------|--------------|
| 442-51270 | 1 lb         |

## Nickel Anti-Seize

### Features:

- Copper-free
- For preventing corrosion, seizing, galling in harsh, chemical environments, and temperatures

**Color:** Silver

**Chemical Compound:** Graphite; Mineral Oil; Nickel

**Applicable Materials:** Most Metals; Stainless Steel

**Resistance:** Acetylene; Acid; Ammonia; Chemical; Corrosive Process; Vinyl Monomer



| SKU       | Capacity Wt. | VOC             |
|-----------|--------------|-----------------|
| 442-51102 | 1 lb         | 2.5 %; 27.0 g/L |
| 442-51286 | 12 oz        | 408.0 g/L       |
| 442-77124 | 8 oz         | 2.5 %; 27.0 g/L |
| 442-77164 | 1 lb         | 2.5 %; 27.0 g/L |

## Silver Grade Anti-Seize

### Features:

- Heavy duty, temperature resistant, petroleum-based lubricant compound fortified with graphite and metallic flake
- Inert, will not evaporate or harden in extreme cold or heat

**Color:** Silver

**NLGI Grade:** 1

**Chemical Compound:** Graphite; Mineral Oil

**Odor/Scent:** Petroleum

**Applicable Materials:** Aluminum; Most Metals; Stainless Steel

**Resistance:** Corrosive Process



| SKU       | Capacity | VOC               |
|-----------|----------|-------------------|
| 442-80209 | 4 oz     | 13.8 %; 162.0 g/L |
| 442-76732 | 8 oz     | 13.8 %; 162.0 g/L |
| 442-76759 | 12 oz    |                   |
| 442-76764 | 1 lb     | 13.8 %; 162.0 g/L |
| 442-80206 | 1 gal    | 13.8 %; 162.0 g/L |

## White High-Temp Anti-Seize

### Features:

- A general purpose non-metallic formulation that protects against high temperature seizing and galling of mated metal parts
- It has excellent lubricity

**Color:** White

**VOC:** 4.7 g/L

**Thickener:** Aluminum Complex

**Chemical Compound:** Mineral Oil

**Odor/Scent:** Mild

**Physical Form:** Paste or Gel

**Applicable Materials:** Brass; Cast Iron; Copper; Stainless Steel; Steel; All Alloys

**Resistance:** Corrosive Process; Heat; Water



| SKU       | Capacity Wt. |
|-----------|--------------|
| 442-34518 | 16 oz        |



**LPS® Copper Anti-Seize Lubricants**

**Features:**

- Prevents seizure up to 1800° F (982° C)
- Protects against seizure, heat-freeze, galling, rust and corrosion
- Cushions impact and shock loads
- Will not run, drip or settle out
- Not affected by contraction, expansion or vibration
- Permits reuse of fittings, saves stud, bolt and nut replacements

**Color:** Bright Copper

**Resistance:** Corrosive Process; Impact; Moisture; Water



| SKU       | Container Size |
|-----------|----------------|
| 428-02916 | 16 oz          |

**LPS® Nickel Anti-Seize Lubricants**

**Features:**

- Prevents seizure up to 2600° F (1427° C)
- Contains no lead, copper, graphite, chlorides, phosphorous, silicone or halogens
- Protects against seizure, rust and corrosion
- Prevents water wash-off
- Can be used with ammonia, acetylene and vinyl monomers
- Safe on stainless steel when temperatures exceed 550° F (288° C)
- Will not run, drip or settle out

**Color:** Silver Gray

**Resistance:** Corrosive Process; Impact; Moisture; Water



| SKU       | Container Size |
|-----------|----------------|
| 428-03908 | 1/2 lb         |



**E-Z Break® Anti-Seize Compound Copper Grades**

**Features:**

- Copper-based anti-seize and lubricating compound
- Recommended for coating nuts, bolts, valves, flanges, splines for easy break out after years of service
- Resists rust and corrosion

**Color:** Copper Gray

**Flash Point:** 410 °F

**Odor/Scent:** Oil

**Applicable Materials:** Stainless Steel

**Resistance:** Corrosion; Rust



| SKU       | Capacity Wt. | Quantity    |
|-----------|--------------|-------------|
| 434-08910 | 10 oz        | 24 per case |

**E-Z Break® Anti-Seize Compound Nickel Grades**

**Features:**

- Contains fine particles of nickel and other additives
- Does not contain copper
- Helps prevent galling of stainless steel threads
- Makes disassembly easy, even after years of service
- Resists rust and corrosion

**Color:** Silver Gray

**VOC:** 0.0 lb/gal

**Odor/Scent:** Grease

**Physical Form:** Paste

**Applicable Materials:** Stainless Steel

**Resistance:** Corrosion; Rust



| SKU       | Capacity Wt. | Quantity    |
|-----------|--------------|-------------|
| 434-08971 | 8 oz         | 24 per case |

**NEVER•SEEZ®**

**Blue Moly Compounds**

**Features:**

- Provides excellent protection against extreme pressure and high temperatures
- Contains no graphite, lead or copper and can be used in applications where these are undesirable or prohibited

**Color:** Blue



| SKU         | Capacity Wt. |
|-------------|--------------|
| 535-NBBT-16 | 16 oz        |

**GlideCote® Saw Table & Tool Surface Sealants**

**Features:**

- Easier and quicker to apply than paste wax
- Eliminates "hang-ups" on sliding surfaces
- Fluoropolymer dramatically reduces sliding friction while it repels dust, dirt, and moisture
- Perfect for table saw beds, drill presses, lathes, planers, band saws, miters, panel saws, and all hand tools
- Protects all tools and equipment from rust

**Color:** Clear

**VOC:** 352.2 g/L

**Applications:** Pneumatic Tools; Conveyor Rollers; Print and Binding Sliding Surfaces; Release Agent for Injection Molds/Printing Plates; Wood Working Tools

**Resistance:** Dirt; Dust; Moisture



| SKU         |
|-------------|
| 535-V207501 |



Industrial Safety Welding Oilfield Construction

## NEVER•SEEZ®

### High Temperature Stainless Lubricating Compounds



**Features:**

- Excellent resistance to corrosion
- Prevents seizure at high temperatures
- Resists galvanic action between dissimilar metals
- Speeds disassembly
- Prevents galling

**Color:** Silver Gray

**NLGI Grade:** 1

| SKU          | Capacity Wt. |
|--------------|--------------|
| 535-NSSBT-16 | 1 lb         |

### Mariner's Choice Anti-Seize

**Features:**

- Extreme pressure lubricant formulated to assure absolute parts protection against seizure, galling and corrosion in fresh and salt water environments
- Offers unparalleled resistance to water washout and the best protection in continuous high moisture environments both above and below water lines

**Color:** Black-Gray



| SKU          | Capacity Wt. |
|--------------|--------------|
| 535-NMCBT-16 | 16 oz        |
| 535-NMCBT-8  | 8 oz         |

### Nickel Nuclear Grade Compounds

**Features:**

- Excellent heat dispersing qualities
- Prevents galling on steel-to-stainless, titanium, magnesium and other hard metals

**Color:** Silver



| SKU         | Capacity Wt. | Packing Type  | Pressure             |
|-------------|--------------|---------------|----------------------|
| 535-NG-165  | 1 lb         | Flat Top Can  | 32,000 psi (tensile) |
| 535-NGBT-16 | 1 lb         | Brush Top Can | 32,000 psi (tensile) |
| 535-NGBT-8  | 8 oz         | Brush Top Can | 32,000 psi (tensile) |

### Pipe Compound

**Features:**

- Formulated to provide maximum thread lubrication in a wide range of pipe threads and fittings
- Prevents corrosion and galling of threads for easy disassembly at temperatures up to 525°F
- PTFE, and other sealant enhancing additives allows greater thread engagement and more positive sealing
- Recommended for use on black iron, galvanized stainless steel, and high pressure steam pipes in contact with malleable cast iron, brass, stainless steel and galvanized fittings



| SKU         | Capacity Wt. |
|-------------|--------------|
| 535-NPBT-16 | 1 lb         |
| 535-NPBT-8  | 8 oz         |

### Pure Nickel Special Compounds

**Features:**

- Excellent heat dispersing qualities
- Prevents galling on steel-to-stainless, titanium, magnesium and other hard metals

**Color:** Silver

**Pressure:** 32,000 psi (tensile)



| SKU          | Capacity Wt. | Packing Type  |
|--------------|--------------|---------------|
| 535-NSBT-16N | 1 lb         | Brush Top Can |
| 535-NSBT-8N  | 8 oz         | Brush Top Can |
| 535-NSN-165  | 1 lb         | Flat Top Can  |

### Regular Grade Compounds

**Features:**

- Protects against rust, corrosion, carbon fusion and seizure at high temperatures
- Keeps parts working longer with less wear, and enables faster disassembly when repairs are needed



| SKU              | Capacity Wt. | Packing Type  | Flash Point |
|------------------|--------------|---------------|-------------|
| 535-NS-130B      | 130 lb       | Drum          | 482 °F      |
| 535-NS-160       | 1 lb         | Flat Top Can  | 482 °F      |
| 535-NS-168       | 8 lb         | Flat Top Can  | 482 °F      |
| 535-NS-42B       | 42 lb        | Pail          | 482 °F      |
| 535-NS-42B-STEEL | 42 lb        | Pail          | 475 °F      |
| 535-NS-42B-STEEL | 42 lb        | Pail          | 475 °F      |
| 535-NSA-16       | 16 oz        | Aerosol Can   | 482 °F      |
| 535-NSBT-16      | 1 lb         | Brush Top Can | 482 °F      |
| 535-NSBT-4       | 1/4 lb       | Brush Top Can | 482 °F      |
| 535-NSBT-8       | 8 oz         | Brush Top Can | 482 °F      |

### White Food Grade Compound w/PTFE

**Features:**

- Premium quality lubricant composed entirely of ingredients which meet FDA requirements where incidental food contact is possible
- It is a virtually odorless, colorless and tasteless multi-purpose lubricant for varied services within the food handling plant

**Color:** White



| SKU         | Capacity Wt. |
|-------------|--------------|
| 535-NSWT-14 | 14 oz        |

CHEMICALS, LUBRICANTS & PAINTS



## Anti-Seize Lubricants

### Features:

- Heavy-duty blend of aluminum, copper and graphite
- Prevents galling, corrosion and seizing of mated parts
- Salt, corrosion and moisture resistant
- Will not evaporate or harden

**Color:** Silver



| SKU       | Capacity Wt. |
|-----------|--------------|
| 230-80071 | 4 oz         |
| 230-80078 | 8 oz         |
| 230-80208 | 16 oz        |

## Nickel Anti-Seize Lubricants

### Features:

- Protects metal parts from seizing and galling
- Copper-free, use under conditions of extreme pressure and temperature, and with stainless steel, titanium and nickel alloys



| SKU       | Capacity Wt. | Quantity    |
|-----------|--------------|-------------|
| 230-77124 | 8 oz         | 12 per case |
| 230-77164 | 16 oz        | 10 per case |

## Permatex® Copper Anti-Seize Lubricants

### Features:

- Anti-seize and thread lubricant that may be used to prevent seizing, corrosion and galling where high temperature conditions exist



| SKU       | Capacity Wt. |
|-----------|--------------|
| 230-09128 | 8 oz         |
| 230-31163 | 16 oz        |



## Anti-Seize & Lubricants

### Features:

- Designed to lubricate and protect metal parts
- Protective film will not harden, separate or evaporate
- Cannot be burned off or removed by abrasion
- Can be used to protect against galling, carbon fusion, and galvanic pitting

**Color:** Copper Gray

**Chemical Compound:** Synthetic Based

**Applicable Materials:** Most Metals

**Resistance:** Corrosive Process; Saltwater



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S00620 | 11 1/4 oz    |



## 3-36® Multi-Purpose Lubricant & Corrosion Inhibitors

### Features:

- Cleans, lubricates, penetrates and loosens corrosion
- Prevents corrosion by displacing moisture
- Penetrates through corrosion to loosen frozen parts
- Lubricates without leaving a sticky residue
- Cleans light soils and contaminants
- Convenient 360 spray valve - can be sprayed from any position

**Color:** Clear Green

**Chemical Compound:** Petroleum Based

**Odor/Scent:** Pleasant

**Applicable Materials:** Aluminum; Brass; Most Metals; Steel



| SKU       | Container Size | Packing Type | VOC               |
|-----------|----------------|--------------|-------------------|
| 125-03005 | 16 oz          | Aerosol Can  | 572.5 g/L; 70.1 % |
| 125-03006 | 1 gal          | Bottle       | 555.8 g/L         |
| 125-03009 | 5 gal          | Pail         | 555.8 g/L         |

## Bright Zinc-It® Instant Cold Galvanize

### Features:

- Protects base metal even when scratched or abraded
- Fast-drying, dries to the touch in 15 minutes

**Color:** Gray

**VOC:** 5.5 lb/gal; 657.0 g/L; 71.0 %

**Finish:** Glossy Metallic

**Chemical Compound:** Zinc

**Odor/Scent:** Solvent

**Applicable Materials:** Most Metals

**Resistance:** Corrosive Process; Weather



| SKU       | Container Size |
|-----------|----------------|
| 125-18414 | 16 oz          |

## SP-350™ Corrosion Inhibitors

### Features:

- Displaces moisture and protects all metals with a thin non-drying film
- Protects equipment and parts in storage, shipment and in process for up to 2 years indoors
- Convenient 360° spray valve - can be sprayed from any position
- High pressure lubricant that withstands up to 1,250 lbs of pressure in Falex test method

**Coverage @ Vol.:** 2,000 sq. ft. @ 1 gal

**Applicable Materials:** Most Metals

**Resistance:** Corrosive Process; Moisture



| SKU       | Container Size |
|-----------|----------------|
| 125-03262 | 16 oz          |



## SP-400™ Corrosion Inhibitors

### Features:

- Firm, waxy film is highly resistant to humidity and salt spray and never becomes brittle
- Long term protection (up to 2 years outdoors) for all metals during shipment or extended storage
- Waxy film seals out moisture completely

**Color:** Dark Amber

**Coverage @ Vol.:** 1,000 sq. ft. @ 1 mL

**Odor/Scent:** Petroleum

**Applicable Materials:** Most Metals

**Resistance:** Chemical; Corrosive Process; Humidity; Moisture; Saltwater; Weather



| SKU       | Container Size | Specific Gravity |
|-----------|----------------|------------------|
| 125-03282 | 16 oz          | 0.693            |

## Zinc-It® Instant Cold Galvanize

### Features:

- Actively fights rust and corrosion with a film of 95% pure zinc
- Protects base metal even when scratched or abraded
- Fast-drying, dries to the touch in 15 minutes
- Excellent weldability

**Color:** Matte

**Chemical Compound:** Acrylic

**Odor/Scent:** Solvent

**Applicable Materials:** Steel

**Resistance:** Corrosive Process; Moisture



| SKU       | Container Size |
|-----------|----------------|
| 125-18412 | 16 oz          |



## Cold Galvanizing Compound

### Features:

- Provides corrosion protection to ferrous metal surfaces
- Good for welded joints, guard rails. Corrugated metal buildings, refinery pipes
- Best long term rust protection
- Dry time set to touch in 3-5 min., hard dry in 48 hrs

**Color:** Gray

**Finish:** Matte

**Chemical Compound:** Zinc



| SKU       | Capacity Vol. | Packing Type | Quantity    |
|-----------|---------------|--------------|-------------|
| 205-7007  | 13 oz         | Aerosol Can  | 12 per case |
| 205-7007G | 1 gal         | Can          | 1 per case  |

## Galva Bright Premium

### Features:

- Stops rust and corrosion on any iron or steel surface
- Zinc-rich formula for long-lasting protection
- Ready to use, the application can be sprayed or brushed on
- Drying Time -Tack-free: 3-5 min., Dust-free: 5-10 min., To touch: 15-20 min., Dry: 24 hrs

**Color:** Gray

**Finish:** Metallic

**Chemical Compound:** Zinc



| SKU      | Capacity Vol. | Container Size |
|----------|---------------|----------------|
| 205-7008 | 13 oz         | 16 oz          |

## DYNAFLUX, INC.

### Spray Galv

### Features:

- Zinc rich coating produces sacrificial protection to stop rust and corrosion on all metal surfaces
  - Any deterioration leads to rust and/or corrosion of the coating rather than the metal surface
  - Equivalent to hot dip galvanizing in cathodic protection and film durability and protects against caustic action salt spray
- Resistance:** Blistering; Gasoline; Oil; Peeling; Rust; Weather



| SKU        | Capacity Wt. | Finish |
|------------|--------------|--------|
| 368-309-16 | 13 oz        | Matte  |

## Ultra Brand Bright Zinc Galvanizing

### Features:

- Produces a hard coat that will stop rust on all metals
- Contains metallic zinc dust, resin and other additives to provide the look of new galvanizing
- Equivalent to hot dip galvanizing in cathodic protection, film durability and protection against caustic action salt spray
- Dries to touch in one hour
- Produce bright finish

**Resistance:** Blistering; Gasoline; Oil; Peeling; Rust; Weather



| SKU          | Capacity Wt. |
|--------------|--------------|
| 368-DF305-16 | 16 oz        |

EUREKA CHEMICAL COMPANY

## Fluid Film® Preventive & Lubricants

### Features:

- Is a lanolin based rust/corrosion preventive and lubricant that provides long term protection and lubrication for all metal surfaces
- Locks out and displaces moisture while lubricating moving parts for extended periods of time



| SKU      | Container Size |
|----------|----------------|
| 275-AS11 | 11 3/4 oz      |



## Cold Galvanize Corrosion Inhibitors

### Features:

- 95% zinc-rich galvanized coating
- Works as a hot dip on ferrous metals indoors and out
- Withstands water temperature up to 212° F (100° C) and continuous dry heat up to 750° F (400° C)
- Flexible coating will not yellow, chalk, crack, or peel
- Electrochemically protect bare metal
- Dries in 3 - 5 minutes



| SKU       | Capacity Vol. |
|-----------|---------------|
| 428-00516 | 14 oz         |

## LPS 3® Premier Rust Inhibitors

### Features:

- Protects steel against rust and corrosion for up to 2 years
- Penetrates to displace moisture
- Resists moisture, sand, dirt, dust and vibration
- Does not contain chlorinated solvents or silicone
- Nonconductive
- Non-staining
- Safe on most surfaces



| SKU       | Capacity Vol. | Packing Type         |
|-----------|---------------|----------------------|
| 428-00305 | 5 gal         | Pail                 |
| 428-00316 | 11 oz         | Aerosol Can          |
| 428-00322 | 22 oz         | Trigger Spray Bottle |
| 428-00355 | 55 gal        | Drum                 |
| 428-03128 | 1 gal         | Container            |



## High Performance V2100 System Galvanizing Compounds

### Features:

- Excellent adhesion to galvanized metal
- Maximum corrosion protection
- Withstands mild chemical fumes and spills
- Contains up to 93% pure zinc in the dry film for ultimate galvanic protection
- Fast dry - less than 30 minutes
- Protects in moderate to extreme environments

**Color:** Gray

**Chemical Compound:** Zinc

**Applicable Materials:** Galvanized Steel

**Resistance:** Corrosive Process



| SKU          | Capacity Wt. |
|--------------|--------------|
| 647-V2185838 | 20 oz        |

## Industrial Choice 1600 System Galvanizing Compounds

### Features:

- Contains a high zinc content in the dry film for ultimate galvanic protection
- Excellent corrosion protection
- Withstands mild chemical fumes and spills
- Great adhesion to galvanized metal' Fast drying
- Ideal for touch-up repair of galvanized metal

**VOC:** 65.0 %

**Chemical Compound:** Alkyd

**Applicable Materials:** Galvanized; Metal

**Resistance:** Solvent



| SKU         | Capacity Wt. |
|-------------|--------------|
| 647-1685830 | 14 oz        |



## Silver Galv Coatings

### Features:

- Produces a dry coating with the bright finish of hot-dip galvanizing
- Recommended dry film thickness of 1.5 to 3.0 mils
- VOC-compliant
- 400 °F dry heat and 100 °F wet heat (non-immersion) resistance
- Resists aromatic hydrocarbon solvents and chlorinated solvents

**Applicable Materials:** Iron; Steel

**Resistance:** Corrosive Process



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S00739 | 14 oz        |

## Zinc-Rich Cold Galvanizing Compounds

### Features:

- Fast-drying, high-solids, high performance, epoxy-based coating
- Provides maximum protection to steel exposed to severe corrosive environments
- 97%-pure zinc dust
- Anti-sag and anti-settling properties

**Color:** Gray

**Applicable Materials:** Most Metals; Steel

**Resistance:** Salt; Water



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S00740 | 14 oz        |



## Bloxide® Rust Preventive Weldable Coatings

**Applicable Materials:** Steel  
**Resistance:** Rust  
**Physical Form:** Liquid  
**Recommended Film Thickness:** Dry: .75 mil; Wet: 3.0 mil



| SKU       | Capacity Vol. | Packing Type |
|-----------|---------------|--------------|
| 719-BL4GL | 1 gal         | Can          |
| 719-BL5GL | 5 gal         | Pail         |
| 719-BLAR  | 12 oz         | Aerosol Can  |



## Brite Zinc Cold Galv

**Features:**

- Repair damaged or welded galvanizing
- Weld-thru, fast dry, meets ASTM A780
- Brite silver, matches hot-dip

**Chemical Compound:** Zinc-Rich  
**Quantity:** 12 per case



| SKU       | Container Size | Packing Type |
|-----------|----------------|--------------|
| 388-B-100 | 12 1/2 oz      | Aerosol Can  |
| 388-B-200 | 1 gal          | Can          |



## CRC Dry Moly Lubricants

**Features:**

- High anti-friction and anti-seizure properties
- Lubricant resists high temperatures, high pressure, water and chemical attack
- Fast drying film resists dirt and dust build-up

**Color:** Dark  
**Odor/Scent:** Solvent  
**Applicable Materials:** Most Metals; Plastic; Rubber



| SKU       | Container Size |
|-----------|----------------|
| 125-03084 | 16 oz          |



## Crown Dry Film Lubricants

**Features:**

- An industrial strength lubricant that is ideal whenever silicone products are not acceptable, and higher temperatures or pressure performance is required
- Reduces clean-up labor time and costs
- Safe for rubber, wood, and metals
- Won't interfere with post-finishing operations
- Durable up to 500°F (260°C) for extended periods
- Unique lubricating qualities; extremely effective against dust



| SKU      | Container Size | Quantity    |
|----------|----------------|-------------|
| 205-6075 | 16 oz          | 12 per case |

## Crown Dry Moly Lubricants

**Features:**

- Withstands extreme temperature and pressure
- Contains no oils or moisture-based diluents
- Quick drying
- Tight adhesion

**Color:** Grayish/Black  
**Odor/Scent:** Ketone



| SKU      | Container Size | Boiling Point   |
|----------|----------------|-----------------|
| 205-6080 | 11.6 oz        | 135 °F - 232 °F |

## Dry Graphite

**Features:**

- Forms a super slippery, non-staining film
- Non-Corrosive
- Non-flaking

**Color:** Black



| SKU      | Container Size | Quantity    |
|----------|----------------|-------------|
| 205-8078 | 12 oz          | 12 per case |

## DIXON GRAPHITE

### Graphokote 495 & 410-S

**Features:**

- Alternative products to the GK 50, 95, and 110-S dry film lubricants line, reformulated with an environmentally friendly, non-HAPs solvent
- Offer reduced odor and VOC content while maintaining excellent performance and drying characteristics

| SKU            | Capacity | Packing Type |
|----------------|----------|--------------|
| 463-GK495-1GAL | 1 gal    | Can          |

| SKU             | Capacity | Packing Type |
|-----------------|----------|--------------|
| 463-GK410S-50LB | 50 lb    | Pail         |



## DIXON GRAPHITE

### Lubricating Natural Graphite

**Features:**

- Finely powdered particles for lubrication of mechanisms with close fitting bearing surfaces
- Use on slug mouth pieces, typesetting machines, gas pot and burner assemblies
- Also for surfaces subjected to high temperatures, pressures and motion, as well as for bushing or swabbing on cylinders, piston rods and crosshead guides
- Sieve size minus 200 mesh

| SKU       | Capacity Wt. |
|-----------|--------------|
| 463-L6355 | 5 lb         |



### Moly-Mist™ Dry Film Lubricants

**Features:**

- Non-flammable
- Prevents galling
- Reduces torque

**Color:** Black

**Physical Form:** Air Dry Solid Film

**Applicable Materials:** Glass; Iron; Most Metals; Plastic; Rubber; Wood

**Resistance:** Corrosive Process; Wear

| SKU       | Capacity Wt. |
|-----------|--------------|
| 399-16041 | 12 oz        |



### Krytox® RFE PFPE High Performance Lubricant



**Features:**

- Specially-formulated synthetic grease designed to provide long-lasting lubrication for all types of moving and/or sliding parts
- This lubricant provides corrosion protection and wear resistance over a broad temperature range

**Color:** White

**NLGI Grade:** 2

**Odor/Scent:** Odorless

**Physical Form:** Paste or Gel

**Applicable Materials:** Most Metals; Plastic; Rubber

**Resistance:** Chemical; Moisture; Water; Wear

| SKU       | Capacity Wt. |
|-----------|--------------|
| 442-29710 | 2 oz         |

### Moly Dry Film Lubricant

**Features:**

- Solid film lubricant for sliding surfaces and slow moving parts
- Temperature resistant up to 750°F as a dry film lubricant, 2400°F as an anti-seize
- Won't squeeze out, burn off, or pick up dirt

**Color:** Black; Grey Black

**Thickener:** Molybdenum

**Chemical Compound:** Graphite; Toluene

**Odor/Scent:** Mild Solvent

| SKU       | Capacity Wt. |
|-----------|--------------|
| 442-39895 | 12 oz        |



### Dry Film PTFE Lubricants

**Features:**

- Dry, thin film won't attract dust or dirt
- Provides excellent lubrication
- Ideal for releasing molded parts
- Nonflammable
- Does not contain silicone or chlorinated solvents
- Safe on most surfaces

**Fill Amount:** 12 oz

| SKU       | Container Size |
|-----------|----------------|
| 428-02616 | 16 oz          |





## Dry Film Silicone Lubricants

### Features:

- Dry film will not attract dust or dirt
- Nonflammable
- Colorless, thin film
- Provides excellent lubrication
- Excellent for releasing molded parts in high temperatures or pressures
- Does not contain chlorinated solvents

**Fill Amount:** 12 oz

**Resistance:** Corrosive Process



| SKU       | Container Size |
|-----------|----------------|
| 428-01616 | 16 oz          |

## Force 842® Dry Moly Lubricants

### Features:

- Fortified with molybdenum disulfide
- Provides a quick-drying, thin film
- For assembly and break-in lubrication
- Works under high temperature: 842° F (450° C) and pressures: 100,000 psi (6890 Bars)
- Prevents seizure of parts
- High adhesion
- Excellent for cables
- Not recommended for friction bearings or light-duty bearings

**Color:** Gray

**Resistance:** Chemical; Dirt; Dust; Water



| SKU       | Container Size | Fill Amount |
|-----------|----------------|-------------|
| 428-02516 | 16 oz          | 11 oz       |



## Dry Graphite Lubes

### Features:

- Ideal where a dry lubricant is required or where petroleum products must be avoided
  - Adheres with minimum pre-treatment
  - Dries rapidly at room temperature
  - Effective up to 850 °F constant/1000 °F intermittent temperature
  - Contains no chlorinated solvents or O.D.P
  - .123 friction coefficient
- Color:** Black



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S00204 | 10 oz        |

## Krytox® Dry Film P.T.F.E. Mold Release Lubricants

### Features:

- Made with DuPont Krytox dry film
- Non-silicone mold release
- Exceptional anti-stick properties that will not transfer to finished parts
- Compatible with most moldable resins, elastomeric compounds, urethanes and styrenes
- Won't attack rubber, paints or metals
- Will not interfere with post-finishing operations
- Contains fluoropolymer
- Contains no CFCs, HCFCs, chlorinated solvents, silicone, or O.D.P

**Color:** White

**Applicable Materials:** Most Metals; Plastic; Rubber



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S00311 | 12 oz        |

## Sprayon® Dry Moly Lubricants

### Features:

- Penetrates pores of substrate and bonds to surface for long-lasting lubrication
- Withstands high pressures up to 50,000 psi
- Contains no chlorinated solvents or O.D.P
- Air dries in 5-to-10 minutes, cures in 2 hours at room temperature
- Works as boundary lube to as cold as -200 °F
- Works to 750 °F intermittently
- Non-conductive
- DanVern™ standard valve

**Color:** Gray



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S00200 | 11 oz        |



## Belt Dressing Lubricants

### Features:

- Tacky, non-drying, water-resistant film minimizes drive belt slippage, resists water wash-off, maintains belt flexibility and prevents loads from slipping on conveyor systems
- Colorless - will not stain finished goods transported on conveyor systems

**Color:** Light Amber

**VOC:** 4.3 lb/gal; 518.0 g/L; 80.0 %

**Thickener:** Polybutene

**Odor/Scent:** Solvent

**Applicable Materials:** Fabric; Rubber

**Resistance:** Water



| SKU       | Container Size |
|-----------|----------------|
| 125-03065 | 16 oz          |

**ITW Professional Brands**

## Cling® Golden Belt Dressing Lubricants

**Features:**

- Stops slipping & squeaking
- Equalizes pressure
- Reduces vibrations
- Improves bearing & belt life

**Color:** Transparent Dark Brown

**VOC:** 5.0 lb/gal

**Odor/Scent:** Solvent



| SKU       | Capacity Wt. | Quantity    |
|-----------|--------------|-------------|
| 253-10095 | 16 oz        | 12 per case |



## Sprayon® Belt Dressing Lubricants

**Features:**

- Conditions belts while increasing pulling power up to 50%
- Reduces squeaky noise
- Apply directly to belts and sheaves of "V" belts
- Contains no asphalt or rosin
- Will not glaze or collect dirt or dust

**Color:** Amber

**Resistance:** Weather



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S00607 | 11 oz        |



## Food Grade Penetrating Oils

**Features:**

- Effective and efficient general purpose lubricant for use on food processing equipment
- Penetrates and loosens rust, scale, corrosion and dirt to free corroded parts and fasteners
- Contains no silicones

**Color:** Clear

**VOC:** 0.0 lb/gal; 0%

**Chemical Compound:** Mineral Oil Based

**Applicable Materials:** Food Processing Equipment



| SKU       | Container Size | Quantity    |
|-----------|----------------|-------------|
| 125-03086 | 16 oz          | 12 per case |

## Power Lube® High-Performance Lubricants With PTFE

**Features:**

- Displaces moisture and seals out corrosion
- Surpasses 3,150 lbs on Falex Load Test (ASTM D-3233)
- Withstands extreme load carrying situations
- Contains PTFE for long-lasting protection

**Color:** Amber

**VOC:** 4.1 lb/gal, 492.0 g/L, 68.2 %

**Chemical Compound:** Petroleum Based

**Odor/Scent:** Wintergreen



| SKU       | Container Size |
|-----------|----------------|
| 125-03045 | 16 oz          |

## Screwloose® Super Penetrants

**Features:**

- Facilitates fast and easy disassembly of mechanical components, fittings, assemblies and other fasteners
- Clear formula contains no dyes and leaves no mess
- Convenient 360° spray valve - can be sprayed from any position

**Color:** Clear Amber

**VOC:** 3.24 lb/gal; 389 g/L; 50 %

**Chemical Compound:** Petroleum Based

**Odor/Scent:** Pleasant

**Applicable Materials:** Most Metals

**Resistance:** Corrosive Process



| SKU       | Container Size |
|-----------|----------------|
| 125-03060 | 16 oz          |



## All-4

**Features:**

- Displaces moisture, lubricates and inhibits corrosion
- Silicone free
- No gummy residue
- Cleans away dirt and grease
- Fills microscopic irregularities on surfaces

| SKU      | Capacity Vol. | Container Size |
|----------|---------------|----------------|
| 205-7340 | 10 oz         | 16 oz          |



## Starrett®

## M1® Industrial Quality All-Purpose Lubricant

**Features:**

- M1 is free of silicone, making it an excellent lubricant
- Deep-down penetration works quickly to free frozen nuts, bolts, and metal parts
- Prevents rust
- Actually removes grease, tar, and grime from metal parts and painted surfaces
- Displaces moisture
- Nonconductive



| SKU       | Capacity Vol. |
|-----------|---------------|
| 681-95173 | 12 oz         |





## KB88 The Ultimate Penetrants

### Features:

- Aggressive formula
- Formulated to attack and quickly release rusted and corroded nuts, bolts, hinges and other frozen components
- High KB solvency value of 151 and low surface tension
- Meets many local, state and federal VOC regulations such as CARB keeping the user within VOC regulatory guidelines
- Penetrates fast and deeper than most other similar products in the market place

**Odor/Scent:** Strong



| SKU       | Capacity Vol. | Container Size |
|-----------|---------------|----------------|
| 428-02316 | 13 oz         | 16 oz          |

## LPS 1® Premium Lubricants

### Features:

- Displaces moisture
- Dries fast and resists oil, dust and dirt build-up
- Ideal for delicate mechanisms
- Loosens rusted or frozen parts
- Nonconductive
- Provides a dry, thin lubricating film
- Provides short term light corrosion resistant barrier
- Safe on paint and most plastics

**Applicable Materials:** Plastic; Rubber

**Resistance:** Corrosive Process; Dirt; Dust; Grease; Moisture; Oil



| SKU       | Capacity Vol. | Packing Type |
|-----------|---------------|--------------|
| 428-00105 | 5 gal         | Pail         |
| 428-00116 | 11 oz         | Aerosol Can  |
| 428-01128 | 1 gal         | Container    |

## LPS 2® Industrial-Strength Lubricants

### Features:

- Displaces moisture
- Loosens rusted or frozen parts
- Nonconductive
- Provides a nondrying, light, oily film for use on indoor/outdoor equipment
- Provides up to one year protection
- Reduces wear caused by friction and corrosion
- Safe on rubber, paint and most plastics
- Strong, multi-purpose lubricant and penetrant with added corrosion protection

**Applicable Materials:** Plastic; Rubber

**Resistance:** Corrosive Process; Moisture; Wear; Weather



| SKU       | Capacity Vol. | Packing Type         |
|-----------|---------------|----------------------|
| 428-00205 | 5 gal         | Pail                 |
| 428-00216 | 11 oz         | Aerosol Can          |
| 428-00222 | 20 oz         | Trigger Spray Bottle |
| 428-00255 | 55 gal        | Drum                 |
| 428-02128 | 1 gal         | Container            |

## Magnum Premium Lubricants w/PTFE

### Features:

- Displaces moisture
- High performance lubricant with PTFE additives
- Ideal for both regular and extreme conditions
- Penetrates and protects metal against rust and corrosion
- Provides complete surface coverage
- Safe to use on most surfaces
- Ultra high lubricity

**Applicable Materials:** Most Surfaces

**Resistance:** Corrosive Process, Moisture

| SKU       | Capacity Vol. |
|-----------|---------------|
| 428-00616 | 11 oz         |



## TKX® All-Purpose Penetrant Lubricant & Protectant

### Features:

- Displaces moisture
- Does not contain CFCs, chlorinated solvents or silicones
- Excellent protective coating for power/hand tools
- Inverted spray valve
- Loosens rusted or frozen parts
- Nonconductive
- Protects against corrosion
- Safe on fabric, plastic, rubber, paint and other finishes

**Applicable Materials:** Most Surfaces

| SKU       | Capacity Vol. | Packing Type |
|-----------|---------------|--------------|
| 428-02016 | 11 oz         | Aerosol Can  |
| 428-02055 | 55 gal        | Drum         |



## X-357 Lubricants

### Features:

- A special extreme pressure lubricant that penetrates and adheres, water resistant and unaffected by temperature extremes
- Contains moly-disulfide

| SKU           | Capacity Wt. |
|---------------|--------------|
| 293-L0149-063 | 11 oz        |



## MICRO-MIST

### Foaming Lubricant

### Features:

- A special blend of friction seekers, lubricants and corrosion inhibitors
- Stop rust and corrosion
- Displace moisture
- Eliminate squeaks

| SKU      | Capacity Wt. |
|----------|--------------|
| 480-1615 | 16 oz        |





## Liquid Wrench® Super Lubricants

### Features:

- Frees rusted parts
- Helps stop corrosion on nuts, bolts, fasteners, chains, cables, linkages, valves and fittings, lawn mowers and auto engines
- Displaces water from wet surfaces and leaves rust inhibiting film
- Dries out engines, spark plugs, coils, switches and wiring
- Harmless to fabrics, plastic and leather

**Applicable Materials:** Most Metals

**Resistance:** Corrosive Process; Moisture



| SKU       | Capacity Wt. | Quantity    |
|-----------|--------------|-------------|
| 615-L2-12 | 11 oz        | 12 per case |

## Liquid Wrench® Super-Penetrants

### Features:

- A powerful blend of quick-acting, fast penetrating solvents that loosens rusted nuts, bolts and parts in seconds

**Quantity:** 12 per case



| SKU       | Capacity Vol. | Packing Type   |
|-----------|---------------|----------------|
| 615-L1-12 | 11 oz         | Aerosol Can    |
| 615-L1-16 | 1 pt          | Bottle w/Spout |



## Rustbreaker™ Penetrants

### Features:

- Inhibits corrosion on unpainted metal surfaces
- High-solids, non-staining white grease
- Jet stream sprays up to two feet
- Contains no CFCs, HCFCs, chlorinated solvents, or O.D.P.
- Fast acting
- Creep properties
- Equipped with Easy-Action Tilt-Spray valve
- Non-staining

**Color:** Transparent

**Dielectric Strength:** 33,000 V/mil

**Viscosity @ Temp.:** 313 SUS @ 100 °F

**Applicable Materials:** Plastic

**Resistance:** Corrosive Process; Moisture



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S00103 | 12 oz        |

## The Protector™ #711® Lubricants

### Features:

- Protects metal surfaces from corrosive elements
- Eliminates moisture-induced short circuits
- Safe on plastic surfaces
- Delivers 17% more usable product with its CO2 propellant
- Formulated to ensure maximum moisture displacement
- Ultra-thin and greaseless

**Dielectric Strength:** 47,000 V/mil



| SKU        | Capacity Wt. | Quantity    |
|------------|--------------|-------------|
| 425-S00711 | 16 oz        | 12 per case |



## Super Lube® Aerosols

### Features:

- Provides more reliable lubrication and outlasts petroleum based greases and oils
- Remains free flowing in freezing temperatures
- Will not stain
- Won't drip, run, or evaporate
- Prevents rust and corrosion while reducing friction

**Color:** Translucent White

**Chemical Compound:** Synthetic

**Odor/Scent:** Odorless

**Applicable Materials:** Fabric; Leather; Plastic; Rubber; Wood

**Resistance:** Corrosive Process; Dirt; Dust; Saltwater; Water



| SKU       | Capacity Wt. |
|-----------|--------------|
| 692-31110 | 11 oz        |



## Industrial Lubricants

### Features:

- Lubricates with oils, additives and PTFE
- Penetrates inaccessible areas
- Protects against moisture and corrosion damage

**Chemical Compound:** Petroleum

**Applicable Materials:** Most Metals, Wood, Plastic, Rubber

**Resistance:** Moisture, Corrosive Process, Wear, Dirt, Dust



| SKU         | Capacity Vol. | Packing Type         | Quantity    |
|-------------|---------------|----------------------|-------------|
| 425-TF20025 | 6 oz          | Aerosol Can          | 12 per pack |
| 425-TF20027 | 12 oz         | Aerosol Can          | 12 per pack |
| 425-TF29200 | 18 oz         | Trigger Spray Bottle | 6 per pack  |



### Kopr-Kote® Tool Joint & Drill Collar Compounds

**Features:**

- KOPR-KOTE® Oilfield drill collar and tool joint compound is a premium-quality, unleaded compound containing copper flake, graphite, and other natural extreme pressure and anti-wear additives

**Color:** Copper

**NLGI Grade:** 1

**Thickener:** Aluminum Complex

**Chemical Compound:** Petroleum Based

**Applicable Materials:** Steel

**Resistance:** Corrosive Process; Water; Wear



| SKU       | Capacity Vol. |
|-----------|---------------|
| 399-10115 | 5 gal         |



### Chain & Wire Rope Lubricants

**Features:**

- Resists water wash-off and high-temperature sling off
- Absorbs pin/bushing shock and cushions rollers, pins and bushing
- Can be applied with guards in place to eliminate costly downtime

**Color:** Amber

**VOC:** 608 g/L

**Odor/Scent:** Solvent

**Applicable Materials:** Most Metals

**Resistance:** Water



| SKU       | Container Size |
|-----------|----------------|
| 125-03050 | 16 oz          |

### Food Grade Chain Lubes

**Features:**

- No known ozone depleting chemicals
- Non-drying film
- Designed to keep roller drive and conveyor chains lubricated
- Foaming action
- P-stream button dispenses narrow, forceful stream
- Reduces friction and wear that causes metal fatigue, including in surface cracks and overhead applications
- Uses include non-food applications as well as where incidental food contact may occur, including in meat and poultry plants

**Color:** Amber

**Chemical Compound:** Mineral Oil

**Applicable Materials:** Most Metals



| SKU       | Container Size | Quantity    |
|-----------|----------------|-------------|
| 125-03055 | 16 oz          | 12 per case |



### Gear, Chain and Cable Lubricant

**Features:**

- Protects and prolongs the life of gears, chains, wire rope, and cable
- Repels dirt, sand, and dust with minimum "throw-off" from centrifugal force
- Contains no ozone depleting compounds

**Color:** Clear

**Odor/Scent:** Petroleum

**Applicable Materials:** Aluminum; Copper; Magnesium Alloy; Steel

**Resistance:** Corrosive Process; Dirt



| SKU       | Capacity Wt. |
|-----------|--------------|
| 442-81251 | 12 oz        |



### Chain Lubricant Food Grade

**Features:**

- Excellent for applications involving incidental food contact on food processing equipment
- Foaming action provides extra penetration and lubrication
- Oily, wet film extends chain life
- Nonflammable

**Color:** Clear

**VOC:** 15.0 %

**Odor/Scent:** Mild



| SKU       | Container Size | Fill Amount |
|-----------|----------------|-------------|
| 428-06016 | 16 oz          | 12 oz       |

### ChainMate® Chain & Wire Rope Lubricants

**Features:**

- Increases chain and wire rope life
- Effective under extreme temperature and pressure ranges
- Deep penetration to the core of wire ropes
- Reduces wear caused by friction and corrosion
- Lubricant and corrosion protectant

**Fill Amount:** 11 oz

**Color:** Gray

**Chemical Compound:** Molybdenum

**Resistance:** Corrosive Process; Wear



| SKU       | Container Size |
|-----------|----------------|
| 428-02416 | 16 oz          |



## Chain & Cable Fluids

### Features:

- Superior penetrating oil
- A cleansing non-gumming oil
- Lubricates wire rope, chains, cables, any moving metal surfaces
- Prevents rust and corrosion
- Protects brightwork, loosens rusty nuts and bolts
- Ideal for tapping and drilling

**Color:** Amber

**Chemical Compound:** Petroleum Based

**Odor/Scent:** Sweet

| SKU           | Capacity Wt. |
|---------------|--------------|
| 293-L0135-063 | 12 oz        |



## Silicone Lubricant

### Features:

- Dries fast to eliminate squeaks, prevents sticking, seals out moisture protecting against rust and corrosion, preserves plastic, rubber, and leather
- Prolongs machine and cutting tool life by helping to prevent glue, wax, ink and paint buildup

| SKU              | Capacity Wt. |
|------------------|--------------|
| 405-021200-85822 | 24 oz        |



## LU™ 201 Open Gear & Wire Rope Lubricants

### Features:

- Penetrates to core of wire rope, minimizing internal friction
- "Travels" on metal surfaces, displacing water to provide excellent rust protection
- Contains no chlorinated solvents or O.D.P
- Does not rub off
- Equipped with extension tube
- Withstands high pressures
- Does not become brittle or break down while working

**Color:** Black

**Applicable Materials:** Most Metals

**Resistance:** Water; Wear; Weather

| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S00201 | 12 oz        |



## Extreme Duty Silicone Lubricants

### Features:

- Reduces friction and galling even on metal-to-metal contact areas
- High temperature (-100 to 450 F), high pressure ( withstands 1200 psi Falex test)
- High grade release and parting agent
- Clear, non-staining, odorless film resists moisture
- Convenient 360° spray valve - can be sprayed from any position

**Color:** Clear

**Odor/Scent:** Solvent

**Applicable Materials:** Most Metals

| SKU       | Container Size |
|-----------|----------------|
| 125-03030 | 16 oz          |



## Moly Chain & Pin Bushing Lubes

### Features:

- Foaming action penetrates close tolerances of chain drive bushings and pins
- Reduces wear, increases chain life up to three times when applied regularly
- Spray-Any-Way valve for application in upright or inverted position
- Non-drying
- Long lasting
- Contains no chlorinated solvents or O.D.P

**Applicable Materials:** Most Metals

**Resistance:** Wear



## Food Grade Silicone Lubricants

### Features:

- Harmless to most rubbers and plastics
- Wide effective temperature range
- Excellent release agent and lubricant for all surfaces
- Convenient 360° spray valve - can be sprayed from any position
- Colorless, odorless low-viscosity lubricant
- Prevents sticking without transferring to end products
- Spray-in-any-position valve
- Contains no chlorinated solvents or O.D.P

**Color:** White

**VOC:** 5.8 lb/gal; 641.0 g/L; 97.0 %

**Thickener:** Silicone

**Odor/Scent:** Solvent

**Applicable Materials:** Most Metals; Plastic; Rubber

**Resistance:** Weather

| SKU       | Container Size |
|-----------|----------------|
| 125-03040 | 16 oz          |



Industrial Safety Welding Oilfield Construction



## Loctite Silicone Lubricant

### Features:

- Multi-purpose lubricant stops sticking, friction, squeaking, and binding of moving parts
- Will not mar paint, rubber, or plastic surfaces
- Waterproofs and electrically insulates
- Non-gumming

**Color:** Opaque

**Chemical Compound:** Silicone

**Odor/Scent:** Negligible

**Applicable Materials:** Most Metals; Plastic; Rubber

**Resistance:** Alcohol; Moisture; Oil; Water



| SKU       | Capacity Wt. |
|-----------|--------------|
| 442-51360 | 5.3 oz       |



## Heavy-Duty Silicone Lubricants

### Features:

- Colorless and odorless
- Dry, nonstaining
- Eliminates sticking, binding and squeaking
- Excellent lubricity
- Ideal for rubber and plastic surfaces
- Safe on most surfaces

**Applicable Materials:** Most Metals; Plastic; Rubber



| SKU       | Capacity Vol. |
|-----------|---------------|
| 428-01516 | 13 oz         |

## LPS® Food Grade Silicone Lubricants

### Features:

- Dry film will not attract dust or dirt
- Provides excellent lubrication
- Contains silicone
- Nonstaining
- Ideal for releasing molded parts
- Fast evaporating
- Does not contain chlorinated solvents
- Noncorrosive



| SKU       | Capacity Vol. |
|-----------|---------------|
| 428-01716 | 10 oz         |



## Liquid Wrench® Silicone Spray

### Features:

- Provides slick coat of protection
- Waterproofs parts, stops rust
- Extends life of metal & non-metal surfaces
- Clear, wet film protects
- Non-stick coating repels moisture
- Low odor



| SKU       | Capacity Wt. |
|-----------|--------------|
| 615-M9-14 | 11 oz        |



## Food Grade Silicone Lubricants with Extension

### Features:

- Harmless to most rubbers and plastics
- Wide effective temperature range
- Excellent release agent and lubricant for all surfaces
- Convenient 360° spray valve - can be sprayed from any position
- Colorless, odorless low-viscosity lubricant
- Prevents sticking without transferring to end products
- Spray-in-any-position valve
- Contains no chlorinated solvents or O.D.P

**Color:** Clear

**Thickener:** Silicone

**Applicable Materials:** Most Metals; Plastic; Rubber; Wood

**Resistance:** Corrosive Process; Water



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S00210 | 10 oz        |

## Premium Silicone Lubes

### Features:

- 6.6% silicone formula
- Stops squeaks and sticking, eliminates friction, repels water and prevents freezing
- Keeps rubber soft and flexible

**Thickener:** Silicone

**Applicable Materials:** Fabric; Leather; Most Metals; Rubber; Wood

**Resistance:** Water; Weather



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S01324 | 10 oz        |



## Band-Ade® Semi-Synthetic Sawing Fluids

**Features:**

- Reduces machine wear and improves band saw tool life
- Surfaces can be welded or painted over
- Gentle to operators' hand: does not remove all oil from skin
- Does not contain chlorine, sulfur, silicone, petroleum oils or sulfonates
- Biodegradable



| SKU       | Capacity Vol. |
|-----------|---------------|
| 433-68003 | 5 gal         |



## Tapmatic® #1 Gold Cutting Fluids

**Features:**

- Excellent for steel and aluminum
- For low speed, high pressure applications
- Minimizes torque increases
- Does not contain chlorinated paraffins, water, solvents, or inactive fillers
- Aerosol provides a pinpoint stream with foaming action

**Color:** Gold

**Applicable Materials:** All Metals



| SKU       | Capacity Vol. | Packing Type |
|-----------|---------------|--------------|
| 428-40312 | 11 oz         | Aerosol Can  |
| 428-40320 | 16 oz         | Bottle       |

## Tapmatic® AquaCut Cutting Fluids

**Features:**

- Water-based formula
- Excellent in applications where cooling of the tool is desired
- Nonflammable
- Nonhazardous
- Does not contain sulfur, chlorine, or oils
- Safe on all metals, except magnesium
- Corrosion inhibitors prevent flash rusting

**Color:** Turquoise

**Odor/Scent:** Cinnamon

**Applicable Materials:** All Metals; Except Magnesium

**Resistance:** Corrosive Process; Moisture



| SKU       | Container Size |
|-----------|----------------|
| 428-01216 | 16 oz          |

## Tapmatic® Edge Creme Cutting Fluids

**Features:**

- Excellent for vertical applications
- Biodegradable
- Apply to cutting tools before tapping or reaming
- Squeeze tube allows easy usage
- Does not contain any hazardous chemicals
- Ecological and economical
- For use when drilling, tapping blind holes, forming, bending, pre-coating fasteners and lubricating rubber seals

**Color:** White

**Applicable Materials:** All Metals



| SKU       | Container Size |
|-----------|----------------|
| 428-43100 | 10 oz          |

## Tapmatic® Edge Lube Cutting Fluids

**Features:**

- White solid waxy bar
- Biodegradable
- Excellent for belt, wheel, or disc grinding, and sawing applications
- Eliminates heat build-up and belt loading
- Does not contain any hazardous chemicals
- Extends grinding wheel life
- Does not contain any hazardous chemicals
- Low toxicity

**Color:** White

**Applicable Materials:** All Metals



| SKU       | Container Size |
|-----------|----------------|
| 428-43200 | 13 oz          |

## Tapmatic® Natural Cutting Fluids

**Features:**

- Nontoxic and Nonhazardous
- Biodegradable
- Does not irritate the skin, eyes or respiratory tract
- Does not contain sulfur, chlorine, chlorinated solvents, water, mineral oil, or inactive fillers
- Great for steel and aluminum
- High performance lubricating ability eliminates galling and seizing

**Color:** Green

**Applicable Materials:** All Metals



| SKU       | Container Size |
|-----------|----------------|
| 428-44220 | 16 oz          |



## Tapmatic® TriCut Cutting Fluids

### Features:

- Excellent on stainless steel and other hard to machine metals
- Extends tool life
- Improves surface finish
- Allows increased removal rates
- Reduces friction
- Is non-corrosive to steel

**Color:** Dark Brown

**Odor/Scent:** Mild

**Applicable Materials:** Most Metals;  
Not Recommended for Aluminum



| SKU       | Container Size |
|-----------|----------------|
| 428-05316 | 16 oz          |



## Rapid Tap™ Metal Cutting Fluid

### Features:

- Greatly extended tool life
- Super-fine machined finish in operation after operation
- Excels in tough materials
- Contains no 1,1,1-trichloroethane or other ozone-depleting chemicals



| SKU              | Capacity Vol. | Packing Type |
|------------------|---------------|--------------|
| 618-01G-NRT      | 1 gal         | Plastic Jug  |
| 618-RAPTAP-PTNEW | 1 pt          | Can          |



## Liquid Lubricants

### Features:

- The original, proven, safe tapping fluid made from a unique blend of synthetic additives for use on all metals
- Does not contain 1, 1, 1-trichloroethane
- No mineral oils or solvents
- No oily residue

**Color:** Amber

**Odor/Scent:** Mild

**Applicable Materials:** All Metals



| SKU       | Capacity Vol. |
|-----------|---------------|
| 648-71912 | 16 oz         |



## Tap Magic Aluminum

### Features:

- Use for any and all cutting operations on aluminum
- Yields a beautiful micro-fine finish
- Ozone-friendly and completely free of 1,1,1 trichloroethane
- Dissipates heat rapidly and provides closer tolerances
- Also highly effective on magnesium and other nonferrous metals



| SKU        | Capacity Vol. |
|------------|---------------|
| 702-20016A | 16 oz         |

## Tap Magic ProTap

### Features:

- Our original biodegradable cutting fluid
- Totally free of all regulated chemicals
- Highly effective for all cutting operations on all metals
- Extends tool life



| SKU         | Capacity Vol. | Packing Type |
|-------------|---------------|--------------|
| 702-30004P  | 4 oz          | Can w/Spout  |
| 702-30012PL | 12 oz         | Aerosol Can  |
| 702-30016P  | 16 oz         | Can w/Spout  |
| 702-30128P  | 1 gal         | Can          |

## Tap Magic w/EP-Xtra®

### Features:

- Outstanding performance for any cutting operation on any metal
- Absolutely without equal on hard metals and on cuts requiring extreme pressure or long cutting times



| SKU         | Capacity Vol. | Packing Type      |
|-------------|---------------|-------------------|
| 702-10004E  | 4 oz          | Can w/Spout       |
| 702-10012EL | 12 oz         | Aerosol Can       |
| 702-10016E  | 16 oz         | Plastic Container |
| 702-10128E  | 1 gal         | Can               |
| 702-10640E  | 5 gal         | Can               |



## XTRA-THICK® Cutting Fluid

**Features:**

- Extreme performance for hard metals
- Virtually eliminates work hardening
- Single application stays with tool for cuts with long duration—all the way to the bottom of most holes
- Clinging action keeps fluid on work piece during high-speed rotation
- Contains the proprietary EP-X® additive for a performance boost

**Color:** Brown

**Applicable Materials:** Stainless; Titanium; Inconel; Pipe Threading



| SKU        | Capacity Vol. |
|------------|---------------|
| 702-70016T | 16 oz         |



## Jump Start™ Starting Fluid with Lubricity

**Features:**

- Assures fast, economical starts in extremely cold or humid climates
- Upper cylinder lubricant minimizes wear during cold starts
- Effective to -65°F
- For diesel and gasoline engines

**Odor/Scent:** Ether



| SKU       | Container Size |
|-----------|----------------|
| 125-05671 | 16 oz          |



## Pyroil Starting Fluids

**Features:**

- Starts engines quickly and reduces drain on batteries
- For engines requiring the most powerful starting aid
- Contains an upper-cylinder lubricant
- Fits diesel injector systems
- Gives smooth starts in all kinds of weather



| SKU        | Capacity Vol. |
|------------|---------------|
| 145-602373 | 11 oz         |



## Starting Fluids

**Applications:** Engine

| SKU        | Capacity Vol. | Brand    | Quantity    |
|------------|---------------|----------|-------------|
| 615-M35-15 | 11 oz         | Instant® | 12 per case |
| 615-M38-15 | 11 oz         | Thrust®  | 12 per case |



## CRC White Lithium Grease

**Features:**

- Excellent heat and water resistance
- Rust and oxidation inhibitors for superior metal protection
- Smooth, buttery consistency provides optimum surface coverage
- Produces a tough, high viscosity film
- White color allows for easy visual inspection of film coverage

**NLGI Grade:** 2


**Thickener:** Lithium

**Odor/Scent:** Solvent

**Physical Form:** Paste or Gel

**Applicable Materials:** Most Metals

**Resistance:** Heat; Water



| SKU       | Container Size |
|-----------|----------------|
| 125-03080 | 16 oz          |

## Extreme Pressure Moly-Graph® Multi-Purpose Grease

**Features:**

- Lithium complex, NLGI #2 grease
- "Moly" and graphite help establish a fine micron plating on all working surfaces
- Maintains 40 lb Timken OK Load
- Typical drop point: 380°F

**NLGI Grade:** 2

**Color:** Gray

**VOC:** 1.5 %

**Thickener:** Lithium Complex

**Chemical Compound:** Graphite; Molybdenum

**Odor/Scent:** Petroleum

**Physical Form:** Paste or Gel



| SKU        | Capacity | Quantity    |
|------------|----------|-------------|
| 125-SL3330 | 14 oz    | 10 per case |





## Lithium General Purpose Grease

### Features:

- Lithium base, NLGI #2 grease
- Extremely stable, designed for light duty applications
- Excellent water resistance
- Typical drop point: 380° F
- Contains Rust & Oxidation Inhibitors

**NLGI Grade:** 2

**Viscosity @ Temp.:** 1,100 SUS @ 100 °F

**Color:** Amber

**VOC:** 0.1 lb/gal; 1.5 %; 14.0 g/L

**Thickener:** Lithium

**Odor/Scent:** Petroleum

**Physical Form:** Semi-Solid

**Resistance:** Heat; Water



| SKU        | Container Size |
|------------|----------------|
| 125-SL3310 | 14 oz          |

## Red Grease

### Features:

- For heavy-duty use, including under extreme pressure, to reduce wear, galling, and scarring
- Long lasting
- Smooth texture
- Thick

**NLGI Grade:** 2

**Physical Form:** Paste/Gel

**Resistance:** Acid; Alkali; Corrosive Process; Oxidation; Salt; Steam; Water; Weather



| SKU       | Container Size | Quantity    |
|-----------|----------------|-------------|
| 125-03079 | 16 oz          | 12 per case |

## Sta-Plex™ Grease

### Features:

- Extremely versatile lithium complex, NLGI #2 grease with excellent high temperature lubrication
- Protects against rust and oxidation
- Maintains 60 lb Timken OK Load
- Typical drop point: 500° F

**NLGI Grade:** 2

**Color:** Red

**VOC:** 0.1 lb/gal; 1.5 %; 14.0 g/L

**Thickener:** Lithium

**Odor/Scent:** Mild Petroleum

**Physical Form:** Semi-Solid

**Resistance:** Corrosive Process; Wear



| SKU        | Container Size |
|------------|----------------|
| 125-SL3190 | 14 oz          |



## Heavy Duty Open Gear & Wire Rope Lubes

### Features:

- A high-grade moly grease that won't become brittle, is not affected by weather, and has outstanding adhesion properties
- Minimizes internal friction
- Withstands extreme pressures with maximum adhesion
- Displaces water to provide excellent rust and corrosion protection
- Prevents metal bearing surfaces from becoming crazed and brittle
- Withstands wash downs; migrates on metal surfaces to the core of wire rope and spring windings

**Grease Type:** Asphaltic



| SKU      | Container Size | Quantity    |
|----------|----------------|-------------|
| 205-7045 | 16 oz          | 12 per case |



## Clover® Silicon Carbide Grease Mix

### Features:

- Standard abrasive paste for fast metal removal
- Produces a smooth, flat surface but not a polished one
- Leaves a rust preventing film on lapped surfaces
- Uses include lapping and honing and grinding activities for valve seats, gear teeth, dowel holes in dies, bushings, and more

**Color:** Grey Black

**Abrasive Material:** Silicon Carbide

**Carrier Material:** Petroleum



| SKU       | Grit |
|-----------|------|
| 442-39452 | 120  |
| 442-39473 | 80   |
| 442-39549 | 600  |

## Food Grade Grease

### Features:

- Extreme pressure grease
- Protects after flushouts and steam cleaning

**NLGI Grade:** 2

**Color:** White

**Odor/Scent:** Grease

**Physical Form:** Paste or Gel

**Applicable Materials:** Bronze; Most Metals; Steel

**Resistance:** Moisture; Water



| SKU       | Capacity Wt. |
|-----------|--------------|
| 442-51252 | 14 1/2 oz    |



## Red and Redi Multi-Purpose Red Grease

### Features:

- Delivers excellent lubrication
- Prevents rust, corrosion and oxidation
- Red color allows easy visual inspection
- Remains effective at extremely high temperatures
- Penetrates quickly
- Reduces friction and vibration
- Resists shock

Fill Amount: 11 oz

NLGI Grade: 2

Color: Red



| SKU       | Container Size |
|-----------|----------------|
| 428-05816 | 16 oz          |

## ThermaPlex® Hi-Temp Bearing Grease

### Features:

- Reduces risk of bearing failure at high temps
- Excellent high temperature performance
- Resists carbonization at high temperatures
- Extends relubrication intervals
- Very high dropping point
- Ensures optimal production rates
- Reduces grease consumption
- Very good vibration resistance
- Reduces need for multiple greases

NLGI Grade: 2

Color: Dark Brown

Physical Form: Paste

Resistance: Impact



| SKU       | Container Size |
|-----------|----------------|
| 428-70214 | 14.1 oz        |

## ThermaPlex® Multi-Purpose Bearing Grease

### Features:

- Excellent load carrying properties
- Extends re-lubrication periods
- Prolongs bearing life
- Good corrosion resistance
- Ideal for lubricating all types of bearings
- Reduces grease consumption

NLGI Grade: 2

Color: Blue

Physical Form: Paste

Resistance: Corrosive Process



| SKU       | Container Size |
|-----------|----------------|
| 428-70614 | 14.1 oz        |

## White Lithium Multi-Purpose Grease

### Features:

- Does not contain any chlorinated solvents
- Produces a long lasting, protective film against rust and corrosion
- PTFE additives for superior lubrication
- Rapidly forms into a pure white grease
- White color allows easy visual inspection

Fill Amount: 10 oz

NLGI Grade: 2

Color: White

Thickener: Lithium



| SKU       | Container Size |
|-----------|----------------|
| 428-03816 | 16 oz          |



## 100 & 130 Series Multi-Purpose Grease

### Features:

- For applications where temperatures do not exceed 170°F/77°C
- Uses include motor assemblies

Grease Type: Calcium

NLGI Grade: 0

Viscosity @ Temp.: 300 SUS @ 100 °F

Color: Off-White

Odor/Scent: Mineral Oil

Physical Form: Paste or Gel

Resistance: Water



| SKU           | Capacity Wt. | Packing Type |
|---------------|--------------|--------------|
| 293-L0034-076 | 3/8 oz       | Tube         |
| 293-L0034-035 | 35 lb        | Pail         |

## 1240 Series Multi-Purpose Grease

### Features:

- Highly water resistant and tacky, they are designed for applications where the grease is subjected to heavy pressure and shock loads
- Lithium complex soap with mineral oil and additives

NLGI Grade: 2

Color: Off-White

Thickener: Lithium Polymer

Odor/Scent: Mineral Oil

Physical Form: Paste or Gel

Resistance: Corrosive Process; Water



| SKU           | Capacity Wt. |
|---------------|--------------|
| 293-L0106-098 | 14 1/2 oz    |



## 630 Series Multi-Purpose Grease

### Features:

- High film strength, exceptional resistance to water, steam and other adverse conditions
- Available in 4 NLGI densities for a variety of applications
- Capable of withstanding extreme pressure

**Grease Type:** Lithium

**Color:** Tan

**Odor/Scent:** Mineral Oil

**Physical Form:** Paste or Gel

**Resistance:** Water

### Features:

- For automatic dispensers, centralized systems, and large lines, operating under adverse conditions

| SKU           | Capacity Wt. | Packing Type | NLGI Grade |
|---------------|--------------|--------------|------------|
| 293-L0067-092 | 10 oz        | Tube         | 1          |
| 293-L0067-001 | 14 oz        | Can          | 1          |
| 293-L0067-035 | 35 lb        | Pail         | 1          |

### Features:

- For multi-purpose applications such as general greasing and bearings operating under adverse conditions

| SKU           | Capacity Wt. | Packing Type | NLGI Grade |
|---------------|--------------|--------------|------------|
| 293-L0072-098 | 14 1/2 oz    | Cartridge    | 2          |
| 293-L0072-035 | 35 lb        | Pail         | 2          |

## 930 Series Multi-Purpose Grease

### Features:

- Formulated for higher temperature applications
- They are shear stable, multi-purpose greases for both plain and anti-friction bearings
- This series works well up to 375°F and for short intervals up to 40°F
- Non-melt drop point

**Grease Type:** Bentone

**Color:** Tan

**Odor/Scent:** Mineral Oil

**Physical Form:** Paste or Gel

**Resistance:** Water; Wear

### Features:

- For high temperature applications, automatic dispensers, and under extreme pressure. Uses include both plain and anti-friction bearings

| SKU           | Capacity Wt. | Packing Type | NLGI Grade |
|---------------|--------------|--------------|------------|
| 293-L0096-001 | 14 oz        | Can          | 1          |
| 293-L0096-098 | 14 1/2 oz    | Cartridge    | 1          |
| 293-L0096-035 | 35 lb        | Pail         | 1          |
| 293-L0096-039 | 120 lb       | Drum         | 1          |

### Features:

- Smooth, tan grease
- Capable of withstanding extreme pressure

| SKU           | Capacity Wt. | Packing Type | NLGI Grade |
|---------------|--------------|--------------|------------|
| 293-L0100-098 | 14 1/2 oz    | Cartridge    | 2          |



## Aero Grease

### Features:

- For cold temperature applications down to -60°F
- Provides low torque and outstanding oxidation resistance

- Excellent for garage door mechanisms

**Grease Type:** Lithium

**NLGI Grade:** 1

**Resistance:** Water

| SKU           | Capacity Wt. |
|---------------|--------------|
| 293-L0113-039 | 120 lb       |



## Automotive Lubricants

### Features:

- A smooth light-bodied grease made especially for motor assembly

- Prevents "Dry-Start"

- Provides lubrication during the initial start up before the motor oil has circulated

- Protects freshly machined engine parts

from rust and corrosion

- Uses include motor assemblies and transmission assemblies

**Color:** Dark Green

**Chemical Compound:** Petroleum Based

**Odor/Scent:** Fatty

**Physical Form:** Paste or Gel

**SAE No.:** 70

| SKU           | Capacity Wt. |
|---------------|--------------|
| 293-L0034-094 | 10 oz        |



## FGL Series Food Machinery Grease

### Features:

- High load-carrying capability

- High shear stability

- Smooth, tacky, white grease

- Anti-wear, anti-rust, anti-corrosion, and anti-oxidation additives

- Resistance to water and caustic wash down

- Designed for the food and beverage industries

- For use in a variety of quick and clean applications, where a class H-1 oil is required

**NLGI Grade:** 2

**Color:** White

**Thickener:** Aluminum Complex

**Odor/Scent:** Oil

**Physical Form:** Paste or Gel

**Resistance:** Corrosive Process; Water; Wear

| SKU           | Capacity  |
|---------------|-----------|
| 293-L0232-098 | 14 1/2 oz |





## FML Series Multi-Purpose Food Grade Grease

### Features:

- Anti-wear, anti-rust, anti-corrosion, and anti-oxidation additives
- Used in the food processing industry for quick, clean applications

**Grease Type:** Anhydrous Calcium

**NLGI Grade:** 2

**Color:** White

**Thickener:** Anhydrous Calcium

**Odor/Scent:** Mineral Oil

**Physical Form:** Paste or Gel

**Resistance:** Water



| SKU           | Capacity Wt. |
|---------------|--------------|
| 293-L0145-098 | 14 1/2 oz    |

## Gear Shield Series Open Gear Grease

### Features:

- Made for all types of open gears
- Gear Shield Extra Heavy is for adverse conditions where gears are exposed to abrasive conditions such as quarry and mining operations
- Low-temp gear shield is for cold weather applications
- Anti-wear, anti-rust, anti-corrosion, and anti-oxidation properties

**Grease Type:** Lithium

**Color:** Black

**Thickener:** Lithium

**Odor/Scent:** Mineral Oil

**Physical Form:** Paste or Gel

**Resistance:** Water; Wear



| SKU           | Capacity Wt. | Packing Type    | NLGI Grade |
|---------------|--------------|-----------------|------------|
| 293-L0152-000 | 10 1/2 oz    | Caulk Cartridge | 2.5        |
| 293-L0152-063 | 11 oz        | Spray Can       | 2          |

## High Temp Multi-Purpose Grease

### Features:

- Multi-Purpose, high temperature grease
- Non-melt type, workable with frequent lube intervals

**Grease Type:** Bentone

**NLGI Grade:** 2

**Resistance:** Water



| SKU           | Capacity Wt. |
|---------------|--------------|
| 293-L0161-098 | 14 1/2 oz    |

## Low Temp Multi-Purpose Grease

### Features:

- Multi-purpose, anhydrous calcium based grease for cold temperatures
- Excellent multi-purpose low temperature grease
- Anti-wear, anti-rust, anti-corrosion, and anti-oxidation properties

**Grease Type:** Anhydrous Calcium

**NLGI Grade:** 1.5

**Color:** Off-White

**Thickener:** Calcium

**Odor/Scent:** Mineral Oil

**Physical Form:** Paste or Gel

**Resistance:** Cold-Weather; Water



| SKU           | Capacity Wt. |
|---------------|--------------|
| 293-L0172-098 | 14 1/2 oz    |

## MAG-1 Grease

### Features:

- Smooth, off-white grease
- Capable of withstanding extreme pressure
- Anti-wear, anti-rust, anti-corrosion, and anti-oxidation properties
- For use at low temperatures, for multi-purpose applications, and applications such as freezers and fifth wheels

**Grease Type:** Lithium Polymer

**NLGI Grade:** 1

**Color:** Off-White

**Thickener:** Lithium Polymer

**Odor/Scent:** Mineral Oil

**Physical Form:** Paste or Gel

**Applicable Materials:** Most Metals; Plastic; Rubber

**Resistance:** Water



| SKU           | Capacity Wt. |
|---------------|--------------|
| 293-L0189-098 | 14 oz        |

## No. 1200-2 Multi-Purpose Grease

### Features:

- It provides a high film strength, great shear stability, anti-wear and extreme pressure additives

**Grease Type:** Lithium

**NLGI Grade:** 2

**Resistance:** Water



| SKU           | Capacity Wt. | Packing Type |
|---------------|--------------|--------------|
| 293-L0102-098 | 14 1/2 oz    | Cartridge    |
| 293-L0102-035 | 35 lb        | Pail         |



## No. 3000 Multi-Purpose Grease

### Features:

- Provide durable, tenacious, adhesive films to protect against water, rust and corrosive contaminants
- Protects against water, rust, and corrosive contaminants
- For applications such as industrial, construction, and mining equipment, under adverse conditions

**Grease Type:** Moly-Lithium

**NLGI Grade:** 2

**Color:** Black

**Thickener:** Lithium

**Odor/Scent:** Mineral Oil

**Physical Form:** Paste or Gel

**Resistance:** Corrosive Contaminants; Corrosive Process; Rust; Water



| SKU           | Capacity Wt. |
|---------------|--------------|
| 293-L0108-098 | 14 1/2 oz    |

## No. 3000-W Multi-Purpose Grease

### Features:

- Provide durable, tenacious, adhesive films to protect against water, rust and corrosive contaminants
- Protects against contaminants
- For use in cold ambient temperatures and weather conditions; under extreme pressure; and on chassis and heavy duty equipment, including construction and mining applications

**Grease Type:** Moly-Lithium

**NLGI Grade:** 1

**Color:** Black

**Thickener:** Lithium

**Odor/Scent:** Mineral Oil

**Physical Form:** Paste or Gel

**Resistance:** Corrosive Contaminants; Corrosive Process; Rust; Water



| SKU           | Capacity Wt. |
|---------------|--------------|
| 293-L0107-098 | 14 1/2 oz    |

## Spray Lube "A"

### Features:

- A multi-purpose, white lithium-based lubricant of medium density
- Sprays like a fluid, congeals to a grease

| SKU           | Capacity Wt. |
|---------------|--------------|
| 293-L0034-063 | 11 oz        |



# Mystik

## JT-6® Multi-Purpose Grease

### Features:

- Waterproof and highly water wash resistant
- Excellent extreme pressure properties
- Prevents against shock loading
- Outstanding rust and corrosion prevention
- Very low oil separation rate
- Light colored and low staining
- Good oxidation resistance

**NLGI Grade:** 2



| SKU              | Capacity Wt. |
|------------------|--------------|
| 122-665006002080 | 14 oz        |

## JT-6® Multi-Purpose Hi-Temp Grease

### Features:

- Provides superior rust, oxidation and corrosion resistance
- Designed to meet the high temperature conditions of modern universal joints, the extreme pressures of wheel bearings and the water washout conditions of fifth wheels and chassis points

**NLGI Grade:** 2



| SKU              | Capacity Wt. | Packing Type |
|------------------|--------------|--------------|
| 122-665005002080 | 14 oz        | Cartridge    |
| 122-665005002044 | 35 lb        | Pail         |

## JT-6® Multi-Purpose Hi-Temp Grease w/Moly

### Features:

- High performance mining and construction grease that provides superior performance where a moly - compounded, adhesive, multi-purpose high temperature lithium complex grease is required
- This product gives optimum protection in severe environments

**NLGI Grade:** 2



| SKU              |
|------------------|
| 122-665056002080 |

## NEVER•SEEZ®

### High Temperature Bearing Lubricants

**Features:**

- Never-Seez® High Temperature Bearing Lubricant is an exclusive combination of a specially formulated high temperature grease and lubricating enhancers that provides long lasting lubrication
- Has no "dropping point"—will not melt
- Good extreme pressure characteristics
- Contains no metallic particles

**NLGI Grade:** 1/2

**Color:** Black

**Resistance:** Water



| SKU         | Cartridge Size |
|-------------|----------------|
| 535-NHTC-14 | 14 oz          |



### LubriMatic Multi-Purpose Lithium Greases

**Features:**

- Long lasting, hard working formula delivers high performance in a wide range of heavy-duty applications
- Works best for lubricating rolling parts

**Applicable Materials:** Chassis; Universal Joints



| SKU       | Capacity Wt. | Quantity    |
|-----------|--------------|-------------|
| 570-11315 | 14 oz        | 10 per pack |



### Super Lube® Grease Lubricants

**Features:**

- Will not run, drip, evaporate, melt, separate, or form gummy deposits

**NLGI Grade:** 2

**Odor/Scent:** Mild

**Physical Form:** Paste or Gel

**Applicable Materials:** Fabric; Leather;

Plastic; Rubber; Wood

**Resistance:** Corrosive Process; Dirt; Dust; Saltwater; Water; Wear



| SKU       | Capacity Wt. | Packing Type |
|-----------|--------------|--------------|
| 692-21030 | 3 oz         | Tube         |
| 692-41150 | 400 g        | Cartridge    |
| 692-41160 | 400 g        | Jar          |
| 692-41030 | 30 lb        | Pail         |



### Hydraulic Fittings



**Features:**

- Features dirt excluding ball check

**Body Material:** Metal

**Connection Type:** Male/Male

**Shape:** Straight

**Operating Pressure:** 10,000 psi

| SKU         | Male Thread  | Wrench Size | Length   |
|-------------|--------------|-------------|----------|
| 025-1610-BL | 1/8 in (PTF) | 7/16 in     | 11/16 in |
| 025-1627-B  | 1/4 in (PTF) | 9/16 in     | 7/8 in   |

## MASTERKIT

### Masterkit Grease Fitting Assortments

**Features:**

- Standard American fractional sizes
- Premium quality imported fittings only
- Assembled in U.S.A

**Includes:** (15) 1/4 28 S.A.E. 45° Angle; (15) 1/4 28 S.A.E. 90° Angle; (15) 1/8 27 P.T. 67° Angle; (25) 1/8 27 P.T. Straight; (30) 1/4 28 S.A.E. Straight; Lid Guide; Specification Label

**Finish:** Zinc Plated



| SKU       | Quantity    |
|-----------|-------------|
| 475-100-5 | 100 per set |



### Alemite® Cordless Grease Guns



**Features:**

- 3-way loading
- High capacity NiCad battery
- Optimized air flow to maximize motor cooling
- (Grease not included)

**Cartridges Per Charge:** 17

**Includes:** (2) Batteries; Carrying Case; One-hour Fast Charger

| SKU        | Cartridge Size | Extension Length | Operating Pressure | Flow       |
|------------|----------------|------------------|--------------------|------------|
| 025-585-B1 | 14 oz          | 36 in            | 10,000 psi         | 5.6 oz/min |



## Extreme Pressure Grease Guns

### Features:

- For giant button head couplings
- Vol. @ No. of Strokes:** 1 oz @ 24
- Outlet Type:** Hose/Coupler
- Drive Type:** Lever Action
- Designated Fluid:** Grease
- Includes:** Adapter 327033; Button Head Coupler 319702; Carrying Strap; Gauge 317150; High Pressure "T" 309727; Hose Assembly 317875-1F; Model 6268-2 Gun; Relief Valve 319700; Swivel 52750; Swivel 52752



| SKU          | Capacity Vol. | Operating Pressure | Outlet Size   |
|--------------|---------------|--------------------|---------------|
| 025-325540-1 | 12 oz         | 15,000 psi         | 1/4 in (NPTF) |

## Heavy Duty Grease Guns

### Features:

- Features automatic variable stroke/pressure, air vent, vinyl grip, loader fitting
- Capacity Vol.:** 16 oz
- Cartridge Size:** 14 oz
- Operating Pressure:** 10,000 psi
- Vol. @ No. of Strokes:** 1 oz @ 21
- Designated Fluid:** Grease



| SKU       | Extension Type | Outlet Type             |
|-----------|----------------|-------------------------|
| 025-500   | Rigid Pipe     | Rigid Extension/Coupler |
| 025-500-E | Flexible Hose  | Hose/Coupler            |

### Features:

- Quick priming
- HD spring
- Dual leverage volume or pressure
- Air bleed valve
- Capacity Vol.:** 16 oz
- Cartridge Size:** 14 oz
- Operating Pressure:** 7,500 psi
- Vol. @ No. of Strokes:** 1 oz @ 30



| SKU       | Extension Type | Outlet Type             |
|-----------|----------------|-------------------------|
| 025-555   | Rigid Pipe     | Rigid Extension/Coupler |
| 025-555-E | Flexible Hose  | Hose/Coupler            |

## GOLDENROD®

## GOLDENROD® Heavy Duty Pistol Guns

### Features:

- Designed for an operating pressure of up to 6,000 PSI
- One-hand operation
- Pistol action gun has 3 way loading (cartridge, bulk or loader nipple)

**Extension Type:** Flexible Hose

**Outlet Type:** Hose/Coupler

**Body Material:** Steel

**Drive Type:** Lever Action

**Designated Fluid:** Grease



| SKU     | Capacity Vol. | Cartridge Size | Extension Length | Operating Pressure |
|---------|---------------|----------------|------------------|--------------------|
| 250-160 | 20 oz         | 14 oz          | 12 in            | 6,000 psi          |



## Air Powered Grease Guns

### Features:

- Full automatic operation—cycles continuously when trigger is pulled, self-priming
- Low operational noise
- Flip-over follower eliminates grease bypass
- Heavy-duty spring for prime retention
- Locking follower rod for easy loading
- 40:1 air motor



| SKU      | Operating Pressure | Pressure [Max] | Outlet Size   |
|----------|--------------------|----------------|---------------|
| 438-1162 | 40 psi - 150 psi   | 6,000 psi      | 7/16 in(UNEF) |

## Heavy Duty High Pressure Grease Guns

### Features:

- Precision-machined, all steel handle, body, and guard bracket provides durability and longevity
- Unique, precision control inlet check valve provides ease of handle operation even with increase in pressure
- Knurled handle for positive grip
- Handy trigger guard prevents pinching
- Reversible inlet check seat and hydraulic jaws provide double life
- Balanced design reduces user fatigue

**Extension Type:** Rigid Tube

**Inlet Size:** 1/4 in NPT(F)

**Body Material:** Steel

**Power Source:** Compressed Air



| SKU     | Operating Pressure | Outlet Size   |
|---------|--------------------|---------------|
| 438-740 | 7,500 psi          | 1/8 in NPT(F) |



## Lever Type Heavy-Duty Grease Guns



Extension Type: 5852 Coupler  
Handle Type: Lever

**Features:**

- Comes with handle grip and vent valve for purging air from gun
- It's designed for rough treatment on the job with a cast iron pump head, precision fit plunger and extra heavy follower spring
- Variable stroke/variable pressure: short stroke-high pressure: long-stroke high volume
- Follower is set for cartridge use

Extension Type: 62028, 6 in. Extension Tube

| SKU      | Lube Cap.                    |
|----------|------------------------------|
| 438-1148 | 16oz. Bulk/14.5oz. Cartridge |

**Features:**

- Exclusive "Flip-Over" follower allows a superior seal for either cartridge or bulk loading applications
- Extra-heavy follower spring insures positive priming and uninterrupted pumping action
- Precision fit and hardened plunger eliminates lubricant bypass
- Accessible check valve allows easy cleaning without gun disassembly
- Lever action with a proven cast head design

Extension Type: 62028, 6 in. Extension Tube

| SKU      | Lube Cap.                    |
|----------|------------------------------|
| 438-1142 | 16oz. Bulk/14.5oz. Cartridge |

**Features:**

- Flip-over follower is set for cartridge use
- Extra-heavy follower spring insures positive priming and uninterrupted pumping action
- Precision fit and hardened plunger eliminates lubricant bypass
- Accessible check valve allows easy cleaning without gun disassembly
- Lever action with a proven cast head design

Extension Type: 71518, 18 in. Flex Hose

| SKU      | Lube Cap.                    |
|----------|------------------------------|
| 438-1147 | 16oz. Bulk/14.5oz. Cartridge |

## Pistol Grip Heavy-Duty Grease Guns



Lube Cap.: 16oz. Bulk/14.5oz. Cartridge  
Handle Type: Pistol Grip

| SKU      | Extension Type                                  |
|----------|---|
| 438-1132 | 5852 Coupler; 67020, 6 in. Straight Pipe        |
| 438-1133 | 5852 Coupler; 71518, 18 in. Flex Hose           |
| 438-1134 | 18 in. Flex Hose; 4 in. Straight Pipe & Coupler |

## PowerLuber® Grease Guns



| SKU      | Voltage | Includes                                    |
|----------|---------|---|
| 438-1242 | 12 V    | Battery; Charger                            |
| 438-1244 | 12 V    | (2) Batteries; Carrying Case; Charger       |
| 438-1442 | 14.4 V  | Battery; Carrying Case; Charger             |
| 438-1444 | 14.4 V  | (2) Batteries; Carrying Case; Charger       |
| 438-1844 | 18 V    | (2) Batteries; Carrying Case; Smart Charger |
| 438-1200 | 12 V    | Battery                                     |



## Cordless Grease Guns



**Features:**

- Compact and lightweight
- 3-way loading
- Fuel gauge
- Soft grip handle
- Hose storage
- Shoulder strap hook

Operating Pressure: 8,150 psi

Extension Length: 36 in

Cartridges Per Charge: up to 7

Battery Type: Lithium-Ion

Includes: 30-Min Charger; Carrying Case; XC Battery

| SKU           | Voltage | Cartridge Size | Flow @ Pressure        |
|---------------|---------|----------------|------------------------|
| 495-2446-21XC | 12 V    | 14 oz          | 2.6 oz/min @ 1,000 psi |



## HD Pistol Grease Guns



**Features:**

- 3-way loading: 14 oz cartridge, bulk or suction
- Variable stroke for use in tight places
- Vinyl Handle Grip

Extension Type: 18 in Flex Hose

Vol. @ No. of Strokes: 1 oz @ 40

Includes: 18 in Flex Hose; Air Bleeder Valve; Bulk Loader Fitting

| SKU        | Cartridge Size | Extension Length | Operating Pressure |
|------------|----------------|------------------|--------------------|
| 570-30-416 | 14 oz          | 18 in            | 7,000 psi          |





### Lever Action Grease Guns



Cartridge Size: 14 oz  
 Extension Length: 6 in  
 Extension Type: Rigid Pipe

- Features:**
- Heavy-duty grease gun for automotive professionals
  - Variable/short stroke for easy use in confined areas
  - Air bleeder and bulk loader fitting for 3-way loading
  - Plated lever with comfortable oversized grip

Operating Pressure: 10,000 psi  
 Outlet Type: Deluxe Coupler

| SKU        | Vol. @ No. of Strokes |
|------------|-----------------------|
| 570-30-465 | 1.8 oz @ 40           |

- Features:**
- Variable/short stroke for easy use in confined areas
  - Rugged fully zinc plated finish
  - Dual port head cap with bulk loader for 3-way loading

Operating Pressure: 10,000 psi  
 Outlet Type: Coupler

| SKU        | Vol. @ No. of Strokes |
|------------|-----------------------|
| 570-30-475 | 1.8 oz @ 40           |

- Features:**
- Variable/short stroke for easy use in confined areas
  - Rugged fully zinc plated finish
  - 2-way loading cartridge or suction

Operating Pressure: 6,000 psi  
 Outlet Type: Ball Check Coupler

| SKU        | Vol. @ No. of Strokes |
|------------|-----------------------|
| 570-30-200 | 1 oz @ 40             |

### Pistol Grease Guns



- Features:**
- Convenient one-hand operation
  - Durable baked enamel finish
  - 2-way loading: cartridge or suction
  - Head cap port for adding air bleeder or bulk loader fitting

Extension Type: Steel Pipe  
 Vol. @ No. of Strokes: 1 oz @ 40  
 Outlet Type: Coupler

| SKU        | Cartridge Size | Extension Length | Operating Pressure |
|------------|----------------|------------------|--------------------|
| 570-30-300 | 14 oz          | 3 1/2 in         | 7,000 psi          |



### Alemite® Hydraulic Couplers



- Features:**
- For hydraulic fittings
- Body Material: Metal  
 Connection Type: Female/Female  
 Coupler Type: Straight  
 Female Thread: 1/8 in (NPTF)  
 Seal Material: Metal  
 Shape: Straight

| SKU        | Operating Pressure |
|------------|--------------------|
| 025-308730 | 10,000 psi         |

### Button Head Couplers



- Features:**
- For use with standard or giant button head fittings
- Connection Type: Female/Female  
 Female Thread: 1/8 in (NPTF)

| SKU          | Wt.     |
|--------------|---------|
| 025-304300-A | 0.45 lb |
| 025-42030-A  | 0.29 lb |

### Grease Gun Extension Hoses



- Features:**
- Economical and durable hose
  - 12,000 psi burst pressure
  - For use with hand operated grease guns only
- Hose Type: Elastomeric  
 Male Thread: 1/8 in (NPTF)

| SKU           | Hose Length | Operating Pressure |
|---------------|-------------|--------------------|
| 025-317850-1F | 18 in       | 4,800 psi          |



### Extensions for Manually or Air-Operated Grease Guns



- Features:**
- Strategically placed coiled spring provides non-slip, push-pull grip and prevents accidental “kinking” which could cause hose ruptures
- Coupler Type: 5845  
 Hose Type: Flexible

| SKU      | Hose Length | Thread Size   | Working Pressure [Max] |
|----------|-------------|---------------|------------------------|
| 438-5818 | 18 in       | 1/8 in NPT(M) | 4,500 psi              |



## High Pressure Swivels

**Features:**

- Operating pressure, is rated for whip hoses only

**Operating Pressure:** 4,500 psi

**Body Material:** Steel

**Shape:** Universal

**Thread - TPI or Pitch:** 1/4 in NPT(m) x 1/4 in NPT(m)



| SKU       |
|-----------|
| 438-83594 |

## Hydraulic Couplers

**Features:**

- For all hydraulic type grease fittings
- Small outside diameter permits easy contact with recessed fittings
- Built-in ball-check prevents leak and lubricant backup

**Inlet Size:** 1/8 in (NPT)



| SKU      | Operating Pressure |
|----------|--------------------|
| 438-5852 | 7,500 psi          |



## Grease Hoses

**Fitting Size:** 1/8 in NPT(M)

**Fitting Type:** Steel on Each End

**Packing Type:** Bulk

**Used With:** Hand Grease Guns

**Features:**

- Can be used with either hand operated or power lube equipment
- Deluxe model comes with threaded center post for positive locking of wheel bearing
- Easily lubricates most bearings
- For all car, boat, trailer and RV bearings having a minimum ID of 1/2 in to a maximum of 5 in



| SKU        | Length | Operating Pressure |
|------------|--------|--------------------|
| 570-10-218 | 18 in  | 3,000 psi          |



## 14.4 V PowerLuber® Batteries

**Features:**

- Contact type provides for very efficient electrical transfer
- Internally insulated
- Long life - High capacity battery
- Padded housing prevents damaged if dropped
- Wide clip design secures battery while allowing for easy swap out



| SKU      | Batt. Cap. | Voltage |
|----------|------------|---------|
| 438-1401 | 1,700 mA-h | 14.4 V  |

## PowerLuber® Accessories

**Features:**

- Dispenses a minimum of three grease cartridges under normal conditions

| SKU      | Batt. Cap. | Voltage |
|----------|------------|---------|
| 438-1201 | 1,300 mA-h | 12 V    |



## Air Tool Lubricants

**Features:**

- Rust proofs and prolongs the life of your tool
- Resistance:** Corrosive Process; Moisture; Wear



| SKU        | Capacity Wt. | Quantity    |
|------------|--------------|-------------|
| 166-ATL016 | 16 oz        | 12 per case |



## 2-26® Multi-Purpose Precision Lubricants

### Features:

- Cleans, lubricates, penetrates and loosens corrosion
- Prevents corrosion by displacing moisture
- Restores resistance values and helps stop current leakage
- Helps restore water damaged electrical equipment
- Convenient 360° spray valve - can be sprayed from any position
- Cleans light soils and contaminants
- Will not harm modern plastics, including polycarbonates, ABS and Noryl®

**Applicable Materials:** Aluminum; Brass; Copper; Most Metals; Plastic; Steel

**Color:** Clear

**Odor/Scent:** Pleasant

**Resistance:** Corrosive Process; Humidity; Moisture; Water



| SKU       | Container Size |
|-----------|----------------|
| 125-02005 | 16 oz          |

## CRC Air Tool Oils

### Features:

- Lubricates and protects pneumatic equipment
- Increases torque; assures long tool life
- Reduces rust, varnish, sludge, and acids

**VOC:** 27.0 g/L; 3.0 %

**Color:** Dark Amber

**Odor/Scent:** Mild



| SKU        | Container Size |
|------------|----------------|
| 125-SL2531 | 15 oz          |
| 125-SL2533 | 1 gal          |

## CRC Food Grade Machine Oil

### Features:

- Contains no silicone and is virtually odorless and colorless
- Will not harm metal, wood, plastic or painted surfaces
- Convenient 360° spray valve - can be sprayed from any position

**VOC:** 0 %; 0 g/L

**Chemical Compound:** Petroleum Based

**Applicable Materials:** Most Metals; Plastic; Wood

**Color:** Clear

**Odor/Scent:** Mild



| SKU       | Container Size |
|-----------|----------------|
| 125-03081 | 16 oz          |

## Cutting Oils

### Features:

- Reduces heat and friction to ease cutting and increase cutting tool life
- Sulfur-free, low odor formula
- Foaming aerosol formulation clings to vertical surfaces
- Compatible with all manual and motor-driven threading equipment

• Superior thread cutting lubricant for use on all types of both ferrous and non-ferrous metals, including brass, copper and aluminum

**Applicable Materials:** Aluminum; Brass; Copper; Most Metals

**Odor/Scent:** Mild Petroleum



| SKU       | Container Size |
|-----------|----------------|
| 125-14050 | 16 oz          |

## GASOILA

CHEMICALS

Specialty Products for Today's Professional

## Free All® Deep Penetrating Oils

### Features:

- Penetrates rust, scale and corrosion to free parts and assemblies INSTANTLY
- Loosens red and white lead, tar, grease, carbon and graphite deposits
- Contains NO silicones, making it safe in paint and shop environments



| SKU      | Capacity Wt. |
|----------|--------------|
| 296-RE12 | 12 oz        |

TW Professional Brands

## Cling® Water Soluble Cutting Oil Lubricants

### Features:

- Dilution ratio 20:1
- VOC:** 0.6 lb/gal
- Color:** Clear Gold Brown
- Odor/Scent:** Pleasant



| SKU       | Capacity Vol. |
|-----------|---------------|
| 253-26090 | 1 gal         |



## LPS® Food Grade Machine Oil

### Features:

- Penetrates to loosen frozen nuts and bolts
- Does not contain silicone
- Colorless, odorless
- Inverta spray valve

Fill Amount: 11 oz



| SKU       | Container Size |
|-----------|----------------|
| 428-01316 | 16 oz          |



## Food Machinery Oils/ Class H-1

### Features:

- SAE Gear Oil No. 80
- ISO viscosity grade 68
- AGMA No. 2

SAE No.: 20

Chemical Compound: Petroleum Based

Color: Clear

Odor/Scent: Mineral Oil

Resistance: Wear



| SKU           | Capacity Vol. |
|---------------|---------------|
| 293-L0882-063 | 12 oz         |

## Lubriplate® Air Tool Lubricants

### Features:

- Designed for both rotary and reciprocating types of air tools
- Removes gumming and sludge



| SKU           | Capacity Vol. |
|---------------|---------------|
| 293-L0713-054 | 1 qt          |

## No. 35 Soluble Oils

### Features:

- Multi-purpose, water soluble cutting oil
- Forms a milky white emulsion that does not readily decompose or separate
- It will not gum or cause rust
- It is noted for its non-foaming features, making it suitable for grinding and cutting operations



| SKU           | Capacity Vol. |
|---------------|---------------|
| 293-L0576-060 | 5 gal         |



## Marvel Mystery Oil® Air Tool Oils

### Features:

- Specially formulated for use in all piston type and rotary air tools, as well as in-line air lubricators
- Prevents rust formation while providing positive lubrication for smooth starting and longer tool life
- Assures maximum performance by dissolving gum and sludge that cut down tool speed and reduce power output



| SKU         | Features     | Capacity Vol. |
|-------------|--------------|---------------|
| 465-080     | • With spout | 4 oz          |
| 465-MM085R1 |              | 1 qt          |

## Marvel Mystery Oils

### Features:

- When added to gasoline: Cleans and lubricates fuel injectors and carburetors
- Improves gas mileage
- Reduces and prevents varnish and gum build-up
- Extends spark plug life
- Safe for catalytic converters and oxygen sensors
- When added to engine oil: Prevents valve sticking and clatter
- Fortifies properties of engine oil, prevents breakdown caused by extreme temperatures
- Promotes easier cold weather starts
- Reduces and prevents sludge and acid formation
- For all marine engines- inboard and outboard



| SKU       | Capacity Vol. |
|-----------|---------------|
| 465-012R  | 1 pt          |
| 465-013R  | 1 qt          |
| 465-MM14R | 1 gal         |

## RECTORSEAL

## Dark Cutting Oils

### Features:

- Reduces friction and acts as an effective coolant and anti-weld agent during hand thread cutting operations and when using low rpm machines



| SKU       | Capacity Vol. |
|-----------|---------------|
| 622-94272 | 1 gal         |



## Shamrock Penetrating Oils

### Features:

- Cuts rust and carbon on nuts, bolts, screws, fittings, valves and other car parts
- Leaves protective film with significant thickness



| SKU           | Capacity Vol. |
|---------------|---------------|
| 662-S-OK-AERO | 10 oz         |



## Cutting Oil Lubricants

### Features:

- Extends tool life
- Recommended for all metals
- Clings to surface
- Jet-spray allows precision applications

**Dielectric Strength:** 10,000 V/mil

**Applicable Materials:** Aluminum; Brass; Copper; Most Metals; Stainless Steel

**Resistance:** Wear



| SKU        | Capacity Vol. |
|------------|---------------|
| 425-S00208 | 12 oz         |



## WD-40® Open Stock Lubricants

### Features:

- Protects metal from rust and corrosion, penetrates stuck parts, displaces moisture, and lubricates

**Chemical Compound:** Petroleum Based

**Applicable Materials:** Fabric; Plastic; Rubber; Steel



| SKU        | Capacity Vol. | Packing Type |
|------------|---------------|--------------|
| 780-110108 | 3 oz          | Aerosol Can  |
| 780-10116  | 16 oz         | Aerosol Can  |
| 780-10124  | 18 oz         | Aerosol Can  |
| 780-10110  | 1 gal         | Canister     |
| 780-10117  | 5 gal         | Canister     |
| 780-10118  | 55 gal        | Drum         |

## WD-40® Smart Straw Lubricants

### Features:

- The WD-40 can with a built in straw
- Never lose the straw again, it's permanently attached
- Smart new design allows for one handed operation: Simply flip it up for a precision stream, and down for regular spray action
- Smart Straw is a more convenient way to protect, clean, and lubricate thousands of items



| SKU        | Capacity Wt. |
|------------|--------------|
| 780-110054 | 8 oz         |
| 780-110078 | 11 oz        |
| 780-10152  | 12 oz        |

## WD-40® Trigger Pro

### Features:

- Multi-purpose lubricant, remover, protector, moisture displacer and more
- Off position on the nozzle
- Recyclable steel packaging
- Two settings – spray or stream



| SKU        | Capacity Wt. | Quantity    |
|------------|--------------|-------------|
| 780-110184 | 20 oz        | 12 per case |

## GOLDENROD®

## GOLDENROD® Heavy Duty Pump Oilers

### Features:

- Built of heavy gauge steel that will stand up to rough use
- Delivers either a drop or stream of fluid
- Easy-to-use filler cap eliminates handling of messy pumps
- Replaceable brass spout tip
- Wrought iron spout
- Copper bronze finish

**Body Material:** Steel

**Drive Type:** Lever Action



| SKU        | Capacity Volume [Max] | Spout Length | Spout Type   |
|------------|-----------------------|--------------|--------------|
| 250-120-C  | 1 pt                  | 10 in        | Not Included |
| 250-120-C3 | 1 pt                  | 10 in        | Flexible     |
| 250-120-A  | 1 qt                  | 15 in        | Not Included |
| 250-120-A3 | 1 qt                  | 15 in        | Flexible     |

## GOLDENROD®

### GOLDENROD® Industrial Pump Oilers

**Features:**

- 5" flexible spout
- Double seamed or drawn steel bases
- Removable spout
- Powder-coated copper bronze finish

**Spout Type:** Flexible

**Body Material:** Steel

**Drive Type:** Lever Action



| SKU     | Capacity Volume [Max] | Spout Length |
|---------|-----------------------|--------------|
| 250-727 | 16 oz                 | 8 in         |



### Sure Shot® Sprayers

**Features:**

- Steel sprayers can be used with oil and solvent based materials, and brass sprayers can be used with water based materials
- They use readily available compressed air, instead of flammable or dangerous propellants, and because they are reusable you don't have to worry about disposal of empty cans

**Capacity Vol.:** 1 qt

**Body Material:** Steel

**Finish:** Powder Coated

**Color:** Red

**Nozzle Type:** Mist; Pin Stream



| SKU       |
|-----------|
| 494-1000R |



### WD-40® Spray Applicators

**Features:**

- 16 oz spray bottle is designed for bulk use of WD-40
- Interior is treated to withstand the penetrating power of WD-40
- Nozzle adjust to stream or spray

**Packing Type:** Case



| SKU       |
|-----------|
| 780-10100 |



### Scotchrap™ Pipe Primers

**Features:**

- Quick-dry, non-sag rubber based primer that permeates metal surface pits and irregularities, preparing the surface for tape application
- Compatible with the special adhesives on Scotchrap Tapes, it enhances adhesion

**Chemical Compound:** Rubber

**Applicable Materials:** Most Metals



| SKU       | Color | Capacity Vol. | Quantity   |
|-----------|-------|---------------|------------|
| 500-42768 | Black | 1 gal         | 4 per case |



### Construction Marking Paints

**Features:**

- Mark is visible for up to 3 months
- Designed to be used in Aervoe's #244 Spot Marker, #245 Marking Stick, or by hand
- Lead free, non-clogging can
- Adheres to almost any surface; not recommended for use on turf surfaces

**Color:** Fluorescent Orange



| SKU     | Capacity Wt. |
|---------|--------------|
| 205-247 | 20 oz        |



### INDUSTRIAL High Heat Paints

**Features:**

- Provides a clean, durable finish
- Protects against rust
- Dries to the touch in minutes

**Color:** Stove Paint Black

**Resistance:** Corrosive Process; Heat; Moisture; Wear; Weather



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-K01618 | 12 oz        |

Industrial Safety Welding Oilfield Construction



## INDUSTRIAL

### Interior/Exterior Industrial Maintenance Paints

#### Features:

- VOC-compliant acrylic lacquer formula, free of lead hazards
- Hard, protective, durable finish
- High amount of solids assures maximum coverage with excellent adhesion
- Dries fast, in just 12 minutes to the touch
- Tough, high-gloss finish
- Uniform coverage
- No recoat window, recoat anytime

**Capacity Wt.:** 12 oz

**Chemical Compound:** Acrylic

**Applicable Materials:** Metal Surfaces; Wood

**Resistance:** Wear; Weather

**Quantity:** 6 per case



| SKU           | Color            |
|---------------|------------------|
| 425-K01501A00 | Glossy White     |
| 425-K01601A00 | Glossy Black     |
| 425-K01602A00 | Ultra-Flat Black |
| 425-K01604A00 | Shadow Gray      |
| 425-K01613A00 | Semi-Flat Black  |
| 425-K01901A00 | Regal Blue       |
| 425-K01910A00 | True Blue        |
| 425-K02001    | Hunter Green     |
| 425-K02101A00 | Cherry Red       |

### Line-Up® Pavement Striping Paints

#### Features:

- Fast drying
- Long-lasting durability on outdoor pavement and indoor surfaces
- Non-clogging spray tip
- VOC compliant, free-of-lead hazards

**Color:** Highway Yellow

**Base Type:** Solvent

**Applicable Materials:** Pavement

**Resistance:** Wear; Weather



| SKU        | Capacity Wt. | Quantity    |
|------------|--------------|-------------|
| 425-K08301 | 18 oz        | 12 per pack |

### Metallic Paints

#### Features:

- High performance
- Fast-Drying

**Capacity Wt.:** 11 oz

**Applicable Materials:** Most Metals; Styrofoam; Wood

**Resistance:** Wear; Weather



| SKU        | Color           |
|------------|-----------------|
| 425-K01401 | Bright Silver   |
| 425-K01404 | Chrome Aluminum |

### OSHA Paints

#### Features:

- Color standards approved by the Occupational Safety and Health Act Governing Board
- High visibility cautions for helping workers' safety

**Capacity Wt.:** 12 oz

**Resistance:** Wear; Weather

| SKU        | Color         |
|------------|---------------|
| 425-K01813 | Safety Yellow |
| 425-K01929 | Safety Purple |
| 425-K02116 | Safety Red    |
| 425-K02410 | Safety Orange |



### Primers

#### Features:

- Coat any metal, wood, both indoor and outdoors for a hard, protective, durable finish
- Dry to touch in under 12 minutes
- No recoat window, recoat anytime

**Capacity Wt.:** 12 oz

| SKU           | Color       |
|---------------|-------------|
| 425-K01315A00 | White       |
| 425-K01317A00 | Ruddy Brown |
| 425-K01318A00 | Gray        |



### Quik-Mark™ APWA Solvent-Based Inverted Marking Paints

#### Features:

- Fast-drying
- Penetrates and adheres to hot surfaces
- Convenient Spray-Thru™ cap, non-clogging spray tip
- VOC compliant, free-of-lead hazards

**Capacity Vol.:** 17 oz

**Applicable Materials:** Asphalt; Brick;

Concrete; Grass

**Resistance:** Weather



| SKU           | Color                  |
|---------------|------------------------|
| 425-S03611    | Red                    |
| 425-S03621    | Blue                   |
| 425-S03821    | High Visibility Yellow |
| 425-A03900000 | Utility White          |

### Quik-Mark™ APWA Water-Based Inverted Marking Paints

#### Features:

- Fast-drying
- Penetrates and adheres to hot surfaces
- Convenient Spray-Thru™ cap, non-clogging spray tip
- VOC compliant, free-of-lead hazards
- One-coat coverage

**Capacity Vol.:** 17 oz

**Chemical Compound:** Water

**Applicable Materials:** Asphalt; Brick;

Concrete; Grass

**Resistance:** Wear; Weather



| SKU        | Color           |
|------------|-----------------|
| 425-S03801 | Utility Yellow  |
| 425-S03901 | Brilliant White |



## INDUSTRIAL

### Quik-Mark™ Solvent-Based Fluorescent Inverted Marking Paints

**Features:**

- High solids formulation for bold, bright, visible markings
- Fast-drying
- Penetrates and adheres to hot surfaces
- Convenient Spray-Thru™ cap, non-clogging spray tip
- VOC compliant, free-of-lead hazards
- One-coat coverage

**Capacity Vol.:** 17 oz

**Applicable Materials:** Asphalt; Brick; Concrete; Grass

**Resistance:** Weather



| SKU        | Color                  |
|------------|------------------------|
| 425-AT3701 | Fluorescent Red/Orange |
| 425-S03622 | Fluorescent Hot Pink   |
| 425-S03702 | Fluorescent Orange     |

### Quik-Mark™ Water-Based Fluorescent Inverted Marking Paints

**Features:**

- High solids formulation for bold, bright, visible markings
- Fast-drying
- Penetrates and adheres to hot surfaces
- Convenient Spray-Thru™ cap, non-clogging spray tip
- VOC compliant, free-of-lead hazards
- One-coat coverage

**Chemical Compound:** Water

**Applicable Materials:** Asphalt; Brick; Concrete; Grass

**Resistance:** Weather



| SKU        | Color                  | Capacity Vol. |
|------------|------------------------|---------------|
| 425-S03408 | Fluorescent Orange     | 12 oz         |
| 425-S03612 | Fluorescent Pink       | 17 oz         |
| 425-S03630 | Fluorescent Neon Green | 17 oz         |
| 425-S03700 | Fluorescent Orange     | 17 oz         |

### Rust Tough® Aerosol Enamels

**Features:**

- Complete coverage with one coat
- Dries to touch in 25 minutes, dries to handle in 1 hour
- Superior appearance and color retention
- Ideal for small touch-up jobs, painting irregular shapes or covering hard-to-reach areas
- For both indoor and outdoor use
- Tough, high gloss finish
- Equipped with EZ TOUCH® FANSPRAY® Nozzle

**Capacity Wt.:** 15 oz

**Chemical Compound:** Acrylic

**Applicable Materials:** Aluminum; Most Metals; Steel; Wood

**Resistance:** Corrosive Process; Gasoline; Oil; Weather



| SKU        | Color                | Finish |
|------------|----------------------|--------|
| 425-R00439 | Safety Yellow (OSHA) | Gloss  |
| 425-R00639 | Safety Red (OSHA)    | Gloss  |
| 425-R00789 | Flat Black           | Matte  |
| 425-R00799 | Gloss Black          | Gloss  |
| 425-R00929 | Gloss White          | Gloss  |

### Rust Tough® Aerosol Primers

**Features:**

- Complete coverage with one coat
- Dries to touch in 25 minutes, dries to handle in 1 hour
- For both indoor and outdoor use
- Tough, high gloss finish
- Equipped with EZ TOUCH® FANSPRAY® Nozzle

**Capacity Wt.:** 15 oz

**Applicable Materials:** Aluminum; Most Metals; Steel; Wood

**Resistance:** Corrosive Process; Weather



| SKU        | Color     |
|------------|-----------|
| 425-R00699 | Red Oxide |
| 425-R00829 | Gray      |

### Tough Coat® Acrylic Alkyd Enamels

**Features:**

- Indoors and outdoors
- Protective coating resists chipping and peeling
- EZ TOUCH fan spray nozzle eliminating 50% of finger fatigue
- Coats metals, motors, machinery, marks off walkways, identifies pipelines

**Capacity Wt.:** 12 oz

**Chemical Compound:** Acrylic

**Applicable Materials:** Most Metals

**Resistance:** Corrosive Process; Gasoline; Oil; Wear; Weather



| SKU        | Color          |
|------------|----------------|
| 425-S01110 | OSHA Red       |
| 425-S01210 | OSHA Orange    |
| 425-S01310 | OSHA Yellow    |
| 425-S01510 | OSHA Blue      |
| 425-S01770 | OSHA Black     |
| 425-S01800 | OSHA White     |
| 425-S03727 | Max-Flat Black |





## INDUSTRIAL Tough Coat® Primers

### Features:

- Specially formulated for a variety of industrial applications
- Indoors and outdoors
- Protective coating resists chipping and peeling
- Fast-drying
- A high solids formula ensures maximum coverage and a premium finish
- EZ TOUCH fan spray nozzle eliminating 50% of finger fatigue
- Coats metals, motors, machinery, marks off walkways, identifies pipelines

**Capacity Wt.:** 12 oz

**Applicable Materials:** Most Metals

**Resistance:** Corrosive Process

| SKU        | Color      |
|------------|------------|
| 425-S00340 | Gray       |
| 425-S00341 | Light Gray |
| 425-S00342 | Red Oxide  |



## Weekend® Economy Paints

### Features:

- Economical, all purpose enamel paint
- Recommended for touch-up, maintenance and general marking applications
- Equipped with standard valve
- Dries tack-free in 20 minutes

**Capacity Wt.:** 11 oz

**Resistance:** Weather

| SKU      | Color           | Finish   |
|----------|-----------------|----------|
| 425-K345 | Chrome Aluminum | Metallic |
| 425-K356 | W.I. Flat Black | Matte    |
| 425-K358 | Gloss Black     | Gloss    |
| 425-K362 | Cherry Red      | Matte    |



## 7471™ Primer T™

### Features:

- A solvent-based primer that speeds the cure of all Loctite® brand anaerobic adhesives and ensures proper cure on inactive metals
- Has on-part life of 7 days and dries in 30 - 70 seconds

**Color:** Amber

**Chemical Compound:** Isopropanol

| SKU       | Capacity Vol. | Viscosity |
|-----------|---------------|-----------|
| 442-22477 | 4 1/2 oz      | 20 cP     |



## 7649™ Primer N™

### Features:

- A solvent-based primer that features very long on-part life of 30 days
- Use to speed the cure of all Loctite® brand anaerobic products and ensure proper cure on inactive metals
- Ideal for cure conditions below room temperature
- Dries in 30 - 70 seconds

**Color:** Clear Green

**Viscosity:** 20 cP

**Chemical Compound:** Copper Salt

**Odor/Scent:** Mild Acrylic

| SKU       | Packing Type |
|-----------|--------------|
| 442-19269 | Bottle       |
| 442-21348 | Aerosol Can  |



## Magnaglo® WCP-2 White Contrast Paints

### Features:

- White contrast paint used with non-fluorescent particles
- Enhances indications

**Color:** White

| SKU            | Capacity Vol. | Quantity    |
|----------------|---------------|-------------|
| 387-01-2250-79 | 16 oz         | 12 per case |



## Pipeline Primers

### Features:

- The pipe surface is protected against stress corrosion cracking with industry proven SCC inhibiting additives
- Machine, spray or brush applicaiton

**Color:** Black

**Base Material:** Elastomer - Resins

**Chemical Compound:** Naptha

**Total Solids:** 30 %

| SKU           | Capacity Vol. | Packing Type |
|---------------|---------------|--------------|
| 406-1027-16OZ | 16 oz         | Aerosol Can  |
| 406-1027-GAL  | 1 gal         | Can          |





## High Performance 2300 System Inverted Striping Paints

**Features:**

- Guaranteed not to clog
- Bright, crisp lines
- Creates up to 300 linear feet with a 2" stripe
- Durable and long-lasting
- Withstands mild chemical fumes and spills
- For indoor and outdoor protection
- Use with Rust-Oleum Striping Machine #2395000

**Finish:** Matte

**Chemical Compound:** Acrylic

**Applicable Materials:** Concrete; Grass; Gravel; Pavement; Dirt

**Resistance:** Wear; Weather



| SKU         | Color  | Capacity Wt. |
|-------------|--------|--------------|
| 647-2348838 | Yellow | 20 oz        |

## High Performance 7400 System DTM Alkyd Enamels



**Base Type:** Solvent

**Odor/Scent:** Solvent

**Applicable Materials:** Metal; Most Metals; Wood

**Resistance:** Corrosive Process; Grease; Oil; Weather; Mild Chemical Fumes & Spills

| SKU         | # | Color         | Finish     | Capacity Vol. |
|-------------|---|---------------|------------|---------------|
| 647-245479  | 1 | Safety Yellow | High-Gloss | 1 gal         |
| 647-2764402 | 2 | Flat White    | Flat       | 1 gal         |
| 647-412402  | 2 | Flat Black    | Flat       | 1 gal         |
| 647-412402  | 2 | Flat Black    | Flat       | 1 gal         |
| 647-1282300 | 3 | Forest Green  | High-Gloss | 5 gal         |
| 647-925300  | 3 | Safety Blue   | High-Gloss | 5 gal         |

## High Performance V2100 System Enamel Aerosols

**Features:**

- Maximum corrosion protections
- Fast dry - 30 minutes
- Superior resistance to chipping, cracking and peeling
- Higher paint solids for excellent coverage and better gloss retention
- Can be used on surfaces that reach temperatures up to 200°F
- For indoor and outdoor protection

**Capacity Wt.:** 15 oz

**Applicable Materials:** Concrete; Masonry; Metal; Wood

**Resistance:** Corrosion



| SKU          | Color                | Finish     |
|--------------|----------------------|------------|
| 647-V2115838 | Silver Aluminum      | Metallic   |
| 647-V2124838 | Safety Blue          | Gloss      |
| 647-V2125838 | Deep Blue            | Gloss      |
| 647-V2137838 | Dark Green           | Gloss      |
| 647-V2143838 | Safety Yellow        | Gloss      |
| 647-V2147838 | Industrial Yellow    | Gloss      |
| 647-V2148838 | Equipment Yellow     | Gloss      |
| 647-V2155838 | Safety Orange        | Gloss      |
| 647-V2163838 | Safety Red           | Gloss      |
| 647-V2164838 | Bright Red           | Gloss      |
| 647-V2171838 | Tan                  | Gloss      |
| 647-V2177838 | Black                | Semi-Gloss |
| 647-V2178838 | Flat Black           | Matte      |
| 647-V2179838 | Black                | Gloss      |
| 647-V2183838 | Light Machinery Gray | Gloss      |
| 647-V2187838 | Dark Machinery Gray  | Gloss      |
| 647-V2192838 | White                | Gloss      |

## High Performance V2100 System Industrial Enamel Primers

**Features:**

- Better corrosion protection than other industrial rust-preventive spray primers
- Can be used on surfaces that reach temperatures up to 200°F (93°C)
- Fast drying, topcoat any time
- Superior adhesion - use on rusted, bare or previously painted metal

**Chemical Compound:** Acrylic; Modified Resin

**Applicable Materials:** Concrete; Masonry; Metal; Wood

**Resistance:** Corrosive Process



| SKU          | Color | Capacity Wt. |
|--------------|-------|--------------|
| 647-V2169838 | Red   | 15 oz        |
| 647-V2182838 | Gray  | 15 oz        |



## High Performance V2300 System Inverted Marking Paints

### Features:

- Bright, vivid colors
- Guaranteed not to clog
- Long-lasting
- Fast dry - less than 5 minutes
- High-output spray tip for bold, easy-to-see markings
- Use with Rust-Oleum Marking Wand or Pistol for quick and accurate site markings

**Capacity Wt.:** 15 oz

**Chemical Compound:** Modified Resin

**Applicable Materials:** Concrete; Grass; Gravel; Metal; Pavement; Dirt



| SKU          | Color                  | Finish     |
|--------------|------------------------|------------|
| 647-V2344838 | High Visibility Yellow | Semi-Gloss |
| 647-V2355838 | Fluorescent Orange     | Matte      |
| 647-V2358838 | Fluorescent Red/Orange | Matte      |

## Industrial Choice 1600 System Enamel Aerosols

### Features:

- Multi-purpose spray paint developed for everyday painting industrial projects
- Dries first - 12 minutes to the touch
- High solids provides complete, even coverage
- High Gloss, durable finish resists solvents that ordinary paints cannot

**Finish:** High-Gloss

**Capacity Wt.:** 12 oz

**Chemical Compound:** Alkyd

**Applicable Materials:** Concrete; Masonry; Most Metals; Wood

**Resistance:** Solvent; Mild Chemical Fumes & Spills



| SKU         | Color              |
|-------------|--------------------|
| 647-1622830 | Regal Blue         |
| 647-1624830 | Safety Blue        |
| 647-1644830 | OSHA Safety Yellow |
| 647-1660830 | Safety Red         |
| 647-1676830 | Ultra-Flat Black   |
| 647-1679830 | Glossy Black       |
| 647-1692830 | Glossy White       |
| 647-214645  | ANSI 61 Light Gray |

## Industrial Choice 1600 System Enamel Primer Aerosols

### Features:

- Provides a solid base for adhesion of topcoat
- Use on bare or painted wood, metal, masonry and more
- Wet or dry sandable
- Fast drying, indoor/outdoor

**Capacity Wt.:** 12 oz

**Chemical Compound:** Alkyd

**Applicable Materials:** Concrete; Masonry; Most Metals; Wood



| SKU         | Color |
|-------------|-------|
| 647-1667830 | Red   |
| 647-1680830 | Gray  |

## Industrial Choice M1600/M1800 System Precision-Line Inverted Marking Paints

### Features:

- Best resistance against premature chalking and fading
- Features a precision-line spray tip for easy-to-read, bright, vivid markings
- Marks more linear feet than the competition
- "No mess" spray tip keeps paint off fingers
- Can be applied down to 25°F (-4°C)
- Fast dry - dries in less than 5 minutes
- Locking tip keeps tip from popping off
- Virtually no overspray

**Capacity Wt.:** 17 oz

**Applicable Materials:** Concrete; Grass; Gravel; Pavement



| SKU         | Color              | Base Type |
|-------------|--------------------|-----------|
| 647-1601838 | Clear              | Solvent   |
| 647-1661838 | Fluorescent Pink   | Solvent   |
| 647-1861838 | Fluorescent Pink   | Water     |
| 647-203022  | Caution Blue       | Solvent   |
| 647-203024  | Caution Yellow     | Solvent   |
| 647-203027  | Fluorescent Orange | Solvent   |
| 647-203029  | Safety Red         | Solvent   |
| 647-203030  | White              | Solvent   |
| 647-203036  | Fluorescent Orange | Water     |
| 647-203038  | Safety Red         | Water     |
| 647-203039  | White              | Water     |



## Industrial Choice MC1800 System Precision-Line Marking Chalks

### Features:

- Guaranteed not to clog
- Can be easily removed with a wire brush and water, or pressure washing
- Marking chalk for temporary markings that will last up to 30 days
- Scuff resistant in 10 minutes

**Color:** APWA White

**Applicable Materials:** Concrete; Grass; Gravel; Pavement



| SKU        | Capacity Wt. |
|------------|--------------|
| 647-205237 | 17 oz        |

## Overall® Economical Fast Drying Enamel Aerosols

### Features:

- Indoor/Outdoor
- Economical, fast-drying industrial enamel spray
- Great for a variety of spray paint needs where durability and long-term quality are not required

**Capacity Wt.:** 10 oz

**Applicable Materials:** Concrete; Masonry; Most Metals; Wood



| SKU          | Color                |
|--------------|----------------------|
| 647-V2401830 | Sandable Gray Primer |
| 647-V2402830 | Gloss Black          |
| 647-V2403830 | Gloss White          |
| 647-V2404830 | Flat Black           |
| 647-V2407830 | Gloss Red            |
| 647-V2408830 | Gloss Blue           |
| 647-V2409830 | Gloss Yellow         |
| 647-V2410830 | Gloss Green          |
| 647-V2412830 | Aluminum             |



## Painter's Touch Ultra Cover 2x Sprays

**Features:**

- Ultimate coverage
- Smooth durable glossy finish
- Any-angle spray with comfort spray tip
- Twice the coverage in a single pass
- Done in half the time

**Color:** Black

**Base Type:** Solvent

**Finish:** Gloss

**Chemical Compound:** Acrylic Modified Alkyd

**Coverage @ Vol.:** 7 sq. ft. @ 12 oz

**Odor/Scent:** Solvent

**Applicable Materials:** Most Metals; Wood



| SKU        | Capacity Wt. |
|------------|--------------|
| 647-249122 | 12 oz        |

## Stops Rust Protective Enamel Sprays

**Features:**

- Indoor/Outdoor
- Durable, corrosion-resistant
- It's never been easier to refinish, refresh and relax

**Color:** Regal Red

**Base Type:** Solvent

**Finish:** Gloss

**Chemical Compound:** Oil Modified Alkyd

**Coverage @ Vol.:** 10 sq. ft. @ 12 oz

**Odor/Scent:** Solvent

**Applicable Materials:** Most Metals; Wood



| SKU      | Capacity Wt. |
|----------|--------------|
| 647-7765 | 12 oz        |



## Red Hot High Heat Aluminum Paint

**Features:**

- Fusing action when heat is applied
- Withstands at least 1600° F of heat
- Will not discolor, blister, peel, chip or crack
- Interior application only

**Application Temp. Range:** 1,600 °F

| SKU      | Capacity Vol. |
|----------|---------------|
| 660-6319 | 1 gal         |



## Paint-All™ Fast-Dry Enamel Paints

**Features:**

- Excellent value in a durable industrial spray paint
- Equipped with EZ TOUCH® Standard Nozzle

**Color:** Chrome Aluminum

**Finish:** Metallic

**Applicable Materials:** Steel

**Resistance:** Wear; Weather



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S04110 | 10 oz        |

## Sprayon® Stencil Inks

**Features:**

- Sprays a sharp, clean edge without smearing or smudging
- Dries quickly
- Waterproof and weather resistant
- Does not contain chlorinated solvents or Sara Title III ingredients

**Color:** Black

**Applicable Materials:** Asphalt; Cardboard; Concrete; Fabric; Glass; Lumber; Most Metals; Plastic; Steel; Wood

**Resistance:** Water; Weather



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S03108 | 12 oz        |



## Protective Coatings

**Features:**

- Stirring thins to brushing, rolling or spraying consistency without the use of thinners
- Excellent under severe corrosive conditions
- Adaptable to underground and/or underwater installations

**Color:** Black

**Applicable Materials:** Concrete; Masonry; Steel



| SKU      | Capacity Vol. |
|----------|---------------|
| 107-50-1 | 1 gal         |
| 107-50-5 | 5 gal         |



## Extend® Rust Treatment

### Features:

- One-step rust treatment goes on white and converts rust to a durable, black, metal-protective coating in 10 minutes
- Wire brush parts and apply with brush or spray
- Surface rust must be present
- Resists temperatures to 250°F intermittent, 200°F continuous

**Color:** Black

**Chemical Compound:** Synthetic

**Odor/Scent:** Mild

**Applicable Materials:** Most Metals



| SKU       | Capacity Vol. |
|-----------|---------------|
| 442-75430 | 1 qt          |
| 442-75448 | 1 gal         |

## Fixmaster® Poxy Pak™ Expoxies

### Features:

- This fast cure, general purpose epoxy bonds virtually any material
- Fills or seals cracks and rebuilds worn surfaces
- Comes in a 1 oz syringe with a built-in plunger for easy dispensing without equipment
- Working time is approximately 4 minutes

**Base Type:** Resin

| SKU         | Color |
|-------------|-------|
| 442-1324007 | Gray  |



## Nordbak® Pneu-Wear

### Features:

- Filled with small ceramic beads and silicone carbide for maximum protection against fine particle abrasion to 250°F
- Trowelable

**Chemical Compound:** Epoxy

**Stress Resistance:** 15,000 psi (compressive)



| SKU       | Capacity Wt. | Color | Hardness   |
|-----------|--------------|-------|------------|
| 442-98382 | 25 lb        | Grey  | 90 Shore D |



## EL™ 601 Red Insulating Varnishes

### Features:

- An insulating spray for general coating, impregnating and insulating electrical and electronic work
  - Excellent adhesion, flexibility, and water resistant
  - Protects surfaces against oils, moisture, acid and alkalis
- Dielectric Strength:** 2,600 V/m



| SKU           | Capacity Wt. | Color |
|---------------|--------------|-------|
| 425-A00601A00 | 15 1/4 oz    | Red   |

## P.D.R.P Waxy Protectant Coatings

### Features:

- Pliable and firm
- No cracking, aging, or hardening
- Up to 2-yr corrosion protection under severe conditions (weather, salt water)
- Contains no O.D.P

**Applicable Materials:** Plastic

**Resistance:** Corrosive Process; Moisture; Saltwater; Weather



| SKU        | Capacity Vol. | Color |
|------------|---------------|-------|
| 425-S00710 | 12 oz         | Amber |



## Toolmaker's Ink

### Features:

- Precise scribing without chipping
- Reduces glare
- Quick drying
- Contains no acids
- Resists heat

**VOC:** 0.92

**Odor/Scent:** Ketone

| SKU      | Color | Capacity Wt. |
|----------|-------|--------------|
| 205-6001 | Blue  | 12 oz        |



## Tack Cloths

### Features:

- Ideal for removing dust and other particles from your surface prior to painting

• Reusable

**Color:** Clear



| SKU           | Length | Width |
|---------------|--------|-------|
| 425-115829000 | 18 in  | 36 in |



## Chip Brushes

**Features:**

- Natural wood handle
- White Chinese bristle
- Steel ferrule

**Bristle Material:** White Chinese

**Handle Material:** Wood



| SKU            | Size     | Thickness | Trim Length |
|----------------|----------|-----------|-------------|
| 449-1500-1     | 1 in     | 5/16 in   | 1 1/2 in    |
| 449-1500-1-1/2 | 1 1/2 in | 5/16 in   | 1 1/2 in    |
| 449-1500-2     | 2 in     | 5/16 in   | 1 1/2 in    |
| 449-1500-3     | 3 in     | 3/8 in    | 1 1/2 in    |
| 449-1500-4     | 4 in     | 11/16 in  | 2 in        |
| 449-1504-4     | 4 in     | 3/8 in    | 2 in        |



## Industrial Paint Brushes

**Features:**

- 100% black bristles epoxy set in white plastic handle
- Thickness:** 1 1/2 in



| SKU     | Trim Length |
|---------|-------------|
| 455-242 | 2 in        |
| 455-243 | 2 1/4 in    |
| 455-244 | 2 1/4 in    |

## Low Cost Paint or Chip Brush

**Features:**

- 100% White bristles vulcanized in rubber
- Single thickness
- Smooth sanded handle with ferrule



| SKU       | Width | Trim Length |
|-----------|-------|-------------|
| 455-236-S | 4 in  | 1 1/2 in    |



## Acid/Flux Brushes

**Features:**

- Tin Ferrule
- Bristle Type:** Flagged Tips  
**Handle Material:** Tin Ferrule  
**Handle Type:** Cylindrical  
**Filter Material:** Flagged Tips Horsehair



| SKU       | Trim Length | Overall Length | Blade Length | Brush Length |
|-----------|-------------|----------------|--------------|--------------|
| 804-44089 | 3/4 in      | 5 3/4 in       | 3/8 in       | 5 3/4 in     |

## Economy Chip & Oil Brushes



**Features:**

- Inexpensive, multi-purpose brushes for use in applications requiring disposable brushes

**Bristle Material:** White Bristle

**Handle Material:** Wood

**Handle Type:** Curved

**Filter Material:** White Bristle

**Finish:** Sanded Hardwood

**Color:** White

| SKU       | Width | Thickness | Trim Length |
|-----------|-------|-----------|-------------|
| 804-40068 | 2 in  | 5/16 in   | 1 3/4 in    |
| 804-40070 | 3 in  | 3/8 in    | 1 3/4 in    |
| 804-40070 | 3 in  | 3/8 in    | 1 3/4 in    |

## Weiler® Chip & Oil Brushes



**Features:**

- Brushes provide lasting, efficient service at minimal cost

**Thickness:** 3/8 in

**Bristle Material:** White China

**Handle Material:** Wood

**Color:** White

**Filter Material:** White Bristle

**Finish:** Sanded Hardwood

| SKU       | Width | Trim Length |
|-----------|-------|-------------|
| 804-40185 | 4 in  | 1 3/4 in    |



## Roller Covers

**Nap Length:** 3/8 in

**Features:**

- Economy twin pack
- Includes:** (2) Covers per pack



**Features:**

- Moisture and solvent resistant cores

**Material:** Polyester Fabric

**Used With:** All Paints

| SKU         | Color  | Size |
|-------------|--------|------|
| 449-RR938-3 | Green  | 3 in |
| 449-RR938-9 | Green  | 9 in |
| 449-RC133-9 | Yellow | 9 in |

**Features:**

- 2-ply polypropylene cores
- Dripless shed-free covers for epoxy floor coatings

**Material:** White Woven

**Used With:** Epoxies

| SKU            | Size  |
|----------------|-------|
| 449-RC101-18CC | 18 in |

Industrial Safety Welding Oilfield Construction



## Roller Frames

### Features:

- 5-wire cage style, plated 5/16" rod, threaded plastic grip with metal ferrule

| SKU         | Size |
|-------------|------|
| 449-RF209-9 | 9 in |



## Magnolia Brush Paint Roller Covers

### Features:

- 100% Synthetic fiber attached to a 4-ply Phenolic Core backing

**Material:** 100% Synthetic Fiber

| SKU        | Length | Trim Length |
|------------|--------|-------------|
| 455-4SC038 | 4 in   | 3/8 in      |



## Linzer Tray Liners

### Features:

- Makes clean-up a snap
- Durable plastic

**Material:** Plastic

| SKU       | Capacity Vol. |
|-----------|---------------|
| 449-RM410 | 1 qt          |



## Roller Trays

### Features:

- Paint wells and ramps allow easy roller rotation and pick up
- Helps remove excess paint from rollers to reduce dripping and running

**Material:** Metal

| SKU          | Capacity Vol. |
|--------------|---------------|
| 425-11764290 | 2 qt          |



## Tray Liners

### Features:

- Designed to make clean up easier
- For use with roller trays
- Constructed of quality materials

**Material:** Plastic

| SKU          | Size |
|--------------|------|
| 425-99355600 | 9 in |



## INDUSTRIAL Marking Wands

### Features:

- Constructed of durable, rugged plastic and lightweight steel
- Applies a uniform, 1" to 1-1/2" width of paint

| SKU        |
|------------|
| 425-K07096 |




## Binks® Spray Guns

### Features:

- Brass body spray gun used for spraying solvents to clean engines and other machinery
- Extra wide trigger, large control knobs, and an ergonomic forged aluminum body

**Fluid Inlet:** 3/8 in (NPSM)

| SKU             | Inlet Size    | Body Material |
|-----------------|---------------|---------------|
| 105-6121-4307-9 | 1/4 in (NPSM) | Aluminum      |
| 105-6530-0000-1 | 1/4 in (NPSM) | Brass         |



## Spray Socks

### Features:

- Provides comfortable protection against overspray and other particulates
- Spray Sock fits over the head and can be worn with goggles, half mask or full mask respirators

**Material:** Stretch-Knit

| SKU         | Size Group        | Quantity       |
|-------------|-------------------|----------------|
| 037-1410-12 | One Size Fits All | 12 per package |



## Tank Liners

### Features:

- Anti-static
- Contoured lip preventing leakage
- FDA approved High-Density Polyethylene

| SKU             | Capacity Vol. | Quantity   |
|-----------------|---------------|------------|
| 105-PT-78-K60   | 2.8 gal       | 60 per box |
| 105-PTL-408-K20 | 9.8 gal       | 20 per box |



**ITW Professional Brands**

## Dykem® Layout Fluids

**Features:**

- Prevents glare with a uniform, deep color
- Dries in minutes
- Reduces eyestrain
- Translucent
- Sharp, clear, precise lines
- Flexible, non-cracking, and non-chipping

**Resistance:** Chlorinated Solvents; Gasoline; Kerosene; Oil; Synthetic Coolants; Toluene



2



| SKU       | # | Capacity Vol. | Packing Type | Color |
|-----------|---|---------------|--------------|-------|
| 253-80000 | 1 | 16 oz         | Aerosol Can  | Blue  |
| 253-80096 | 2 | 16 oz         | Aerosol Can  | Red   |
| 253-80300 | 1 | 4 oz          | Brush-In-Cap | Blue  |
| 253-80400 | 1 | 8 oz          | Brush-In-Cap | Blue  |
| 253-80600 | 1 | 930 mL        | Bottle       | Blue  |



## Layout Fluids

**Features:**

- Fast-drying, non-flaking, non-etching, won't peel
- Heat resistant, non-corrosive
- Adheres to metal or glass
- Equipped with EZ TOUCH® FANSPRAY® Nozzle

**Resistance:** Corrosive Process



| SKU        | Capacity Wt. |
|------------|--------------|
| 425-S00603 | 12 oz        |



## Ice-Off® Windshield Spray De-Icer

**Features:**

- Melts ice, snow, and frost on contact
- Harmless to car finish

| SKU       | Container Size |
|-----------|----------------|
| 125-05346 | 12 oz          |



## De-Icers

**Features:**

- Melts frost and ice fast
- Harmless to car finishes
- Convenient and easy to use
- Ozone safe propellant
- Non-smear formula
- Frees ice encrusted wipers

| SKU         | Capacity Vol. |
|-------------|---------------|
| 145-DI-11-5 | 11 1/2 oz     |



Specialty Products for Today's Professional

## All Purpose Water Finding Paste



**Features:**

- Paste will turn yellow-green in the presence of water
- Fast, reliable way to detect water in fuel storage tanks
- Accurately detects phase separation in ethanol blend applications
- For all petroleum fuels

| SKU      | Capacity Wt. |
|----------|--------------|
| 296-AP02 | 2 oz         |

## Regular Water Finding Paste



**Features:**

- Reformulated for better consistency and improved color change
- Quickly and accurately detects water in fuel storage tanks
- Mustard yellow paste turns red upon contact with water
- Effective with gasoline, diesel and other solutions but not for ethanol blends

| SKU      | Capacity Wt. |
|----------|--------------|
| 296-WT25 | 2 1/2 oz     |



## Liquid Finding Paste



**Features:**

- Golden brown turns red on contact
- Gauges petroleum for water content, sulphuric acid, nitric acid, hydrochloric acid, ammonia, soap, salt, and other chloride solutions

| SKU      | Capacity Wt. | Packing Type |
|----------|--------------|--------------|
| 460-KK01 | 3 oz         | Tube         |

**Features:**

- Light pink turns red on contact with gasoline, naphtha, kerosene, gas oil, crude oil, and other chemicals

| SKU      | Capacity Wt. | Packing Type |
|----------|--------------|--------------|
| 460-KK02 | 2 1/4 oz     | Jar          |



## Armor All® Original Protectants

**Features:**

- Protects vinyl, rubber and plastic from fading and cracking caused by UV, ozone, oxidation and extreme temperatures

| SKU       | Capacity Vol. | Quantity   |
|-----------|---------------|------------|
| 158-10326 | 32 oz         | 6 per case |

