

Air Compressors .....	436	Pneumatic Engravers.....	445
Air Hose Fittings.....	438, 439	Pneumatic Hacksaw Parts & Accessories .....	440
Air Hose Reels .....	439	Pneumatic Hacksaws .....	440
Air Hoses.....	437	Pneumatic Impact Wrenches.....	441, 442
Balancers .....	452	Pneumatic Pad Sanders.....	450
Blow Guns.....	436, 437	Pneumatic Ratchet Wrenches .....	445
Pneumatic Angle Grinders .....	446, 447	Pneumatic Reciprocating Saws .....	440
Pneumatic Belt Sander Parts & Accessories.....	446	Pneumatic Riveting Hammers.....	452
Pneumatic Belt Sanders .....	445	Pneumatic Scaler Parts & Accessories.....	451, 452
Pneumatic Chipping Hammers .....	450	Pneumatic Scalers.....	450, 451
Pneumatic Chisels & Steel .....	450	Pneumatic Screwdrivers.....	441
Pneumatic Demolition Hammers .....	450	Pneumatic Stapler Parts & Accessories .....	441
Pneumatic Die Grinders.....	447, 448	Pneumatic Straight Grinders.....	447
Pneumatic Drills .....	440, 441	Pneumatic Tampers & Rammers .....	452



## Electric-EHP™ Portable Compressors

### Features:

- Oil free, maintenance free pump, for convenient use
- Efficient high pressure motor allows the compressor to be run with an extension cord (12 Ga. or heavier, 50 ft. or less) due to consistent amp draw requirement of the compressor
- High flow coupler allows for maximum nailer performance
- Robust dual purpose handle provides additional protection to the compressor along with serving as a hose wrap
- Metal console panel provides a display area well as protects the gauges, couplers, and regulator

**Frequency:** 60 Hz

**Amps:** 15 A

**Voltage:** 120 V

**Flow @ Pressure:** 5.4 CFM @ 100 psi

**Height:** 44 3/4 in

**Drive Type:** Belt

**Wt.:** 88 lb

**Noise Level [Max]:** 78 dB



SKU	Tank Cap.	Power Capacity	Operating Pressure	Speed
115-D55168	15 gal	1 4/5 hp	200 psi	1,750 rpm



The Right Connection™


## ASME Air Receiver Manifolds

### Features:

- All openings are female NPT thread
- ASME compressed air receiver with protective frame

**Inlet Connection:** 2 in NPT(M)

**Outlet Connection:** 1 in NPT(F); 1/2 in NPT(F); 3/4 in NPT(F)



SKU	Capacity Vol.	Pressure [Max]	Material
238-1217AR-4AK	7 gal	200 psi	Metal



## Gas-Driven Portable Wheelbarrow Compressors

### Features:

- Built to last, oil-lube compressors are designed for the toughest 100% continuous duty applications
- Designed for maximum maneuverability on the job site
- The quick disconnects makes it able to power multiple tools

**Engine Type:** Honda

**Flow @ Pressure:** 11.8 CFM @ 90 psi

**Height:** 25 in

**Length:** 43 in

**Includes:** (2) Quick Disconnects; Gauge; Pressure Switch; Regulator



SKU	Tank Cap.	Power Capacity	Operating Pressure	Outlet Size
383-SS3J5.5GH-WB	16 gal	5 1/2 hp	135 psi	3/8 in (NPT)



## 600 Series Blow Guns

### Features:

- Available with a wide selection of tips to fit any application
- Tough zinc die cast body
- Four self-lubricating O-rings prevent valve leakage, making blow gun repairs unnecessary

**Inlet Size:** 1/4 in (NPT)

**Inlet Pressure:** 150 psi

**Body Material:** Zinc



SKU
166-600S-DL



## 700 Series Standard Blow Guns

### Features:

- Vinyl handle covering increases user comfort while allowing a more positive grip
- Available with a wide selection of tips to fit any application

**Body Material:** Aluminum



SKU	Inlet Size
166-700S	1/4 in (NPT)



### Force 5™ Air Guns

**Features:**

- Adjustable auxiliary handle
- Rugged all metal construction
- Delivers 100% of the power as supplied by the air compressor still meeting OSHA standards
- Designed for heavy duty industrial and construction

**Inlet Size:** 3/8 in (FNPT)

**Material:** Aluminum Extension

**Control Type:** Dead-Man Trigger

**Nozzle Type:** Venturi

**Operating Pressure:** 120 psi



SKU	Extension Length	Length
335-F5048AA	48 in	59 5/8 in
335-F5060AA	60 in	71 5/8 in

### Jet Guard Safety Air Guns

**Features:**

- Venturi nozzle delivers 100% more thrust compared to conventional air guns
- Patented protective air cone protects operator from dangerous chip fly-back

**Inlet Size:** 1/4 in (FNPT)

**Body Material:** Cast Aluminum



SKU	Length	Operating Pressure
335-74SK	6 1/2 in	120 psi

### Long John® Safety Air Guns

**Features:**

- Cleans hard-to-reach areas
- Venturi nozzle delivers 100% more thrust compared to conventional air guns
- Best for cleaning benchtops, workstations, machinery and equipment

**Inlet Size:** 1/4 in (FNPT)

**Material:** Aluminum Extension

**Body Material:** Cast Aluminum

**Operating Pressure:** 150 psi



SKU	Extension Length
335-75LJ006AA	6 in
335-75LJ012AA	12 in
335-75LJ018AA	18 in
335-75LJ024AA	24 in
335-75LJ036AA	36 in
335-75LJ048AA	48 in
335-75LJ060AA	60 in

### Syphon Spray Guns

**Features:**

- Pistol grip style air gun
- Separate liquid and air controls provide user with optimum flexibility
- Best for spraying oils, solvents, cleaners, disinfectants, insecticides, mold release agents and coatings

**Inlet Size:** 1/4 in (FNPT)

**Material:** Aluminum Extension

**Body Material:** Cast Aluminum

**Includes:** 6 ft. Syphon Hose w/Sinker



SKU	Flow	Extension Length	Length
335-79SG012	16 gal/h	12 in	19 1/2 in

### Whisper Jet® Safety Air Guns

**Features:**

- Venturi nozzle delivers 100% more thrust compared to conventional air guns
- Unique Coandaire® nozzle reduces noise 6 to 20 dB compared to conventional air guns

**Inlet Size:** 1/4 in (FNPT)

**Body Material:** Cast Aluminum

**Nozzle Type:** Aluminum Coandaire®



SKU	Length	Operating Pressure
335-80WJ	6 in	120 psi

### Xtra Thrust® Safety Air Guns

**Features:**


- Comes with a full length trigger and an aluminum venturi nozzle which increases thrust and limits static pressure to less than 30 psi if the tip is blocked

**Inlet Size:** 1/4 in (FNPT)

**Material:** Aluminum Extension

**Body Material:** Cast Aluminum

**Operating Pressure:** 150 psi



SKU	Extension Length
335-75XT012AA	12 in
335-75XT024AA	24 in
335-75XT036AA	36 in
335-75XT048AA	48 in



### Flexcoil® Polyurethane Self-Storing Air Hoses

**Features:**

- Highly kink and abrasion resistant
- Outstanding coil memory
- Resistant to most oils and fuels

**Connection Type:** Male/Male

**Color:** Blue; Blue

**Fitting Size:** 1/4 in

**Tube Material:** Polyurethane


**Fitting Type:** (2) Swivel

**Measuring System:** Inch



SKU	Inner Dia	Outside Dia	Length	Pressure @ Temp.
166-PU14-25B-B	1/4 in	3/8 in	25 ft	125 psi @ 75 °F

## Coilflow™ Industrial Interchange Couplers



### Features:

- This series of couplers and connectors is engineered to interchange with the Industrial interchange designs of all manufacturers
- Standard packaging consists of twenty-five pieces per box or ten pieces per plastic bag

**Connection Type:** Female/Female

**Female Quick:** 1/4 in

**Shape:** Straight

**Measuring System:** Inch

**Body Material:** Brass

**Female Thread:** 1/4 in (NPT)

SKU
166-150



## Air Chief Industrial Automatic Coupler Standard Hose Barb



### Features:

- Automatic - push to connect
- Couplers shut-off when disconnected
- Air chief industrial couplers are the popular industrial design and will interchange with many other makes
- MIL-C-4109F/A-A-59439
- For air service only
- Operating pressure for couplings utilizing hose barb connections may be dramatically reduced to that of the hose rating and/or hose end connection combination
- Consult hose manufacturer's catalog for hose end connection ratings
- If in doubt, test under controlled conditions for suitability to application
- Dixon cannot assume liability for misapplication of production resulting in equipment down-time, lost production, and/or personal injury including death

**Material:** Brass

SKU	Hose I.D.	Body Size	Operating Pressure	Flow
238-DCB1045	1/2 in	1/2 in	300 psi	91 CFM

## Air Chief Industrial Quick Connect Fittings



### Features:

- Sturdy, tough quick connect fittings are for on and off applications without the need of any tools
- They are made of steel and are corrosion- and rust-resistant
- With a 300 operating pressure the connect fittings are tiny and secure

**Operating Pressure:** 300 psi

SKU	Connection Type	Body Material	Height
238-DC10	Female/Female	Steel	2.96 in
238-DC1045	Male/Female	Steel	3.62 in
238-DC20	Female/Female	Brass	1.83 in
238-DC2044	Male/Female	Brass	2.49 in
238-DC21	Male/Female	Brass	2 1/2 in
238-DCP21	Male/Male	Steel	1.66 in

## Air King Universal Couplings

### Features:

- Designed to provide quick, effective and easy coupling of air hose
- Made of high strength iron and perform great on jackhammer and other industrial applications

**Operating Pressure:** 110 psi

**Body Material:** Malleable Iron



SKU	Connection Type	Height
238-AM10	Genderless	3.438 in
238-AM6	Male/Female	4.188 in
238-AM7	Male/Genderless	3.63 in
238-AM8	Female/Genderless	2 1/2 in

## King Safety Cables



### Features:

- King cable is the low cost answer to eliminate injuries by broken air hose connections
- Highly resistant to rust and corrosion
- No tools needed - easy to install and remove

**Connection Type:** Hose End/Hose End

SKU	Cable/Wire Size	Hose I.D.
238-WA2	1/4 in	1 1/2 in - 3 in
238-WA4	3/8 in	4 in
238-WB1	1/8 in	1/2 in - 1 1/4 in
238-WB3	3/16 in	1/2 in - 2 in

## Safety Pin Universal Couplings

### Features:

- The use of an Air King safety clip is necessary to ensure couplings will not become accidentally disconnected
- This guarantees the fittings are properly connected as the pin will not go through the holes in the mating flanges until couplings are locked in place
- Only one air king safety clip is required for each Air King universal coupling



SKU	Length
238-AKSP1	1 3/4 in


# LINCOLN

## Lincoln Style Couplers & Nipples

### Features:

- Positive action locking mechanism so coupler cannot be detached accidentally
- Extra large air passage insures greater air flow
- Automatic air check valve shuts off air instantly when uncoupled, providing leak-proof seal
- Corrosion-resistant steel plug and stainless steel check and check spring for long service life
- Free swiveling action prevents curling or kinking of air hose

**Flow @ Pressure:** 52 SCFM @ 100 psi  
**Operating Pressure:** 250 psi



SKU	Hose I.D.	Dia.	Thread Size
438-815	1/4 in	1 1/16 in	1/4 in (NPT)



## Coxreels® Heavy Duty Hose Reels

### Features:

- Adjustable solid rubber hose stop for convenient lead length positioning
- Cartridge-style spring motor easily accessed, serviced and/or replaced if necessary
- High-quality steel construction & durable epoxy powder-coat finish
- Standard hose is for air or water service only



SKU	Inner Dia	Outside Dia	Length	Operating Pressure
170-SH-N-450	1/2 in	27/32 in	50 ft	300 psi

## EZ-Coil® Performance Safety Reels

### Features:

- Patented EZ-Coil™ Rewind Safety System
- EZ-COIL™ retracts up to 80% slower for greater safety
- Easily wraps, stores and protects hose improving workplace safety
- High-quality heavy-duty steel construction
- Durable “CPC” proprietary powder coat finish
- Brass NPT swivel inlet
- Guide arm adjusts for wall, ceiling or floor mounting
- Rolled edges & ribbed discs provide extra strength and rigidity
- Multi-position locking ratchet secures hose at desired length
- 1/4” steel base and support post adds rigidity reducing vibration
- Made in the USA



SKU	Inner Dia	Outside Dia	Length	Operating Pressure
170-EZ-P-LP-350	3/8 in	21/32 in	17 1/8 in	300 psi

## Performance Hose Reels

### Features:

- Easily wraps, stores and protects hose improving efficiency
- High-quality heavy-duty steel construction
- Durable proprietary “CPC” powder coat finish
- Brass NPT swivel inlet machined from solid
- Guide arm adjusts for wall, ceiling or floor mounting
- Factory-matched cartridge-style lubricated spring motor
- Rolled edges & ribbed discs for maximum strength & protection
- Multi-position locking ratchet secures hose at desired length
- 1/4” steel base and support post adds rigidity reducing vibration
- Made in the U.S.A.

**Operating Pressure:** 300 psi



SKU	Inner Dia	Outside Dia	Length
170-P-LP-325	3/8 in	21/32 in	13 1/2 in
170-P-LP-350	3/8 in	21/32 in	17 1/8 in
170-P-LP-450	1/2 in	27/32 in	17 1/8 in



## Air/Water Hose Reels

### Features:

- The steel guide arm and dual pedestal base are stamped with ribs and gussets and robotically welded to ensure maximum strength and lightest possible weight
- The unitized cast fluid path and ratchet reduce wearable parts and ease of assembly
- The full flow swivel combines the highest grade seal design and materials with bearing areas to ensure maximum service life
- The unitized cast aluminum fluid path with built in declutching arbor virtually eliminates possibility of leakage and spring damage due to reverse winding
- Only the highest quality spring steel is used and conditioned to ensure there are no imperfections offering maximum service life
- Individually powder-coated components offer the maximum protection from premature corrosion

**Inlet Size:** 1/2 in (NPTF)



SKU	Inner Dia	Outside Dia	Operating Pressure	Hose Length	Outlet Size
523-82075OLP	1/2 in	3/4 in	300 psi	75 ft	1/2 in (MNPT)

## Gas Welding Hose Reel

### Features:

- Double-sealed, specially molded o-rings prevent leakage. The swivel inlets are both permanently identified with machined grooves on the gas side to assure proper installation
- Individually powder-coated components offer the maximum protection from premature corrosion
- The robotically welded steel base offers maximum strength and consistent quality
- The seals and hoses are T-grade for use with a variety of welding gases including MAPP, propane, natural, and fuel gases



SKU	Operating Pressure	Hose Length	Outlet Size
523-TW84100OLPT	200 psi	100 ft	9/16 in (flare)



## Pneumatic Hacksaws

### Features:

- Ideally suited for trimming pipes and profiles made of steel, cast-iron, autoclaved aerated concrete and plastics

**Cutting Cap.:** 24 in. Diam. Max; 11-27/64 W x 21-11/16 in. H; 18-3/4 L x 6-3/4 in. H

**Watts:** 1,100 W

**Operating Pressure:** 87 psi

**Air Consumption:** 51.2 CFM

**Includes:** (1) Additional Handle; (2) Blades; Hose Coupling; Set of Wrenches



SKU	Stroke Length	Speed
232-ST5-325R	2 3/8 in	330 rpm

## FEIN Hacksaw Blades

### Features:

- Hacksaw Blade
  - For pipe cutting
  - Made of high strength steel
- Cutting Edge Material:** HSS



SKU	Length	Teeth Per Inch	Thickness	Cutter Dia
232-6-35-03-069-00-8	20 7/8 in	12	1/16 in	14 3/4 in
232-6-35-03-073-00-6	23 5/8 in	16	5/64 in	17 5/16 in



## Sioux Tools Air Reciprocating Saws

### Features:

- Swivel air inlet

**Inlet Size:** 1/4 in (NPT)

**Inlet Pressure:** 90 psig

**Handle Type:** Back D-Handle/Body Grip

**Control Type:** Variable Speed; Trigger Lock-Off



SKU	Cycle Rate	Air Consumption	Noise Level [Max]
672-1300	0 strokes/min - 1,800 strokes/min	35 CFM	86 dB



## Air Angle Drills

### Features:

- Durable Jacobs multi-craft chuck
- Grease plug for easy preventative maintenance
- Precision machine gearing ensures maximum power transfer and durability

**Chuck Type:** Keyed

**Air Consumption @ Load:** 17 CFM

**Inlet Size:** 1/4 in NPT(F)

**Hose Size:** 3/8 in

**Noise Level [Max]:** 89 dB

**Control Type:** Lever Throttle; Reversible



SKU	Chuck Size	Free Speed	Power Capacity	Inlet Pressure
383-7807R	3/8 in	1,800 rpm	0.33 hp	90 psi

## Ingersoll-Rand Pneumatic Drills

**Chuck Type:** Keyed

**Inlet Size:** 1/4 in

**Control Type:** Reversible; Trigger

**Housing Material:** Aluminum

**Handle Type:** Pistol Grip



### Features:

- Quick reverse lever
- Variable speed throttle for starting holes easily
- Heavy duty ball and needle bearing
- More power and long tool life
- Planetary gear reduction balances the load

SKU	Chuck Size	Free Speed	Power Capacity	Air Consumption @ Load
383-7803RA	1/2 in	500 rpm	1/2 hp	27 CFM

### Features:

- Requires less air to deliver more power
- Has a convenient reverse mode with trigger-mounted control
- The palm-swelled handle and contoured professional trigger provide greater comfort and control

SKU	Chuck Size	Free Speed	Power Capacity	Air Consumption @ Load
383-7802RA	3/8 in	2,000 rpm	1/2 hp	26 CFM



### Maintenance Drills

**Features:**

- Has a convenient reverse mode with trigger-mounted control
- Requires less air to deliver more power
- The palm-swelled handle and contoured professional trigger provide greater comfort and control

**Chuck Type:** Keyless  
**Inlet Size:** 1/4 in (NPT)

**Control Type:** Reversible; Trigger

**Inlet Pressure:** 90 psi  
**Air Consumption:** 4 CFM

**Air Consumption**

**@ Load:** 26 CFM

**Hose Size:** 3/8 in



SKU	Chuck Size	Free Speed	Power Capacity
383-7802RAKC	3/8 in	2,000 rpm	1/2 hp



### Sioux Tools Pistol Grip Drills

**Features:**

- 3 idler gear system for increased life and load capacity
- Ergonomic handle with soft textured grip
- Light weight aluminum housing

**Chuck Type:** Keyed  
**Inlet Pressure:** 90 psi

**Air Consumption:** 30 CFM

**Spindle Thread:** 3/8 in - 24

**Inlet Size:** 1/4 in (NPT)

**Noise Level [Max]:** 80 dB

**Control Type:** Trigger; Non-Reversing



SKU	Chuck Size	Free Speed
672-SDR10P12N3	3/8 in	1,200 rpm
672-SDR10P26N3	3/8 in	2,600 rpm



### BOSTITCH

### PowerCrown™ Heavy Duty Staples

**Features:**

- Adhesive collated
- Staple Height:** 3/8 in  
**Cross Section Length:** 0.05 in  
**Cross Section Width:** 0.019 in  
**Cross Section Shape:** Rectangular



SKU	Staple Width	Quantity
688-STCR50193/8-5M	7/16 in	5,000 per pack



### Ingersoll-Rand Pneumatic Screwdrivers

**Features:**

- Positive action clutch, for full torque throughout rundown
- Convenient one-handed operation, with reverse control at trigger
- Variable speed throttle for easy starts
- Through-handle exhaust
- Compact, lightweight and maneuverable

**Drive Type:** Hex

**Inlet Size:** 1/4 in NPT(F)

**Control Type:** Reversible; Trigger Start



SKU	Drive Size	Free Speed	Air Consumption	Noise Level [Max]
383-371	1/4 in	1,800 rpm	4 CFM	78 dB



### 3/4" Dr. Impact Wrenches

**Features:**

- Excellent on hard joints with a good power/weight ratio
- Steel clutch housing
- 3-piece construction
- Built-in power regulator
- Quick torque adjustment

**Drive Type:** Square

**Retainer Type:** Hole

**Clutch Type:** Pin

**Max. Torque:** 750 ft. lb. Reverse

**Noise Level [Max]:** 100 dB

**Inlet Size:** 3/8 in (NPTF)

**Length:** 11 in



SKU	Drive Size	Torque [Max]	Free Speed [Max]	Air Consumption
147-CP9561	3/4 in	75 - 500 ft lb	5,500 rpm	30 CFM

### 3/4" Drive Pneumatic Impact Wrenches

**Features:**

- Air inlet swivel
- Air regulator
- Friction ring retainer
- Oil bath clutch
- One handed reverse button

**Drive Type:** Square

**Retainer Type:** Ring

**Clutch Type:** Pin

**Inlet Size:** 1/4 in

**Includes:** Tool; Safety and Instruction Manuals



SKU	Drive Length	Air Consumption @ Load	Pressure	Noise Level [Max]
147-772H	3/4 in	24 CFM	90 psi	107 dB



## 3/8" Drive Pneumatic Impact Wrenches



**Features:**

- Butterfly forward/reverse throttle
- Air inlet swivel
- Lightweight
- Rocking dog clutch
- Air regulator
- Friction ring retainer

**Drive Type:** Square

**Retainer Type:** Ring

**Clutch Type:** Rocking Dog

**Inlet Size:** 1/4 in

**Control Type:** Butterfly Throttle

**Includes:** Tool; Safety and Instruction Manuals

**Housing Material:** Aluminum

SKU	Drive Length	Air Consumption @ Load	Pressure	Noise Level [Max]
147-CP7722	3/8 in	13 CFM	90 psi	108 dB

## Chicago Pneumatic 1/2" Dr. Impact Wrenches



**Features:**

- Compact & ergonomic
- High torque in small package
- Through handle air exhaust
- Exhaust directed away from work piece

**Drive Type:** Square

**Retainer Type:** Friction Ring

**Clutch Type:** Dyna Pact™

**Max. Torque:** 425 ft. lb. Reverse

**Inlet Size:** 1/4 in (NPTF)

SKU	Drive Size	Torque	Free Speed [Max]	Air Consumption	Noise Level [Max]
147-734H	1/2 in	25 - 380 ft lb	8,400 rpm	15 CFM	94 dB

## Chicago Pneumatic 3/8" Dr. Impact Wrenches



**Features:**

- Tri-spring anti slip head
- Grease fitting on reverse lever
- Contoured handle

**Drive Type:** Square

**Retainer Type:** Ball

**Inlet Size:** 1/4 in

**Includes:** Tool; Safety and Instruction Manuals

SKU	Drive Size	Drive Length	Air Consumption	Pressure	Noise Level [Max]
147-CP828	3/8 in	3/8 in	15 CFM	90 psi	96 dB



## 1" Air Impactool™ Wrenches

**Drive Type:** Square  
**Control Type:** Trigger



**Features:**

- Handle exhaust directs air away from the work
- 3-position power regulator provides torque management

SKU	Free Speed	Air Consumption	Inlet Size
383-295A	5,000 rpm	10 CFM	3/8 in NPT(F)

**Features:**

- Impressive power-to-size ratio
- Pressure-feed lube system for longer service life
- Dead handle improves operator control

SKU	Free Speed	Air Consumption	Noise Level [Max]	Inlet Size
383-271	5,500 rpm	9.5 CFM	101.1 dB	3/8 in NPT(F)

**Features:**

- Superior balance, "angled-down" exhaust
- High efficiency 6-vane air motor
- 3-position power regulator

SKU	Free Speed	Air Consumption	Noise Level [Max]	Inlet Size
383-285B	5,000 rpm	10 CFM	107 dB	1/2 in NPT(F)
383-285B-6	5,000 rpm	10 CFM	107 dB	1/2 in NPT(F)

## 3/4" Air Impactool™ Wrenches

**Features:**

- Combines a six-vane high output air motor, through-bolt construction, ergonomic handle and housing design create an impact tool that offers increased power and durability
- 3-position power regulator
- 360 degree swivel inlet
- Full power reverse

**Drive Type:** Square



SKU	Drive Size	Torque	Free Speed	Air Consumption	Noise Level [Max]
383-2161XP	3/4 in	1,250 ft lb	6,000 rpm	10 CFM	98 dB

**Features:**

- Combines compact size with high output
- Handle exhaust directs air away from you
- Trouble-free, longer performance aided by the Pressure-Feed Lube System

SKU	Drive Size	Torque	Cycle Rate	Free Speed	Air Consumption
383-259	3/4 in	200 - 800 ft lb			8 CFM
383-261	3/4 in	200 - 1,100 ft lb	1,000 ipm	5,500 rpm	9.5 CFM





### 3/8" Air Impactool™ Wrenches

**Features:**

- More torque, less vibration
- Pistol-style yet extremely compact and lightweight
- Built-in power regulator prevents over-torquing
- Handle exhaust



SKU	Drive Size	Torque	Cycle Rate	Free Speed	Air Consumption
383-212	3/8 in	20 - 180 ft lb	1,500 ipm	10,000 rpm	2.5 CFM

**Features:**

- Titanium hammer case is lightweight with unparalleled durability
- The original, perfected twin hammer mechanism utilizes proprietary advanced metallurgy
- Patented four-position power regulator dial for MAX control
- New 7-vane motor delivers even more power
- Patented one-hand forward/reverse for easy operation
- Feather-touch trigger enables impressive control

**Drive Size:** 3/8 in

SKU	Torque	Cycle Rate	Free Speed	Air Consumption
383-2115TIMAX	25 - 230 ft lb	1,500 blows/min	15,000 rpm	4 CFM



### 1/2" Air Impactool™ Wrenches

**Drive Size:** 1/2 in

**Features:**

- Handle exhaust
  - High output impact mechanism
  - Balanced design with easy-to-use controls, tease trigger
  - Full power in reverse; adjustable power in forward
- Free Speed:** 9,500 rpm  
**Air Consumption:** 4 CFM



SKU	Cycle Rate (ipm)	Inlet Size
383-236	1,200	1/4 in NPT(F)

**Features:**

- Pressure-Feed lubrication System automatically greases the impact mechanism
- Powerful, with smooth, balanced blows

**Free Speed:** 7,000 rpm

**Air Consumption:** 5.4 CFM

**Length:** 1.817 in; 7.3 in

SKU	Cycle Rate (ipm)	Inlet Size
383-244A	1,300	1/4 in (NPT)

**Features:**

- The original, perfected twin hammer mechanism utilizes proprietary advanced metallurgy
- Patented four-position power regulator dial for MAX control
- Patented one-hand forward/reverse for easy operation
- Pressure-Feed lubrication System automatically greases the impact mechanism
- Contoured handle for comfort and control

SKU	Cycle Rate (blows/min)	Free Speed	Air Consumption	Inlet Size
383-2135PTIMAX	1,250	9,800 rpm	5 CFM	1/4 in NPT(F)
383-2135TIMAX	1,250	9,800 rpm	5 CFM	1/4 in NPT(F)
383-231C	1,200	8,000 rpm	4.2 CFM	1/4 in (NPT)

**Features:**

- Titanium hammer case is lightweight with unparalleled durability
- The original, perfected twin hammer mechanism utilizes proprietary advanced metallurgy
- Patented four-position power regulator dial for MAX control
- Patented one-hand forward/reverse for easy operation
- Feather-touch trigger enables impressive control
- Patented Quiet Tool technology, which reduces sound levels caused by air pulsating through the impact motor

**Free Speed:** 9,800 rpm

**Air Consumption:** 5 CFM

SKU	Cycle Rate (blows/min)	Inlet Size
383-2135QPTIMAX	1,250	1/4 in NPT(F)
383-2135QTIMAX	1,250	1/4 in NPT(F)



## 3900Ti Series Impact Wrenches

### Features:

- Variable speed lever-style throttle
- Built in power regulator
- Pressure-feed mechanism lubrication
- Titanium Hammer Case for added durability

**Inlet Size:** 1/2 in (NPT)

**Hose Size:** 3/4 in



SKU	Drive Size	Torque	Free Speed	Air Consumption @ Load
383-3940B2Ti	1 in	1,650 ft lb	6,000 rpm	75 CFM

## Industrial Duty Impact Wrenches

### Features:

- Ideal for when your work demands more power
- Designed to break free large, tough fasteners

**Free Speed:** 5,500 rpm

**Air Consumption:** 40 CFM

**Pressure:** 90 psi

**Inlet Size:** 3/8 in (NPT)



SKU	Drive Size	Torque	Cycle Rate
383-1720P1	3/4 in	200 - 1,000 ft lb	1,000 ipm

### Features:

- Pressure feed impact mechanism lubrication

**Free Speed:** 5,000 rpm

**Air Consumption:** 23 CFM

**Pressure:** 90 psi

**Inlet Size:** 1/4 in (NPT)

SKU	Drive Size	Torque	Cycle Rate
383-2906P1	1/2 in	40 - 500 ft lb	1,200 ipm

### Features:

- 1" square drive or No. 5 spline models
- Plated ductile iron hammer case and durable epoxy-coated motor housing and handle
- Twin hammers mean more power per pound
- Pressure feed impact mechanism lubrication
- Two piece motor housing

**Free Speed:** 6,000 rpm

**Air Consumption:** 47 CFM

**Pressure:** 90 psi

**Inlet Size:** 1/2 in (NPT)



SKU	Drive Size	Torque	Cycle Rate
383-1712B2	1 in	450 - 1,350 ft lb	800 ipm

### Features:

- **MAX Durability:** Built to last and designed to withstand tough use in rugged environments
- **MAX Power:** 1350 ft-lbs maximum reverse torque from a tool that weighs just 7.4 lbs and is compact enough to access tight spaces
- **MAX Productivity:** An air motor that's 16% more efficient than its predecessor and an easy-to-clean inlet screen means less downtime, better tool performance, and less money spent on compressed air

**Pressure:** 90 psi

**Inlet Size:** 1/2 in (NPTF)



SKU	Drive Size	Torque	Cycle Rate	Air Consumption
383-2145QIMAX	3/4 in	200 - 900 ft lb	1,150 blows/min	8.5 CFM

## Ingersoll-Rand 1/2" Dr. Impact Wrenches

### Features:

- Durable epoxy-coated motor housing and handle
- Plated steel hammer case
- Pressure-Feed impact mechanism lubrication

**Drive Type:** Square

**Inlet Size:** 1/4 in (NPT)



SKU	Torque	Cycle Rate	Free Speed	Hose Size
383-2705P1	40 - 400 ft lb	1,200 ipm	8,500 rpm	3/8 in
383-2707P1	40 - 450 ft lb	1,300 ipm	7,750 rpm	3/8 in

## Street Legal™ ThunderGun® Impact Wrenches

### Features:

- Distinctive appearance similar to the IR ThunderGun racing tool
- Torque (Max) reverse power of 625 ft.lbs
- Adjustable forward power regulator

**Drive Type:** Square

**Inlet Size:** 1/4 in (NPT)

**Air Consumption:** 5.4 CFM

**Hose Size:** 3/8 in



SKU	Drive Size	Torque	Cycle Rate	Free Speed
383-232TGSL	1/2 in	400 ft lb	1,200 ipm	10,000 rpm

## Super Duty Impact Wrenches

### Features:

- Titanium hammer case
- Ergonomic handle design
- Three position power regulator

**Drive Size:** 1 in

**Air Consumption:** 60 CFM



SKU	Torque	Cycle Rate	Free Speed	Center to Side Distance
383-2925P3TI	1,450 ft lb	1,050 ipm	5,200 rpm	1 3/4 in

### Features:

- Three position power regulation
- Three-piece motor housing

**Drive Size:** 3/4 in

SKU	Cycle Rate	Free Speed	Air Consumption @ Load	Inlet Size
383-2925RBP1TI	1,050 ipm	5,200 rpm	60 CFM	3/8 in (NPT)



## Ingersoll-Rand Pneumatic Ratchet Wrenches

Drive Type: Square  
 Air Consumption: 4 CFM  
 Inlet Size: 1/4 in NPT(F)  
 Control Type: Lever Throttle



SKU	Drive Size	Torque	Free Speed
383-1077XPA	1/2 in	45 ft lb	160 rpm
383-107XPA	3/8 in	45 ft lb	160 rpm
383-109XPA	3/8 in	60 ft lb	300 rpm



## Air Scribe®

Features:

- Adjustable power for a variety of applications and materials such as metals, plastics, ceramics, and glass
- Convertible to a hammer or a light scaler
- Lightweight for easy operation

Inlet Size: 1/4 in NPT(F)  
 Control Type: On/Off  
 Includes: Air Filter; Air Hose; Stylus



SKU	Air Consumption	Noise Level	Vibration	Length
147-9361	2.1 CFM	82 dB	4.2 m/s <sup>2</sup>	8 in

## Air Scribe® Kits

Features:

- Adjustable power for a variety of applications and materials such as metals, plastics, ceramics, and glass
- Convertible to a hammer or a light scaler
- Lightweight for easy operation

Inlet Size: 1/4 in (NPT)  
 Includes: Air Filter Assembly; Air Hose; Anvil, use w/Chisels & Blanks; Carrying Case; Chisel Blank; Flat Chisel; Round Nose Chisel; Stylus, Carbide Tipped



SKU	Air Consumption	Cycle Rate
147-93611	1.1 CFM	13,500 blows/min



## Sioux Force Tools Air Engraving Pens

Features:

- Non-marring cover over leader hose
- High quality stainless steel housing
- Replaceable engraving points

Inlet Size: 1/4 in (NPT)  
 Control Type: Twist Throttle  
 Includes: 45°, 30°, 15° Carbide Tipped Points



SKU	Cycle Rate	Hose Length
672-5980	13,000 blows/min	59 in



## Dynafile® II Abrasive Belt Machines

Features:

- Reach normally inaccessible areas

Free Speed: 20,000 rpm  
 Pressure: 90 PSIG  
 Noise Level [Max]: 80 dB  
 Inlet Size: 1/4 in (NPT)  
 Hose Size: 3/8 in  
 Control Type: Mechanical Variable  
 Applicable Materials: Fiberglass; Glass; Metal; Plastic; Rubber; Stone  
 Includes: 11206 Contact Arm  
 Machining Speed: 4,550 sfpm  
 Air Consumption: 4 CFM; 28 SCFM



SKU	Belt Width	Belt Length	Power Capacity
415-40320	3/4 in	18 in	1/2 hp

## Mini-Dynafile® II Air Powered Abrasive Belt Machines

Features:

- Ideal for working in narrow openings
- Rear exhaust air motor
- Multi-position grinding head pivots 360 degrees

Inlet Size: 1/4 in (NPT)  
 Includes: 15026 Contact Arm; 15118 Drive Wheel



SKU	Belt Width	Belt Length	Free Speed	Pressure	Noise Level [Max]
415-15003	1/2 in	12 in	25,000 rpm	90 psi	80 dB

## The Original Dynafile® Abrasive Belt Machines

Features:

- For use on metal, plastic, fiberglass, composites, rubber, glass and stone
- Easy adjustable motor

Pressure: 90 PSIG  
 Noise Level: 77 dB  
 Inlet Size: 1/4 in (NPT)  
 Hose Size: 3/8 in  
 Applicable Materials: Composites; Fiberglass; Glass; Metal; Plastic; Rubber; Stone  
 Includes: 11218 Contact Arm  
 Machining Speed: 5,800 sfpm  
 Air Consumption: 4 CFM; 31 SCFM



SKU	Belt Width	Belt Length	Free Speed [Max]
415-14000	1/8 in; 1/4 in; 1/2 in	24 in	20,000 rpm



## Dynaflex® Contact Arms

### Features:

- Standard arm on model 14000
- Includes: Contact Wheel Assembly; Platen Pad 11025
- Wheel Material: Rubber
- Wheel Width: 3/8 in
- Belt Width: 1/2 in
- Wheel Dia: 5/8 in



SKU	Belt Length	Length
415-11218	24 in	38,139 in



## Angle Grinders

### Features:

- Rotatable guard
- Ergonomic side handle
- Adjustable rotating guard
- Power Capacity: 4/5 hp
- Handle Type: Lever



SKU	Wheel Dia	Spindle Thread	Free Speed	Air Consumption	Control Type
147-CP9120CRN	4 in	3/8 in - 24	12,000 rpm	21 CFM	Lever

### Features:

- Alloy body
- High performance
- Easy handling
- Left or right hand side handle

Power Capacity: 1.12 hp

Handle Type: Side Rod; Rubber Grip

SKU	Wheel Dia	Spindle Thread	Free Speed [Max]	Air Consumption	Control Type
147-CP9123	7 in	5/8 in - 11	7,500 rpm	40 CFM	Lever Throttle

## Industrial Angle Grinders

### Features:

- Grinding wheel fits a wider range of applications and helps prevent accidents
- Longer life of bevel gears due to constant lubrication

Spindle Thread: 5/8 in - 11



SKU	Wheel Dia	Free Speed	Air Consumption	Length
147-CP3450-12AB5	5 in	12,000 rpm	18 CFM	9.1 in



## Depressed Center Angle Grinders

### Features:

- Patented stainless steel motor controller with industry's only lifetime guarantee
- Self-locking throttle lever prevents accidental operation
- Integral steel guard provides extra strength for added operator protection
- Adjustable ergonomic side handles increase operator control
- Built-in mist lubricator automatically oils motor when tool is started



Spindle Thread: 5/8 in - 11

Inlet Size: 1/2 in (NPT)

Free Speed: 6,000 rpm

Pressure: 90 psi

Hose Size: 3/4 in

SKU	Wheel Dia	Power Capacity	Air Consumption
383-88V60P107	7 in	2 1/10 hp	61 CFM

## G-Series Extended Angle Grinders

### Features:

- Collet Body Wrench
- Big Power in a small package
- Composite housing prevent cold feel for operator comfort
- Dual exhaust capabilities
- Easy to service one nut removal for motor repair
- Ergonomic D Shaped handle designed for operator comfort
- One-nut access for all motor servicing
- Laser-etched product information won't wear off



Inlet Size: 1/4 in NPT(F)

Hose Size: 3/8 in

Control Type: Lever Throttle

SKU	Wheel Dia	Free Speed
383-G2E135RH64	4 in	13,500 rpm

## MAX Angle Grinders

### Features:

- Built-in lubricating wick optimizes the life of the angle gear set by improving lubrication to the bevel and pinion gear set
- Enhanced grip design enables extended usage without fatigue
- Internal governor maximizes speed under load



Inlet Size: 1/4 in

SKU	Wheel Dia	Free Speed	Air Consumption	Length
383-3445MAX	4 1/2 in	12,000 rpm	10 CFM	9.6 in



## Right Angle Grinders

### Features:

- Built-in speed regulator
- Spindle Thread:** 5/8 in - 11
- Inlet Size:** 1/4 in (NPT)
- Hose Size:** 3/8 in
- Length:** 10 in
- Control Type:** Lock-Off Lever Throttle



SKU	Wheel Dia	Free Speed	Air Consumption
672-5268	4 1/2 in	12,000 rpm	13.2 CFM



## Compact Pencil Grinders

### Features:

- Ideal for intricate work
- Good power to size ratio
- Good maneuverability
- Collet Size:** 1/8 in
- Inlet Size:** 1/4 in (NPT)
- Length:** 8 in



SKU	Free Speed [Max]	Air Consumption	Noise Level [Max]	Vibration [Max]
147-CP9104Q	60,000 rpm	7 CFM	74 dB	8.3 m/s <sup>2</sup>

## Angle Die Grinders

### Features:

- Soft grip
- Variable air regulator on top for easy adjustment
- Collet Size:** 1/4 in
- Inlet Size:** 1/4 in (NPTF)



SKU	Free Speed [Max]	Air Consumption	Noise Level [Max]	Vibration [Max]	Hose Size
147-875	22,500 rpm	11 CFM	101.3 dB	3 m/s <sup>2</sup>	3/8 in

## Chicago Pneumatic Straight Die Grinders



### Features:

- Adjustable power regulator
- High power and rubber grip
- Control Type:** Lock-Off Lever Throttle
- Handle Type:** Body Grip

SKU	#	Free Speed [Max]	Noise Level [Max]	Inlet Size
147-872	1	22,000 rpm	100.9 dB	1/4 in (NPTF)

### Features:

- Adjustable power regulator for precise control
- Square handle design for positive grip
- Excellent for cleaning tire moldings, porting and relieving engines, and general high-speed polishing and grinding

SKU	#	Free Speed [Max]	Air Consumption	Noise Level [Max]	Inlet Size
147-860	2	24,000 rpm	10.5 CFM	92.5 dB	1/4 in (NPTF)

### Features:

- Compact and lightweight tool designed for easy maneuverability
- Excellent for high speed blending, smoothing, porting, and deburring in confined areas

SKU	#	Free Speed [Max]	Air Consumption	Noise Level [Max]	Inlet Size
147-876	3	30,000 rpm	12 CFM	101.3 dB	1/4 in (NPTF)

### Features:

- Soft grip
- Variable air regulator on top for easy adjustment

SKU	Free Speed [Max]	Noise Level [Max]	Inlet Size
147-CP9105QB	27,000 rpm	80 dB	1/4 in (NPT)



## 7° Offset Die Grinders

### Features:

- Gearless motor reduces downtime
- Gearless motor also lessens repair expense compared to geared tools
- Collet Size:** 1/4 in
- Spindle Thread:** 3/8 in - 24
- Pressure:** 90 PSIG
- Inlet Size:** 1/4 in (NPT)
- Control Type:** Lever Throttle
- Includes:** Collet
- Power Capacity:** 1/2 hp



SKU	Free Speed [Max]	Air Consumption	Noise Level [Max]	Hose Size
415-52211	18,000 rpm	4 CFM; 28 SCFM	77 dB	3/8 in



## 300 Series Die Grinders 0.25 HP

### Features:

- For automotive and light maintenance applications
- Durable and long lasting, with an all ball bearing construction and precision-machined steel gears
- Self-locking throttle lever prevents accidental starting of motor
- Precision-machined steel gears
- Front exhaust helps keep work surface clean
- Easy-to-use, integral safety-lock throttle lever prevents accidental start-up
- Small and lightweight design provides easy operation greater access to tight spots
- Strong aluminum housing withstands tough operating conditions
- Tool comes with both a 1/4 in and 6mm collets and two wrenches



**Collet Size:** 6 mm; 1/4 in

**Inlet Size:** 1/4 in

**Control Type:** Lever Throttle; Throttle Lever

**Includes:** 1/4 in nd 6mm Collets; Tool

SKU	Free Speed	Air Consumption	Pressure	Noise Level
383-301B	20,000 rpm	3 CFM; 6 CFM	90 psi	92 dB

## 300 Series Die Grinders 0.33 HP

### Features:

- For automotive and light maintenance applications
- Durable and long lasting, with an all ball bearing construction and precision-machined steel gears
- Self-locking throttle lever prevents accidental starting of motor
- Precision-machined steel gears
- Built-in lubricating wick increases angle gear life
- Durable ball-bearing construction improves balance, reduces vibration, and ensures a longer life
- Integral safety-lock throttle lever prevents accidental start-up
- Lightweight, durable and ergonomic composite housing protects tool from cold air and offers greater operator comfort
- Piped-away exhaust optional
- Rear exhaust directs air away from the operator
- Front exhaust helps keep work surface clean



**Collet Size:** 6 mm; 1/4 in

**Inlet Size:** 1/4 in

**Includes:** 1/4 in nd 6mm Collets; Tool

SKU	Free Speed	Air Consumption	Pressure	Noise Level
383-302B	18,000 rpm	3 CFM; 6 CFM	90 psi	90 dB

## 301 Series Die Grinders 0.25 HP

### Features:

- It can be used with all types of accessories for porting, weld breaking, and smoothing sharp edges, as well as deburring, polishing, and grinding
- Superior maneuverability
- Safety lever prevents accidental starts
- Front exhaust helps keep work surface clean
- Versatile and reliable
- Easy-to-use, integral safety-lock throttle lever prevents accidental start-up
- Small and lightweight design provides easy operation greater access to tight spots
- Strong aluminum housing withstands tough operating conditions
- Tool comes with both a 1/4 in and 6mm collets and two wrenches



**Collet Size:** 6 mm; 1/4 in

**Inlet Size:** 1/4 in; 1/4 in NPT(F)

**Control Type:** Lock-Off Lever Throttle; Throttle Lever

**Includes:** 1/4 in nd 6mm Collets; Tool

SKU	Free Speed	Air Consumption	Pressure	Noise Level
383-307B	27,000 rpm	3 CFM; 6 CFM	90 psi	83 dB

## 301 Series Die Grinders 0.33 HP

### Features:

- A general purpose tool designed for porting, light weld grinding, and breaking sharp edges
- Ball bearing construction for longer tool life
- Self-locking throttle lever
- Positive grip collet chuck
- Built-in lubricating wick increases angle gear life
- Durable ball-bearing construction improves balance, reduces vibration, and ensures a longer life
- Integral safety-lock throttle lever prevents accidental start-up
- Lightweight, durable and ergonomic composite housing protects tool from cold air and offers greater operator comfort
- Piped-away exhaust optional
- Rear exhaust directs air away from the operator
- Front exhaust helps keep work surface clean
- Ball bearing construction for longer tool life



**Collet Size:** 6 mm; 1/4 in

**Inlet Size:** 1/4 in; 1/4 in NPT(F)

**Control Type:** Lock-Off Lever Throttle; Throttle Lever

**Includes:** (2) Collet Wrenches; 1/4 in nd 6mm Collets; Tool

SKU	Free Speed	Air Consumption	Pressure
383-308B	25,000 rpm	3 CFM; 7 CFM	90 psi



### 5000MAX Series Die Grinders

**Features:**

- Lightweight yet durable design
- All ball bearing construction
- Safety release throttle
- Ergonomic and durable composite housing
- 0.4 hp and 20,000/25,000 RPM motor delivers the power you need for the toughest jobs
- Enhanced grip design and low-profile throttle lever provides for extended run time without fatigue
- MAX Comfort
- MAX PERFORMANCE
- MAX POWER
- Spindle lock feature on the 5102MAX allows for faster abrasive changeovers and lube free design eliminates contamination of work environment
- All ball bearing construction

**Collet Size:** 6 mm; 1/4 in  
**Air Consumption:** 3 CFM; 6 CFM

**Inlet Size:** 1/4 in; 1/4 in NPT(F)  
**Control Type:** Lever Throttle; Throttle Lever  
**Pressure:** 90 psi



SKU	Free Speed	Noise Level
383-5102MAX	20,000 rpm	84.1 dB
383-5108MAX	25,000 rpm	83.3 dB



### 1/4" Pneumatic Die Grinders

**Features:**

- Durable precision machined hardened steel gears
- Heavy duty ball bearing construction for vibration free performance
- Lightweight yet powerful and compact design
- Variable speed throttle control with self closing lever

**Collet Size:** 1/4 in  
**Inlet Size:** 1/4 in (NPT)  
**Control Type:** Mechanical Variable



SKU	Power Capacity	Free Speed	Pressure
825-JSM-512A	1/4 hp	22,000 rpm	90 psi

### Jet® Pneumatic Die Grinders

**Features:**

- Lightweight yet powerful and compact design
- Heavy duty ball bearing construction for vibration free performance
- Durable precision machined hardened steel gears

**Collet Size:** 1/4 in  
**Inlet Size:** 1/4 in (NPT)  
**Control Type:** Mechanical Variable



SKU	Power Capacity	Free Speed	Pressure	Vibration
825-JSM-522A	1/4 hp	22,000 rpm	90 psi	2.2 m/s2



### Pencil Die Grinders



**Features:**

- Built-in speed regulator
  - Remote exhaust
- Collet Size:** 1/8 in  
**Inlet Size:** 1/4 in (NPT)  
**Length:** 5.3 in  
**Control Type:** Twist Throttle  
**Includes:** 60 in. Hose w/Hose Protector

SKU	Free Speed	Air Consumption
672-5978A	54,000 rpm	16.8 CFM
672-5979A	70,000 rpm	21.2 CFM

### Sioux Force Tools Right Angle Die Grinders

**Features:**

- Built-in speed regulator
- Collet Size:** 1/4 in  
**Inlet Size:** 1/4 in (NPT)  
**Control Type:** Lock-Off Lever Throttle



SKU	Features	Free Speed	Length
672-5055A	• Aluminum housing	20,000 rpm	5 1/2 in
672-5056	• Rear exhaust	16,000 rpm	7 1/2 in

### Sioux Force Tools Straight Die Grinders

**Features:**

- Built-in speed regulator
  - Aluminum housing
- Collet Size:** 1/4 in  
**Inlet Size:** 1/4 in (NPT)  
**Housing Material:** Aluminum  
**Control Type:** Lock-Off Lever Throttle



SKU	Free Speed	Length
672-5054A	22,000 rpm	6 1/2 in



### Sioux Tools Straight Die Grinders

**Features:**

- Built-in speed control
  - Front exhaust
  - Ergonomic grip
  - Lock-off lever throttle
  - Drop in motor assembly
  - Ease of maintenance
- Collet Size:** 1/4 in  
**Inlet Size:** 1/4 in (NPT)  
**Control Type:** Lock-Off Lever Throttle  
**Handle Type:** Body Grip; Ergonomic Grip



SKU	Free Speed	Pressure	Length
672-SDG10S25F	25,000 rpm	90 PSIG	7 1/2 in; 7.52 in



## Dynorbital-Spirit™ Sanders

### Features:

- Custom engineered composite cylinder
- Double row balancer bearing keeps out contaminants
- Can be converted easily to self-generated or central vac model for hook-up to dust collection system

**Spindle Thread:** 5/16 in - 24

**Pressure:** 90 PSIG

**Noise Level [Max]:** 75 dB

**Inlet Size:** 1/4 in (NPT)

**Hose Size:** 1/4 in

**Control Type:** Lever Throttle

**Includes:** Urethane, Weight-Mated, Non-Vac Pad



SKU	Disc/Pad Dia	Orbit Dia	Free Speed [Max]	Air Consumption
415-59020	5 in	3/16 in	12,000 rpm	2 CFM; 14 SCFM



## Angle Sanders

**Inlet Size:** 1/4 in

**Hose Size:** 3/8 in

**Control Type:** Lever Throttle

### Features:

- Ball bearing construction for long life
- Heavy duty motor handles tough jobs

**Air Consumption:** 8 CFM

**Air Consumption @ Load:** 23 CFM

**Noise Level [Max]:** 99.3 dB



SKU	Disc/Pad Dia	Spindle Thread	Free Speed
383-313A	7 in	5/8 in - 11	5,000 rpm

### Features:

- Low vibration
- Dependable performance
- Balanced ball bearing construction
- Adjustable built-in regulator for positive speed control

**Air Consumption:** 4 CFM

**Air Consumption @ Load:** 17 CFM

**Noise Level [Max]:** 85.6 dB

SKU	Disc/Pad Dia	Spindle Thread	Power Capacity	Free Speed
383-311A	6 in	5/16 in - 24	1/4 hp	10,000 rpm



## Carbide-Tipped Stylus Points

### Features:

- For writing and marking

SKU	Height	Length	Width
147-P054177	0.4 in	1.8 in	0.4 in



## Grooved Barrel Heavy Duty Air Chippers

### Features:

- Strong forged steel throttle handle for durability
- Plated piston for reduced wear and extended life
- Barrel is grooved for use with retainers
- Long nozzle section for long life

**Bit/Blade Mounting Type:** Round Nozzle

**Bore Dia:** 1 1/8 in

**Pressure:** 90 psi

**Inlet Size:** 3/8 in

**Hose Size:** 1/2 in

**Control Type:** On/Off - Outside Trigger



SKU	Shank Dia	Stroke Length	Cycle Rate (blows/min)
383-2A2SA*	0.68 in	2 in	2,300

\*Air Consumption: 28 CFM

## 95 Series Diggers

### Features:

- Multiple latch configurations
- Extra long nozzles for long life
- Three finger trigger
- Great for heavier digging, foundation work, pipeline and utility work as well as heavier concrete, bridge and brick demolition

**Inlet Size:** 3/8 in (NPT)

**Handle Type:** Back D-Handle



SKU	Chuck Size	Cycle Rate	Pressure	Air Consumption
383-95LA1	7/8 in x 3 1/4 in	1,850 blows/min	90 psi	47 CFM



## Needle Scaler/Weld Flux Chippers

### Features:

- Quick chisel changing
- Steel body weld flux chipper

**Shank Type:** Square

**Noise Level [Max]:** 99 dB

**Inlet Size:** 1/4 in (NPT)

**Handle Type:** Lever



SKU	Cycle Rate	Pressure [Max]	Air Consumption	Length
147-CP7120	4,600 blows/min	90 psi	15.5 CFM	13 in





### Pneumatic Needle Scaler Kits

**Features:**

- Long nozzle section extends retainer life and permits the use of a variety of accessories
- Positive chisel retainer is simple to operate
- Strengthened head block holds up under the most extreme conditions

**Pressure:** 90 psi

**Inlet Size:** 1/4 in NPT(F)

**Hose Size:** 5/16 in

**Handle Type:** Swan Neck, Outside Trigger

**Includes:** (1) Extra Set of NS11-22-19 Needles 5 in.; (1) Set of NS11-122-19 Needles 7 in.; (1) WF-14A-6-1/8 Angle Chisel; (1) WF-14B-6-1/8 Angle Chisel; (1) WF-14F-7 Flat Chisel; Carrying Case; Complete NS11A Needle Att. w/5 in. Long Needles



SKU	Stroke Length	Cycle Rate	Air Consumption
383-182K1	1 1/16 in	4,000 blows/min	13 CFM

### Pneumatic Needle Scalers

**Inlet Size:** 1/4 in NPT(F)

**Control Type:** On/Off - Lever

**Features:**

- Adjustable bayonet-type needle housing lock allows adjustment without special tools
- Choice of three needle materials permits custom selection for various surfaces
- Rubber-faced throttle valve means positive sealing
- Tested and approved in accordance with MIL-S-23492A (Ships)
- Precision heat-treated needles for maximum performance

**Hose Size:** 5/16 in



SKU	Stroke Length	Cycle Rate	Air Consumption
383-172LNA1	5/16 in	5,500 blows/min	12 CFM
383-182LNA1	1 1/16 in	4,000 blows/min	13 CFM

**Features:**

- For surface preparation work involving the cleaning or removal of paint, rust, dirt, or weld slag, the 125 is a durable, dependable, economical solution
- 19 needles, each being an 1/8"

**Air Consumption:** 8 CFM

**Hose Size:** 5/16 in

SKU	Stroke Length	Cycle Rate
383-125	1 1/8 in	4,600 blows/min

**Features:**

- Pistol grip needle scaler with lever throttle
- Adjustable bayonet type oval front tube
- For removing unwanted surface deposits such as rust, weld splatter, slag, paint, and marine repairs and maintenance

**Air Consumption:** 5.5 CFM

SKU	Stroke Length	Cycle Rate
383-170PG	1.4 in	3,000 blows/min

### Pneumatic Scalers

**Features:**

- Long nozzle section extends retainer life and permits the use of a variety of accessories
- Positive chisel retainer is simple to operate
- Strengthened head block holds up under the most extreme conditions

**Inlet Size:** 1/4 in NPT(F)

**Control Type:** Lever Throttle

**Pressure:** 90 psi

**Hose Size:** 5/16 in



SKU	Stroke Length	Cycle Rate
<b>Air Consumption: 13 CFM</b>		
383-182L	1 1/16 in	4,000 blows/min



### Needle Scaler/Flux Chippers

**Features:**

- Heat-treated barrels and pistons for extended tool life
- Needle scalars can be used either as a scaler or chipper

**Pressure:** 90 psi

**Air Consumption:** 4 CFM

**Inlet Size:** 1/4 in (NPT)

**Hose Size:** 3/8 in



SKU	Stroke Length	Cycle Rate (blows/min)	Length
825-F-25NS	7/8 in	4,000	12 in
825-JSG-9121NS	1 1/8 in	4,600	12 1/2 in



### Needle Sets

**Features:**

- 3 Chisel types—angle, straight and flat
  - Complete NS11A needle attachment with 5 in long needles
  - Durable vinyl carrying case
  - One set of NS11-122-19 extended steel needles, 7 in long
- Material:** Steel




SKU	Quantity
383-NS11-122-19	19 per set

## JET<sup>®</sup> Scaler Needles

**Features:**

- Package of replacement needles



SKU	Dia.	Length	Quantity	Width
825-N307	3 mm	12 in	19 per pack	3 1/2 in



## Air Hammers

**Features:**

- Professional touch trigger for total control
- Long-life tool with a tough one piece alloy barrel
- Easy to maintain, with an "easy out" throttle valve assembly



**Air Consumption:** 3 CFM

**Air Consumption @ Load:** 15 CFM

**Inlet Size:** 1/4 in NPT(F)

**Hose Size:** 3/8 in

SKU	Shank Dia	Stroke Length	Cycle Rate	Pressure
383-121-K6*	0.401 in	3 1/2 in	2,000 blows/min	90 psi

**Features:**

- The economical air hammer for fast cutting action, especially for medium exhaust system, panel cutting, and general repair work
- Longer life alloyed steel barrel and heat-treated piston

**Air Consumption:** 3 CFM

**Air Consumption @ Load:** 15 CFM

**Inlet Size:** 1/4 in

**Hose Size:** 3/8 in

SKU	Shank Dia	Stroke Length	Cycle Rate	Pressure
383-116	0.401 in	2 5/8 in	3,500 blows/min	90 psi

\* Includes: (6) Chisels; Blow Molded Plastic Case

## Ingersoll-Rand Rivet Busters

**Features:**

- New, improved piston with shock-resistant material
- Piston and barrel design provides better air pocket cushion between piston and accessory for maximum accessory life
- Lock assembly locks retainer nut onto barrel for positive accessory retention
- Forged Steel Handle
- 9001 uses Jumbo Four Side Tools



**Inlet Size:** 1/2 in

SKU	Stroke Length	Cycle Rate	Air Consumption
383-9001	9 in	900 blows/min	40 CFM



## Pneumatic Tampers

**Features:**

- Compact for backfill tamping between foundations and around other jobsite obstructions
- Dual action sand wiper front end keeps dirt out of barrel
- Plated piston for excellent wear resistance
- Built-in lubricator and muffler
- 7/8" tapered rod

**Stroke Length:** 4 in



SKU	Cycle Rate	Air Consumption
383-341A2M	1,550 blows/min	29 CFM



## Heavy Duty Mechanical Tool Balancers

**Features:**

- Enable all types of portable tools weighing up to 25 pounds to be suspended within easy reach of the operator
- Prevent damage to the tools by eliminating accidental dropping of the suspended tool



SKU	Capacity Wt	Cable Length
166-BL02	1 - 3 1/2 lb	8 ft