

Battery Chargers & Starting Systems	424	Gage Glass.....	426
Battery Clamps	424	Measuring Cans.....	424, 425
Booster Cables	424	Plastic Sheeting.....	425
Copper Tubing.....	426	See Snakes, Transmitters, & Locators	428, 429
Drain Cleaners	428	Shim Sets	426
Fiberglass Repair Kits.....	425	Shims.....	426
Fittings.....	425	Tarps.....	425
Funnels.....	424	Valves	426



ASSOCIATED

Heavy Duty Fast Chargers

Boost Rating: 600 A
 Cranking Assist Rating: 280 A
 A.C. Leads: 6-1/2 ft, 16-3 AWG
 D.C. Leads: 7 ft, 4 AWG
 Clamp Rating: 500 A

- Features:**
- Automatic 90-minute timer with "Hold"
 - AC and DC circuit overload protection
 - Fan cooled



SKU	Voltage	Amps
075-6006	6 V; 12 V; 24 V	30 A; 65 A; 75 A



Heavy Duty Battery Clamps

- Features:**
- Excellent electrical and physical properties
 - Hammer-on copper connection
 - Heavy duty tension spring gives positive connection on front and side
 - Vinyl insulation that is highly resistant to oil, acid, abrasion, chemicals and ozone
 - Color coded

Jaw Material: Steel

Kit Parts

Style: Standard

Cable/Wire Size [Min]: 1 - 3 /0 AWG



SKU	Amps	Jaw Opening	Color
102-67120B	600 A	1 in	Black
102-67120R	600 A	1 in	Red

Anchor Brand Booster Cables

- Features:**
- Ultra flexible cable, chemical and abrasion resistant, sequentially marked every foot
 - Made in USA
- Cable/ Wire Size:** 4 AWG



SKU	Amps	Length
100-JUMPERCABLES-15FT	600 A	3 3/4 in
100-JUMPERCABLES-20FT	600 A	3 1/2 in

ASSOCIATED

Booster Cables

- Features:**
- Has T-94 jacket which is flexible to -40°F
- Cir. Mil. Copper:** 41,300
Clamp Rating: 500 A
Side Terminal Adapters: Yes
Flexi-Spring: Yes



SKU	Cable/ Wire Size
075-6160	4 AWG



Automotive Booster Cables

- Features:**
- No-Tangle™ Booster Cable
 - T-Prene® Jacket remains flexible even in extreme cold temperatures
 - Wire jacket material is oil, chemical, and water resistant
- Amps:** 500 A
Conductor Size: 4/1 AWG
Jacket: Red



SKU	Length
172-08660	4 3/4 in
172-08666	16 ft

Coleman Cable Booster Cables

- Features:**
- No-Tangle™ Booster Cable
 - T-Prene® Jacket remains flexible even in extreme cold temperatures
 - Wire jacket material is oil, chemical, and water resistant
- Amps:** 500 A
Jacket: Black



SKU	Conductor Size	Length
172-08760	4/1 AWG	20 ft
172-08766	4/1 AWG	3 3/4 in
172-08860	2/1 AWG	3 1/2 in



Funnels

Features:

- Capacity indicates what the funnel will hold when the outlet is blocked

Material: Galvanized Steel

SKU	#	Capacity Vol.	Dia.	Tip Dia
570-75-002	1	6 qt	9 in	1 1/4 in
570-75-004	2	8 qt	9 1/2 in	1 in

Galvanized Measures

Features:

- Deluxe measures with spill proof tops
- Angled spouts for ease of pouring
- Rolled edge, easy grip handles
- Calibrated fill line
- Available in both rigid spout with 7/8" OD top and flexible spout with 1/2" OD tip models

Outlet Type: Flexible Spout

Handle Position: Back



SKU	Capacity Vol.	Height
570-75-444	4 qt	11 in

Painted Measuring Cans

Features:

- Designed for one hand operation
- Thumb operated valve controls flow, flip action locks valve open
- Flexible metal spout with tapered tip s wings into the necessary angle for hard to reach jobs
- Recessed bottoms drain fully and guard against puncture
- Rolled edge top helps prevent oil spillage

Outlet Type: Flexible Spout

Spout Length: 14 in



SKU	Capacity Vol.	Height	Handle Position
570-75-664	4 qt	9 1/2 in	Back
570-75-668	8 qt	14 in	Back; Top



Fiberglass Repair Kits

Features:

- Everything needed for the Do-It-Yourself
- Easy How-To Directions, fiberglass resin, liquid hardener, plastic spreader, fiberglass cloth, mixing stick and mixing tray

Includes: Includes fiberglass resin, spreader; mat, and hardener.



SKU	Capacity Vol.
104-422	1 qt




Poly-Cover Plastic Sheets

Features:

- Guaranteed to be full weight and thickness

Length: 100 ft

Material: Plastic



SKU	Thickness	Width	Color
795-4X10-C	4 mil	10 ft	Clear
795-4X20-C	4 mil	20 ft	Clear
795-6X10-C	6 mil	10 ft	Clear
795-6X20-B	6 mil	20 ft	Black
795-6X20-C	6 mil	20 ft	Clear
795-6X32-B	6 mil	32 ft	Black
795-6X40-B	6 mil	40 ft	Black



Multiple Use Tarpaulin

Material: Polyethylene

Thickness: 5 mm



SKU	Width	Length
101-0810	8 ft	10 ft
101-1012	10 in; 10 ft	12 ft
101-1216	12 in; 12 ft	16 ft
101-1220	12 in; 12 ft	20 ft
101-1620	16 in; 16 ft	20 ft
101-2020-TARP	20 in; 20 ft	20 ft
101-1020	10 ft	20 ft
101-1824	18 in; 18 ft	24 ft
101-1525	15 ft	25 ft
101-2030	20 in; 20 ft	30 ft
101-2040	20 in; 20 ft	40 ft
101-3040	30 in; 30 ft	40 ft
101-4060	40 in; 40 ft	60 ft



Protective Tarps

Features:

- Durable canvas
- Water- and mildew-resistant

Resistance: Mildew; Water



SKU	Capacity Wt.	Width	Length	Material	Color
103-92561	12 oz	8 ft	10 ft	Canvas	Brown
103-92552	10 oz	10 ft	12 ft	Tarpaulin	Green
103-92562	12 oz	10 ft	12 ft	Canvas	Brown
103-92553	10 oz	12 ft	16 ft	Tarpaulin	Green
103-92564	12 oz	16 ft	20 ft	Canvas	Brown



Boss Stems

Features:

- Use with Boss Clamps
- Connection Type:** Male/Male
Male Thread: 2 in (NPT)
Male Plain: 2 in
Body Material: Malleable Iron



SKU	Height
238-MS26	6 7/8 in

GEARENCH Petol Sight Glasses

Body Material: Polycarbonate

SKU	Dia.	Length	Operating Pressure
306-SG0500	2 in	8 in	500 psi
306-SG0500-3	3 in	8 in	500 psi
306-SG0500-4	4 in	0 in; 8 in	500 psi
306-SG1000	2 in	8 in	1,000 psi



Cerro™ Seamless Copper Tubing

Features:

- Seamless copper tube produced to special internal cleanliness and dehydration requirements
- Preferred material for use with most refrigerants

Length: 50 ft

Material: Copper



SKU	Outside Dia
136-1450R	1/4 in
136-3850R	3/8 in

GAGE GLASS Gage Glass

Features:

- Made especially for moderate pressure service on boilers, vats & tanks, coffee urns, where pressures do not exceed the maximum recommended
- No corrosion

Material: Glass



SKU	Length	Operating Pressure
055-58X48RL	48 in	165 psig
055-58X36RL	36 in	205 psig



Brass Shim Stock Rolls

Thickness: 0.01 in

Material: Brass

Thickness Tolerance (-) [Min]: 0.0008 in

Thickness Tolerance (+) [Max]: 0.0008 in

Hardness: 56 Rb - 68 Rb Tensile

Strength: 57,000 psi - 67,000 psi

SKU	Width	Length
605-17415	6 in	100 in



GEARENCH[®] PETOL™ Run Ticket Boxes with Hinged Lid

Features:

- Eliminates the expense of tracking down lost or unreadable tickets
- Protects tickets, keeping them safe and dry in a constant location on the well site
- Box is made from durable polyethylene
- Clear plastic window allows easy ticket visibility
- Spring-load

Depicted Text: "Run Ticket Box"

Material: Polyethylene



SKU
306-RTB1

Slotted Shim Assortment Kits

Thickness: 0.001 in; 0.002 in; 0.003 in; 0.004 in; 0.005 in; 0.01 in; 0.015 in; 0.02 in; 0.025 in; 0.05 in; 0.075 in; 0.1 in; 1/8 in

Thickness: 0.001 in

Thickness: 1/8 in

Material: Stainless Steel

Shape: Slotted

Includes: Metal Box



Features:

- A new way to level large, heavy-duty motors, pumps and equipment
- Reduces machine down time
- Shims marked with thicknesses in decimal and metric

SKU	Width	Length	Includes
605-42935	8 in	8 in	4 Pieces of Each Thickness

Features:

- Slotted shim is the best way to solve alignment and leveling problems on motors, pumps generators and other plant machinery
- Shims marked with thickness in decimal and metric
- Convenient assortment to carry to job site

SKU	Width	Length	Includes
605-42900	2 in	2 in	20 Pieces of Each Thickness
605-42910	3 in	3 in	20 Pieces of Each Thickness
605-42920	4 in	4 in	20 Pieces of Each Thickness
605-42930	5 in	5 in	20 Pieces of Each Thickness



Water Cooler Replacement Spigots

Features:

- OEM replacement part
- Easy to install
- For use with Rubbermaid 3 gal to 10 gal Rubbermaid Water Coolers

Finish: Black; White



SKU
325-2B87T8-WHT




Short Handle Faucets

Features:

- Machined and lapped brass faceplate for smooth operation and perfect seal
- 45-60 degree discharge for optimum flow control
- Short, sturdy, two inch metal stamped handle provides easy flow control
- Brass faceplate designed for oval discharge to ensure no splashing

Body Material: Cast Iron

Designated Fluid: Heavy Oils; Light Grease; Varnish; Molasses; Honey; Cream; Non-Flammable Viscous Fluids



SKU	Inlet Size
687-V0075200	2 in (NPT)

RIDGID

Model K-7500 Drain Cleaners

Features:

- The performance, cable control, durability, and maneuverability demanded by professionals
- Ideal for any tough jobs, such as roots - up to 250' - Recommend 5/8" cable for 3" to 6" drain lines up to 250'
- Recommend 3/4" cable for 4" to 10" drain lines up to 250'
- Powerful yet quiet, 4/10 Hp universal motor and gearbox bear down as cutter engages tough obstructions
- Provides audible and visual signal to operator
- Inner-drum and ball bearing distributor arm work with motor/gearbox system to recude chance of cable flip-over
- Main and inner drums won't rust, split, or dent - and clean easily for professional appearance; main drum holds up to 125' of 3/4" cable or 150' of 5/8" cable
- Powerful autofeed mechanism has grease fittings and an open design for for easy maintenance; advances and retrieves cable up to 22' per minute
- Patented two position stair climber eases transport and loading
- Narrow profile allows machine to fit through bathroom doors
- For tools and cables for K-7500 refer to model K-7500 accessory chart



Voltage: 115 V

Speed: 200 rpm

Pipe Diam: 3 in - 10 in

Includes: Leather Gloves, Tool Box, Hex Key; T-403 3 in. P-Trap Cutter; T-406 Spear Blade; T-407 Retrieving Auger; T-408 Sawtooth Cutter; T-411 2 in. Double Cutter; T-413 3 in. Double Cutter; T-414B 4 in. Double Cutter - (Blade Only); T-416B 6 in. Double Cutter (Blade Only); T-468 3/4 in. Flexible Leader

SKU	Model No.
632-60052	K-7500 w/C-100

Cables and Flexible Leaders

Catalog No.	Model No.	Description	Weight lb. kg
92460	C-25	25' I.C. Cable (7.6m)	24 10.9
92465	C-26	50' I.C. Cable (15.2m)	43 19.5
92470	C-27	75' I.C. Cable (22.9m)	63 28.6
42647	C-24	100' I.C. Cable (30.5m)	84 38.1
58193	C-24HC	100' Hollow Core (30.5m)	52.75 23.9
92475	C-28	25' I.C. Cable (7.6m)	30 13.6
92480	C-29	50' I.C. Cable (15.2m)	60 27.2
41212	C-75	75' I.C. Cable (22.9m)	93 42.5
41897	C-100	100' I.C. Cable (30.5m)	122 55.3
47427	C-75HC	75' Hollow Core (22.9m)	75 34.0
47432	C-100HC	100' Hollow Core (30.5m)	100 45.5
92555	T-458	1/4" x 2' Leader	1.90 0.85
92560	T-468	1/4" x 2' Leader	2.75 1.25
44122	-	1/4" Pigtail	2.5 1.13
44117	-	1/4" Pigtail	3.5 1.59

Accessories

Catalog No.	Model No.	Description	Weight lb. kg
60042	A-7534D	Drum Assembly w/1/4" Pigtail	31 14
61107	A-7558D	Drum Assembly w/1/4" Pigtail	30 13.6
60047	A-75DR	Drum Only	20 9
60032	A-75PF	Auto Feed Assembly	10 4.5
60037	-	Auto Feed Spacers	-
41992	-	C-100 IC Kit w/Tools 1/4" x 100'	-
49032	-	Front Guide Hose Assembly	2.8 1.3
31487	A-7570	1/4" Repair Splicer	1.5 43
92805	A-6682	1/4" Male Coupling	1 28
92810	A-6683	1/4" Female Coupling	2 57
31492	A-7571	1/4" Repair Splicer	2 56
92880	B-6840	1/4" Male Coupling	1 28
92885	B-6841	1/4" Female Coupling	2 57
41927	-	Pair of Work Gloves Leather	5 0.2
70032	-	Pair of Work Gloves PVC	5 0.2
59360	A-3	Tool Box	5 2.3
59982	-	Cable Rust Inhibitor 1 QT.	2.5
59987	-	Cable Rust Inhibitor 1 GAL.	8.5

Tools and Replacement Blades - Fits C-24, C-25, C-26, C-27, C-28, C-29, C-75, C-100, C-24HC, C-27HC, C-75HC and C-100HC

Catalog No.	Model No.	Description	Replacement Blade(s)	Holder
92485	T-403	P-Trap Cutter, 3"	92835	92900
92490	T-404	P-Trap Cutter, 3 1/2"	92840	92900
92495	T-406	Grease Blade	92850	92915
92500	T-407	Retrieving Auger	-	-
92505	T-408	Sawtooth Cutter	92890	92915
51762	T-409	H-D Butt Auger	-	-
92510	T-411	Double Cutter, 2"	92815	92905
92515	T-412	Double Cutter, 2 1/2"	92820	92905
92520	T-413	Double Cutter, 3"	92825	92910
92525	T-414	Double Cutter, 4"	92830	92910
92530	T-416	Double Cutter, 6"	92855	92910
92535	T-432	3-Blade Cutter, 2"	92860	92895
92540	T-433	3-Blade Cutter, 3"	92865	92895
92545	T-434	3-Blade Cutter, 4"	92870	92895
92550	T-436	3-Blade Cutter, 6"	92875	92895

Micro CA-100 Handheld Inspection Cameras

Features:

- Comfortable pistol-grip design, one-hand controls, and large LCD color screen make it easy to detect and diagnose the unreachable
- New RIDGID micro CA-100 Inspection Camera allows you to perform more detailed visual inspections in even harder-to-reach areas



Monitor Type: 3.5 in Color LCD

Waterproof Depth: 10 ft

Lighting: 4 Adjustable LED's

Includes: (4) AA Batteries; 3 ft. RCA Video Out Cable; Hook; Magnet Attachments; Mirror

SKU	Cable Length
632-36738	3 ft

NaviTrack Scout Locators

Features:

- The NaviTrack Scout Locator is designed to solve the most demanding remote transmitter (sonde) locating issues using multi-directional locating technology
- This locator verifies the locate position using a micro-mapping display to mark distinctive poles in front of and behind the target, ensuring an accurate locate
- Depth is automatically calculated and displayed when over the target
- This locator verifies the locate position using a micro-mapping display to mark distinctive poles in front of and behind the target, ensuring an accurate location



Battery Type: 4 C-Cell Batteries

Frequencies: 512Hz; Line Trace - 512 Hz, 8 kHz and 33 kHz; Passive AC Line Trace - 60 Hz, 50 Hz; Sonde - 512Hz, 640 Hz and 33 kHz

Includes: Instructional DVD; Hard plastic carry case, surface markers and clip, instructional DVD, four C-cell batteries; 4 C-cell batteries; Hard plastic carry case; Surface Markers and Clip

Power Source: C-Cell Batteries

SKU	Run Time
632-19238	24 h

RIDGID

SeekTech SR-20 Utility Locators

Features:

- A lightweight yet rugged receiver that provides all the information needed for faster, more accurate locates
- Features easy to use target line and guidance arrows, and proximity signal and signal strength readings to help with difficult locates

Frequencies: Sonde - 512 Hz; Active Line Trace: 128Hz, 1kHz, 8kHz, 33kHz, 51kHz, 93kHz, 200kHz, 262kHz; Passive Power Trace: 50Hz, 60Hz, <4 kHz; Passive Radio Trace: 4kHz - 15kHz, 15kHz - 36kHz

Includes: (4) C-Cell Batteries

Power Source: C-Cell Batteries



SKU
632-21893

SeekTech SR-60 Utility Locators

Features:

- Can trace any frequency for 10Hz to 490,000 Hz, can energize lines and sondes simultaneously
- The fastest, easiest, most versatile receiver available

Frequencies: Sonde - 512 Hz; Active Line Trace: 128Hz, 1kHz, 8kHz, 33kHz; Sonde Frequencies: 16Hz, 512Hz, 640Hz, 850Hz, 8kHz, 16kHz, 33kHz

Includes: (4) C-Cell Batteries

Power Source: C-Cell Batteries



SKU
632-22163

SeekTech ST-305 Line Transmitter

Features:

- SeekTech ST-305 line transmitter lets you energize metallic lines for tracing
- Lightweight and compact transmitter that delivers up to 5 Watts of power
- Can transmit two frequencies simultaneously
- Audio feedback confirms a good circuit before beginning a trace

Frequencies: Direct Connect: 1 kHz, 8 kHz, 33 kHz, 93 kHz; Induction: 1 kHz, 8 kHz, 33 kHz, 93 kHz



SKU
632-21898

SeekTech ST-510 Line Transmitters

Features:

- SeekTech ST-510 Line Transmitter is compatible with competitors equipment and the LCD display provides instant visual feedback on line resistance and current flow

Frequencies: Direct Connect: 128Hz, 1kHz, 8kHz, 33kHz, 262kHz; Induction: 1kHz, 8kHz, 33kHz, 292kHz

Includes: (8) C-Cell Batteries

Power Source: C-Cell Batteries



SKU
632-21903